



HE31930A140A0004AP

Specifications:		UnCased		Wet Coil -Air Pressure Drop (in inches)								Weights	Dimensions	
Slab Num	Nom	CFM	Face Vel.	13	14	15.5	17	20	20.5	23.5	25.12		A	14"
E31	18	600	224		0.22							24	B	19.5"
	24	800	299		0.25								C	13"
	30	1000	375		0.29									

Highlighted rows are not suitable for downflow configuration.

H	E31	9	30	A	140	A	00	04	AP
Color- Embossed				TX Valve					
Slab Number- Copper Slab				Product Code- Left-hand uncased					
Metering Device- Non-bleed HP-A/C TXV (R-410A)				Height- 13					
Nominal MBTUH- 2.5 Tons				Upper Notch- Uncased					
Depth- 19.5				Width- 14"					

Product Features

MICROBAN antimicrobial additive to inhibit the growth of mold and mildew in the drain pan.

HydroTEC low water retention drain pan.

UV resistant drain pans are molded of high temperature (450 deg. F) engineered polymer.

Coils are air pressure tested at 500 psi, leak tested with helium, sealed with rubber plugs, then charged with dry air.

Liquid line refrigerant connections are 3/8" ODF.

Suction line refrigerant connections are 3/4" ODF (A-Coil 18-36 size models) or 7/8" ODF (A-coil 42-60 size models & all Horizontal Slab Coils).

Cased coils have heavy gauge embossed galvanized cabinets fully lined with 5/8" foil faced insulation.

All A-Coils are upflow or downflow capable.

All multi-position coils are upflow, downflow, and left or right airflow capable.

Enhanced refrigerant pipe grommets: secure, tight, and easy to install.

Intertech lab tested 1% or less cabinet air leakage for better efficiency.

Foam drain seal for reduced air leakage.

All multi-position coils are field convertible from horizontal right-to-left airflow and horizontal left-to-right airflow.

Dual 3/4" FPT condensate drains on front-left and front-right side of drain pans.