



# MATERIAL SAFETY DATA SHEET

**Husky Green Fin Primer**

Part No. B6277CT (Aerosol)  
Revision 1 ♦ June 4, 2012  
Page 1 of 8

CONFORMS TO THE GLOBALLY HARMONIZED SYSTEM (GHS), ANSI Z400.1-2004, EU DIRECTIVE 91/155/EEC & 99/45/EC, OSHA 29 CFR 1910.1200, NOHSC:2011(2003), AND CANADIAN CPR

## Section 1 • PRODUCT AND COMPANY IDENTIFICATION • Section 1

Product Numbers *B6277CT*  
 Product Name *Husky Green Fin Primer*  
 Synonyms *None*  
 Products Uses *For increased coating adhesion*  
 Revision Number *1*  
 Revision Date *June 4, 2012*  
 Print Date *June 13, 2012*

**24 hr Emergency  
Phone Number**

**800-255-3924**  
(Chem-Tel – Contract #MIS001566)

| MANUFACTURER INFORMATION |  | DISTRIBUTOR INFORMATION |   |
|--------------------------|--|-------------------------|---|
| Company Name             |  | Company Name            | <i>Bronz-Glow Technologies</i>                      |
| Address                  |  | Address                 | <i>175 Bronz-Glow Way<br/>St Augustine FL 32095</i> |
| Phone Number             |  | Phone Number            | <i>904-825-0175</i>                                 |
| Fax Number               |  | Fax Number              | <i>904-825-0122</i>                                 |

## Section 2 • HAZARDS IDENTIFICATION • Section 2

|                               |  |
|-------------------------------|--|
| <b>EMERGENCY<br/>OVERVIEW</b> | <b>EXTREMELY FLAMMABLE AND UNDER PRESSURE.</b> STORE BELOW 120°F, OUT OF SUNLIGHT, AND AWAY FROM HEAT SOURCES. DO NOT PUNCTURE OR INCINERATE. AVOID CONTACT WITH SKIN AND EYES. VAPOR HARMFUL. EYE AND SKIN IRRITANT. HARMFUL OR FATAL IF SWALLOWED. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL. |
|-------------------------------|--|

OSHA Classification *This product is a "hazardous chemical" as defined by 29 CFR 1910.1200.*  
 European Classification *Repr. Cat. 3  
F+, Xn, Xi,  
R 12-20/21-36/38-66-67  
S 16-2-25-26-29-33-9*  
 WHMIS Classification *A, B5, D1B, D2A, D2B*

|                 |     |
|-----------------|-----|
| HEALTH          | * 2 |
| FLAMMABILITY    | 4   |
| PHYSICAL HAZARD | 0   |



| HEALTH HAZARDS |   | PHYSICAL HAZARDS |  |                |   |                  |  |                |  |
|----------------|---|------------------|--|----------------|---|------------------|--|----------------|--|
| Irritant       | ✓ | Sensitizer       |  | Combustible    |   | Explosive        |  | Pyrophoric     |  |
| Toxic          |   | Highly Toxic     |  | Flammable      | ✓ | Oxidizer         |  | Water Reactive |  |
| Corrosive      |   | Carcinogenic     |  | Very Flammable |   | Organic Peroxide |  | Unstable       |  |
| Reproductive   |   | Aspiration       |  | Under Pressure | ✓ | Self Reactive    |  | Corrosive      |  |

| INDUSTRIAL LABELING REQUIREMENTS |  |                    |     |
|----------------------------------|--|--------------------|-----|
| CANADA WHMIS                     | UNITED STATES  | EUROPE & AUSTRALIA | GHS |
|                                  | DANGER<br>CONTENTS EXTREMELY FLAMMABLE<br>AND UNDER PRESSURE |                    |     |



# MATERIAL SAFETY DATA SHEET

Husky Green Fin Primer

Part No. B6277CT (Aerosol)

Revision 1 ♦ June 4, 2012

Page 2 of 8

CONFORMS TO THE GLOBALLY HARMONIZED SYSTEM (GHS), ANSI Z400.1-2004, EU DIRECTIVE 91/155/EEC & 99/45/EC, OSHA 29 CFR 1910.1200, NOHSC:2011(2003), AND CANADIAN CPR

## POTENTIAL HEALTH EFFECTS AND SIGNS / SYMPTOMS OF EXPOSURE

|  |   |
|--|---|
| <b>Eye Contact</b>                     | <i>Liquid contact may cause pain along with moderate eye irritation.</i>  |
| <b>Skin Contact</b>                    | <i>Prolonged or repeated exposure may cause skin irritation. Repeated contact may cause drying or flaking of skin. May cause more severe response if confined to skin.</i>  |
| <b>Ingestion</b>                       | <i>Due to being an aerosol, the product does not lend itself to ingestion. Should ingestion occur, it may cause irritation to membranes of the mouth, throat, and gastrointestinal tract resulting in vomiting and/or cramps. Aspiration of vomit into the lungs may cause inflammation, and possible chemical pneumonitis, bronchopneumonia, or pulmonary edema.</i>   |
| <b>Inhalation</b>                      | <i>Prolonged or repeated overexposure is anesthetic. May cause irritation of the respiratory tract, or acute nervous system depression characterized by headache, dizziness, staggering gait, confusion or death. Irritation of the mucous membranes, coughing, and dyspnea are also possible.</i>  |
| <b>Effects of Chronic Exposure</b>     | <i>Reports have associated repeated and prolonged occupational overexposure to solvents with irreversible brain and nervous system damage (sometimes referred to as "Solvent or Painter's Syndrome"). Intentional misuse by concentrating and inhaling this product may be harmful or fatal.</i><br><br><i>Toluene: Reports of chronic poisoning describe anemia, decreased blood cell count and bone marrow hypoplasia. Liver and kidney damage may occur. Exposure may affect a developing fetus. .</i> |
| <b>Medical Conditions Aggravated</b>   | <i>May aggravate personnel with pre-existing disorders associated with any of the Target Organs.</i>  |
| <b>Primary Hazards</b>                 | <i>Sensory Irritation (Methyl Ethyl Ketone, Acetone, Xylene), Narcosis (Toluene)</i>  |
| <b>Target Organs</b>                   | <i>Eyes, skin, respiratory system, central nervous system, liver, kidneys</i>   |
| <b>Routes of Exposure</b>              | <i>Skin contact, skin absorption, eye contact, inhalation</i>   |
| <b>Potential Environmental Effects</b> | <i>See Section 12 for environmental effects</i>   |

## Section 3

## • COMPOSITION / INFORMATION ON INGREDIENTS •

## Section 3

| ID | INGREDIENT          | CAS NUMBER  | EINECS    | EU CLASSIFICATION   | % WT    |
|----|---------------------|-------------|-----------|---------------------|---------|
| 1  | Oxibismethane       | 000115-10-6 | 204-065-8 | F+; 12              | 15 - 40 |
| 2  | Toluene             | 000108-88-3 | 203-625-9 | F, Xn, Xi; 11-20    | 15 - 40 |
| 3  | Methyl Ethyl Ketone | 000078-93-3 | 201-159-0 | F, Xi; 11-36-66-67  | 10 - 30 |
| 4  | Acetone             | 000067-64-1 | 200-662-2 | F, Xi; 11-36-66-67  | 5 - 10  |
| 5  | Propane             | 000074-98-6 | 200-827-9 | F+; 12              | 3 - 7   |
| 6  | Xylene              | 001330-20-7 | 215-535-7 | Xn, Xi; 10-20/21-38 | 1 - 5   |
| 7  | Cyclohexanone       | 000108-94-1 | 203-631-1 | Xn; 10-20           | 1 - 5   |

|                                     |   |
|-------------------------------------|---|
| <b>Risk Phrases</b>                 | <i>See Section 15 for risk phrase text</i>          |
| <b>LD50 and LC50 Information</b>    | <i>See Section 11 for toxicological information</i> |
| <b>Occupational Exposure Limits</b> | <i>See Section 8 for OELs</i>                       |

## Section 4

## • FIRST AID MEASURES •

## Section 4

|                           |  |
|---------------------------|--|
| <b>Ingestion</b>          | <i>Do not induce vomiting! Immediately have the victim drink plenty of water. Do not give milk or digestible oils. Keep airways free. Contact a physician. Never give anything by mouth if victim is rapidly losing consciousness, unconscious, or convulsing.</i> |
| <b>Skin Contact</b>       | <i>Remove with soap and water, rinsing and repeating for 15 minutes. Use skin cream to counter any resulting dryness. Consult a physician if irritation continues. If large skin area is affected, remove contaminated clothing.</i>                               |
| <b>Eye Contact</b>        | <i>Immediately flush with clear water for at least 15 minutes, including under the eyelids. Consult a doctor.</i>  |
| <b>Inhalation</b>         | <i>Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention if symptoms persist or if unconscious.</i>   |
| <b>Notes to Physician</b> | <i>Treat symptomatically.</i>  |
| <b>Antidotes</b>          | <i>No specific antidote.</i>   |



# MATERIAL SAFETY DATA SHEET

Husky Green Fin Primer

Part No. B6277CT (Aerosol)

Revision 1 ❖ June 4, 2012

Page 3 of 8

CONFORMS TO THE GLOBALLY HARMONIZED SYSTEM (GHS), ANSI Z400.1-2004, EU DIRECTIVE 91/155/EEC & 99/45/EC, OSHA 29 CFR 1910.1200, NOHSC:2011(2003), AND CANADIAN CPR

## Section 5

### ● FIRE FIGHTING MEASURES ●

## Section 5

|                                       |  |                                  |                       |
|---------------------------------------|--|----------------------------------|-----------------------|
| Flash Point, Liquid                   | > 1.4 °F (-17.0 °C)  | Flash Point, Propellant          | > -156 °F (-104.4 °C) |
| Explosive Limits                      | 1.00% to 13.00%  | Autoignition Temperature, Liquid | 759.2 °F (404 °C)     |
| Conditions of Flammability            | <i>Heat, sparks, flame, red hot metal</i>  |                                  |                       |
| Extinguishing Media                   | <i>Water, CO<sub>2</sub>, dry chemical, or universal aqueous film forming foam</i>   |                                  |                       |
| Unsuitable Extinguishing Media        | <i>Water jet</i>   |                                  |                       |
| Hazardous Combustion Products         | <i>Oxides of carbon (CO, CO<sub>2</sub>), smoke, and vapors</i>  |                                  |                       |
| Sensitivity to Mechanical Impact      | <i>Mechanical impact may cause aerosol can to rupture, resulting in a rapid release of its contents. In the presence of an ignition source the liquid and/or vapor content may be ignited.</i> |                                  |                       |
| Sensitivity to Static Discharge       | <i>Vapor within the flammable limits may be ignited by a static discharge of sufficient energy.</i>  |                                  |                       |
| Special Equipment and Precautions     | <i>Use water spray to cool fire exposed aerosol containers, as contents can rupture violently from heat developed pressure. Firemen should wear self-contained breathing apparatus.</i>        |                                  |                       |
| Special Explosion Hazards             | <i>Contents extremely flammable and under pressure</i>   |                                  |                       |
| Autoreactivity / Oxidizing Properties | <i>Not available</i>   |                                  |                       |

## Section 6

### ● ACCIDENTAL RELEASE MEASURES ●

## Section 6

|                           |   |
|---------------------------|---|
| Personal Precautions      | <i>Use personal protection recommended in Section 8. Isolate hazard area and deny entry to unnecessary and unprotected personnel.</i>   |
| Environmental Precautions | <i>Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.</i>  |
| Containment Procedures    | <i>Product is an aerosol, therefore spills and leaks are unlikely. In case of rupture, released content may be contained with oil/solvent absorbent pads, socks, and/or absorbents. DO NOT use combustible material such as sawdust.</i>  |
| Cleanup Procedures        | <i>Spills from aerosol cans are unlikely and are generally of small volume. Large spills are therefore not normally considered a problem. In case of actual rupture, avoid breathing vapors and ventilate area well. Remove sources of ignition and use non-sparking equipment. Soak up material with inert absorbent and place in safety containers for proper disposal.</i>     |
| Other Information         | <i>Aerosol products represent a limited hazard and will not spill or leak unless ruptured. In case of rupture contents are generally evacuated from the can rapidly. Area should be ventilated immediately and continuous ventilation provided until all fumes and vapors have been removed. Aerosol cans should never be incinerated or burned. See Section 13 for disposal.</i> |
| Prohibited Materials      | <i>Combustible absorbent material such as sawdust, use of equipment that may cause sparking.</i>  |
| Reporting Requirements    | <i>Spills due to the rupture of a single aerosol can are generally below any regulatory reporting requirements. However, if larger spills somehow result, the reporting requirements of all governing agencies should be observed.</i>  |

## Section 7

### ● HANDLING AND STORAGE ●

## Section 7

|                                       |   |
|---------------------------------------|---|
| Precautions for Safe Handling and Use | <i>KEEP OUT OF THE REACH OF CHILDREN. Avoid prolonged or repeated skin contact. Avoid breathing of vapors. Do not incinerate (burn) containers. Always replace overcap when not in use. <b>Do not smoke</b> while handling or using this product. Avoid use around open flames or other sources of ignition. Exposure to heat or prolonged exposure to sun may cause can to burst. Use only with adequate ventilation, opening doors or windows to achieve cross-ventilation. Wash hands after use.</i> |
| Storage Requirements and Conditions   | <i>Storage of individual cans should be done in an area below 120 °F (55 °C), and away from heat sources. Ensure can is in a secure place to prevent knocking over and accidental rupture. For storage of pallet quantities, compliance with NFPA 30B (Manufacture and Storage of Aerosol Products) is recommended. This product is classified as a Level 3 Aerosol.</i>  |
| Special Packaging Materials           | <i>Not applicable.</i>  |



# MATERIAL SAFETY DATA SHEET

**Husky Green Fin Primer**

Part No. B6277CT (Aerosol)  
Revision 1 ♦ June 4, 2012  
Page 4 of 8

CONFORMS TO THE GLOBALLY HARMONIZED SYSTEM (GHS), ANSI Z400.1-2004, EU DIRECTIVE 91/155/EEC & 99/45/EC, OSHA 29 CFR 1910.1200, NOHSC:2011(2003), AND CANADIAN CPR

## Section 8 • EXPOSURE CONTROLS / PERSONAL PROTECTION • Section 8

### Occupational Exposure Limits

| ID | UNITED STATES OSHA PEL | UNITED STATES NIOSH REL | UNITED STATES NIOSH IDLH | UNITED STATES ACGIH TLV | AUSTRALIA TWA | GERMANY MAK | JAPAN OEL |
|----|------------------------|-------------------------|--------------------------|-------------------------|---------------|-------------|-----------|
| 1  | N/E                    | N/E                     | N/E                      | N/E                     | 400 ppm       | 1000 ppm    | N/E       |
| 2  | 200 ppm                | 100 ppm                 | 500 ppm                  | 50 ppm                  | 50 ppm        | 50 ppm      | 50 ppm    |
| 3  | 200 ppm                | 200 ppm                 | 3000 ppm                 | 200 ppm                 | 150 ppm       | 200 ppm     | 200 ppm   |
| 4  | 1000 ppm               | 250 ppm                 | 750 ppm                  | 500 ppm                 | 500 ppm       | 1200 mg/m3  | 200 ppm   |
| 5  | 1000 ppm               | 1000 ppm                | 2100 ppm                 | 1000 ppm                | N/E           | N/E         | N/E       |
| 6  | 100 ppm                | 100 ppm                 | 900 ppm                  | 100 ppm                 | N/E           | 100 ppm     | 50 ppm    |
| 7  | 50 ppm                 | 25 ppm                  | 700 ppm                  | 25 ppm                  | 25 ppm        | 20 ppm      | 25 ppm    |

| ID | CANADA ALBERTA OEL | CANADA BC TWA | CANADA ONTARIO TWA/EV | CANADA QUEBEC TWA | MEXICO MPEL-PTA | UNITED KINGDOM WEL | UNITED STATES AIHA WEEL |
|----|--------------------|---------------|-----------------------|-------------------|-----------------|--------------------|-------------------------|
| 1  | N/E                | 1000 ppm      | N/E                   | N/E               | N/E             | N/E                | 1000 ppm                |
| 2  | 100 ppm            | 20 ppm        | 50 ppm                | 100 ppm           | 50 ppm          | 50 ppm             | N/E                     |
| 3  | 200 ppm            | 50 ppm        | 200 ppm               | 200 ppm           | 200 ppm         | 200 ppm            | N/E                     |
| 4  | 750 ppm            | 250 ppm       | 500 ppm               | 750 ppm           | 1000 ppm        | 500 ppm            | N/E                     |
| 5  | N/E                | 1000 ppm      | 1000 ppm              | N/E               | N/E             | N/E                | N/E                     |
| 6  | 100 ppm            | 100 ppm       | 100 ppm               | 100 ppm           | 100 ppm         | 50 ppm             | N/E                     |
| 7  | 25 ppm             | 20 ppm        | 20 ppm                | 25 ppm            | 50 ppm          | 10 ppm             | N/E                     |

### Engineering Measures

Use only with adequate ventilation. General ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Local exhaust ventilation or an enclosed handling system may be necessary to control air contamination below that of the lowest OEL from the table above.

### Biological Exposure Indices

Not Available.

### General Hygiene Considerations

Avoid breathing vapors and contact with the skin and eyes. Always replace overcap when not in use. Keep out the reach of children. Wash hands after use.

### Thermal Hazards

This product does not present a thermal hazard.

### PERSONAL PROTECTIVE EQUIPMENT



### Respiratory Protection

An approved respirator with an organic vapor cartridge may be permissible under certain circumstances where airborne concentrations are expected to exceed occupational exposure limits. If respirators are needed, in the United States compliance with OSHA standard 29 CFR 1910.134 is necessary.

### Skin Protection

For brief contact, no precautions other than clean body-covering clothing should be needed. When prolonged or repeated contact could occur, use protective clothing impervious to the ingredients listed in Section 2.

### Eye/Face Protection

Safety glasses with side shields are recommended as a minimum for any type of industrial chemical handling. Where eye contact with this material could occur, chemical splash proof goggles are recommended.

### Other Protective Equipment

Safety showers and eye-wash stations should be available in the workplace near where the material will be used.

## Section 9 • PHYSICAL AND CHEMICAL PROPERTIES • Section 9



# MATERIAL SAFETY DATA SHEET

**Husky Green Fin Primer**

Part No. B6277CT (Aerosol)

Revision 1 ♦ June 4, 2012

Page 5 of 8

CONFORMS TO THE GLOBALLY HARMONIZED SYSTEM (GHS), ANSI Z400.1-2004, EU DIRECTIVE 91/155/EEC & 99/45/EC, OSHA 29 CFR 1910.1200, NOHSC:2011(2003), AND CANADIAN CPR

|                     |                                    |                                  |                             |
|---------------------|------------------------------------|----------------------------------|-----------------------------|
| Boiling Point       | > 133 °F (56.1 °C)                 | Melting / Freezing Point         | > -139.6 °F (-95.3 °C)      |
| Flash Point, Liquid | > 1.4 °F (-17.0 °C)                | Flash Point, Propellant          | -156 F (-104.4)             |
| Explosive Limits    | 1.00% to 13.00%                    | Autoignition Temperature, Liquid | 759 °F (404.0 °C)           |
| Flammability        | <i>Extremely Flammable Aerosol</i> | Density (H <sub>2</sub> O = 1)   | 0.804 g/cc                  |
| Molecular Weight    | <i>Not Available</i>               | Weight                           | 6.706 lbs/gal               |
| Vapor Pressure      | <i>Not Available</i>               | pH                               | <i>Not Available</i>        |
| Vapor Density       | <i>5 g/cc Maximum</i>              | Evaporation Rate                 | <i>Not Available</i>        |
| Physical State      | <i>Liquid Under Pressure</i>       | Partition Coefficient            | <i>Not Available</i>        |
| Viscosity           | <i>Not Available</i>               | Refractive Index                 | <i>Not Available</i>        |
| Odor Threshold      | <i>Not Available</i>               | Heat of Combustion               | <i>Not Available</i>        |
| Odor                | <i>Paint-like</i>                  | Water Solubility                 | <i>Not Available</i>        |
| Appearance / Color  | <i>Clear dull coating</i>          | Heat of Combustion               | <i>Not Available</i>        |
| Percent Volatile    | 90% Wt (93% Vol) Max               | VOC Content                      | 5.197 lbs/gal (674.801 g/L) |
| Percent VOC         | 82% Wt (86% Vol) Max               | HAP Content                      | 2.083 lbs/gal (249.610 g/L) |
| Solids Content      | 11% Wt (8% Vol) Max                | Maximum Incremental Reactivity   | 1.838 g O <sub>3</sub> /g   |

## Section 10

## ● STABILITY AND REACTIVITY ●

## Section 10

|                          |   |
|--------------------------|---|
| Stability                | <i>Stable</i>   |
| Physical Hazards         | <i>Contents under pressure, Flammable</i>   |
| Conditions to Avoid      | <i>Not Available</i>  |
| Hazard Polymerization    | <i>Not expected to occur</i>  |
| Material Incompatibility | <i>Strong oxidizing agents, alkaline earth metals, powered metal salts, amines, ammonia, caustics, pyridines, nitric acid, dichlorohydrantion, hydrogen peroxide, strong reducing agents, hexachloromelamine, trichloromelamine, halogenated solvent/alkali mixtures, potassium tert-butoxide bases, sulfur dichloride, acids, isocyanates, alkali metals, nitrogen tetroxide, silver perchlorate, tetranitromethane, uranium hexafluoride.</i> |
| Conditions of Reactivity | <i>Heat, sparks, flame, red hot metal</i>   |
| Decomposition Products   | <i>Oxides of carbon</i>   |

## Section 11

## ● TOXICOLOGICAL INFORMATION ●

## Section 11

|                          |  |
|--------------------------|--|
| Irritancy of Product     | <i>The following ingredients are eye irritants: Methyl Ethyl Ketone, Acetone, Cyclohexanone. The following ingredients are skin irritants: Toluene, Xylene, Cyclohexanone.</i>   |
| Sensitization to Product | <i>None of the ingredients cause sensitization.</i>  |
| Carcinogen Data          | <i>Ethyl Benzene (a component of Xylene) is listed with IARC as Class 2B (possible human carcinogen) and with ACGIH as A3 (confirmed animal carcinogen with unknown relevance to humans). Ethyl Benzene is also listed with the State of California as a carcinogen.</i> |
| Reproductive Toxicity    | <i>The following ingredients are considered reproductive toxicants: Toluene</i>  |
| Teratogenicity           | <i>The following ingredients are considered teratogens: Xylene, Toluene</i>  |
| Mutagenicity             | <i>Product does not contain any known or suspected mutagens.</i>   |
| Synergistic Products     | <i>Xylene &amp; Toluene: Exposure to related solvents, such as benzene, toluene and ethanol slows the rate of clearance of from the body, thus enhancing the toxic effects</i>   |

LD<sub>50</sub> and LC<sub>50</sub> Information



# MATERIAL SAFETY DATA SHEET

**Husky Green Fin Primer**

Part No. B6277CT (Aerosol)

Revision 1 ♦ June 4, 2012

Page 6 of 8

CONFORMS TO THE GLOBALLY HARMONIZED SYSTEM (GHS), ANSI Z400.1-2004, EU DIRECTIVE 91/155/EEC & 99/45/EC, OSHA 29 CFR 1910.1200, NOHSC:2011(2003), AND CANADIAN CPR

| ID | ORAL LD50  |         | DERMAL LD50  |         | INHALATION LC50 |      |         |
|----|------------|---------|--------------|---------|-----------------|------|---------|
|    | VALUE      | SPECIES | VALUE        | SPECIES | VALUE           | TIME | SPECIES |
| 1  | —          | —       | —            | —       | 164000 ppm      | 4 hr | rat     |
| 2  | 636 mg/kg  | rat     | >12000 mg/kg | rabbit  | 49 mg/m3        | 4 hr | rat     |
| 3  | 2740 mg/kg | rat     | > 8050 mg/kg | rat     | 11300 ppm       | 4 hr | rat     |
| 4  | 5800 mg/kg | rat     | 20000 mg/kg  | rabbit  | 76 mg/m3        | 4 hr | rat     |
| 5  | —          | —       | —            | —       | 658 mg/L        | 4 hr | rat     |
| 6  | 2840 mg/kg | rat     | 4500 mg/kg   | rabbit  | 6300 mg/L       | 4 hr | rat     |
| 7  | 1535 mg/kg | rat     | 948 mg/kg    | rabbit  | 8000 ppm        | 4 hr | rat     |

## Section 12

## • ECOLOGICAL INFORMATION •

## Section 12

**Mobility** Not Available  
**Persistence** Not Available  
**Degradability** Not Available  
**Bioaccumulation** Not Available  
**Other Ecologic Data** Do not allow to enter waters, waste water, or soil.  
**Effects on the Ozone Layer** This product does not contain any ozone depleting ingredients.

### Ecotoxicity

| ID | TYPE | FISH       |        | TYPE | INVERTEBRATES |        | TYPE | AQUATIC PLANTS |        | TYPE | MICROORGANISMS |        |
|----|------|------------|--------|------|---------------|--------|------|----------------|--------|------|----------------|--------|
|    |      | VALUE      | PERIOD |      | VALUE         | PERIOD |      | VALUE          | PERIOD |      | VALUE          | PERIOD |
| 1  | NOEC | >4000 mg/L | 96 hr  | NOEC | > 4000 mg/L   | 48 hr  | —    | —              | —      | EC10 | > 1600 mg/L    | 48 hr  |
| 2  | LC50 | 13 mg/L    | 96 hr  | EC50 | 11.5 mg/L     | 48 hr  | EC50 | >250 mg/L      | 24 hr  | EC0  | 29 mg/L        | 16 hr  |
| 3  | LC50 | 5600 mg/L  | 96 hr  | EC50 | >520 mg/L     | 48 hr  | EC3  | > 4300 mg/L    | 7 days | EC5  | 2982 mg/L      | 48 hr  |
| 4  | LC50 | 13 g/L     | 48 hr  | LC50 | 8800 mg/L     | 48 hr  | EC50 | >20 g/L        | 14 day | EC50 | >14 g/L        | 15 min |
| 5  | —    | —          | —      | —    | —             | —      | —    | —              | —      | —    | —              | —      |
| 6  | LC50 | 26.7 mg/L  | 96 hr  | LC50 | 14 mg/L       | 24 hr  | —    | —              | —      | —    | —              | —      |
| 7  | LC50 | 536 mg/L   | 48 hr  | EC50 | 800 mg/L      | 24 hr  | —    | —              | —      | —    | —              | —      |

## Section 13

## • DISPOSAL CONSIDERATIONS •

## Section 13

**Waste Disposal** Characteristics and waste stream classification can change with product use and location. It is the responsibility of the user to determine the proper storage, transportation, treatment, and/or disposal methodologies for spent materials and residues at the time of disposition. All waste must be disposed of in compliance with the respective national, federal, state, and/or local regulations.

**Waste Disposal of Packaging** In the United States, an aerosol container that does not contain a significant amount of liquid would meet the definition of scrap metal (40 CFR 261.1(c)(6)), and would be exempt from RCRA regulation under 40 CFR 261.6(a)(3)(iv) if it is to be recycled. If containers are to be disposed of (not recycled) it must be managed under all applicable RCRA and state regulations.

**Landfill Precautions** Not Available

**Incineration Precautions** \*\* DO NOT INCINERATE \*\* CONTENTS UNDER PRESSURE \*\*

## Section 14


## • TRANSPORTATION INFORMATION •

## Section 14

### DOT SHIPPING INFORMATION (United States)

CONSUMER COMMODITY  
**ORM-D**  
 PROPER SHIPPING NAME: ... Consumer Commodity  
 HAZARD CLASS: ... ORM-D  
 PACKING GROUP: ...  
 UN or ID NUMBER: ...  
 NAERG NUMBER: ... 171

### ICAO/IATA SHIPPING INFORMATION (International Air)

  
 PROPER SHIPPING NAME: ... Consumer Commodity  
 HAZARD CLASS: ... 9  
 PACKAGING GROUP: ...  
 UN or ID NUMBER: ... ID8000  
 PACKAGING INSTRUCTION: ... Y963



# MATERIAL SAFETY DATA SHEET

**Husky Green Fin Primer**

Part No. B6277CT (Aerosol)  
Revision 1 ♦ June 4, 2012  
Page 7 of 8

CONFORMS TO THE GLOBALLY HARMONIZED SYSTEM (GHS), ANSI Z400.1-2004, EU DIRECTIVE 91/155/EEC & 99/45/EC, OSHA 29 CFR 1910.1200, NOHSC:2011(2003), AND CANADIAN CPR

### IMDG SHIPPING INFORMATION (International Ocean)



PROPER SHIPPING NAME: ... Aerosols, Limited Quantity  
CLASS: ..... 2.1  
PACKAGING GROUP: ..... -  
SUBSIDIARY RISK(S): ..... -  
UN or ID NUMBER: ..... UN1950  
PACKING INSTRUCTIONS: ... P003  
EmS NO.: ..... F-D, S-U  
STOWAGE: ..... Category A  
MFAG NO.: ..... 620

### ADR SHIPPING INFORMATION (European Union)



PROPER SHIPPING NAME: ... Aerosols, Limited Quantity  
ADR CLASS: ..... 2  
PACKAGING GROUP: ..... -  
UN or ID NUMBER: ..... UN1950  
CLASSIFICATION CODE: ..... 5F  
HAZCHEM CODE: ..... -

### TDG SHIPPING INFORMATION (Canada)



PROPER SHIPPING NAME: ... Aerosols, Limited Quantity  
HAZARD CLASS: ..... 2.1  
PACKAGING GROUP: ..... -  
UN or ID NUMBER: ..... UN1950

### NMFC DESCRIPTION (United States)

ITEM DESCRIPTION: Paint Related Material  
ITEM NUMBER: 149980 Sub 2  
CLASS: 55

## Section 15

## REGULATORY INFORMATION

## Section 15

### United States - Federal

| ID | TSCA INVENTORY | SARA 302 EHS | RCRA | CERCLA | SARA 313 | FIRE | REACTIVITY | SARA 311/312 ACUTE | CHRONIC | PRESSURE | CLEAN AIR ACT | CLEAN WATER ACT |
|----|----------------|--------------|------|--------|----------|------|------------|--------------------|---------|----------|---------------|-----------------|
| 1  | ✓              | —            | —    | —      | —        | ✓    | —          | ✓                  | —       | ✓        | —             | —               |
| 2  | ✓              | —            | U220 | 1000#  | 24.36%   | ✓    | —          | ✓                  | ✓       | —        | XOV           | 1000#           |
| 3  | ✓              | —            | U159 | 5000#  | 15.53 %  | ✓    | —          | ✓                  | ✓       | —        | —             | —               |
| 4  | ✓              | —            | U002 | 5000#  | —        | ✓    | —          | ✓                  | —       | —        | —             | —               |
| 5  | ✓              | —            | —    | —      | —        | ✓    | —          | ✓                  | —       | —        | —             | —               |
| 6  | ✓              | —            | U239 | 100#   | 3.46%    | ✓    | —          | ✓                  | ✓       | —        | XOV           | 100#            |
| 7  | ✓              | —            | U057 | 5000#  | —        | ✓    | —          | ✓                  | ✓       | —        | —             | —               |

### United States - States

| ID | CALIFORNIA | DELAWARE | FLORIDA | MASSACHUSETTS    | PENNSYLVANIA | MINNESOTA | NEW JERSEY | NEW YORK | WASHINGTON |
|----|------------|----------|---------|------------------|--------------|-----------|------------|----------|------------|
| 1  | —          | —        | ✓       | 5,6              | —            | I         | ✓          | —        | —          |
| 2  | D          | ✓        | ✓       | 2,4,5,6 F7 F8 F9 | E            | ANO       | ✓          | ✓        | ✓          |
| 3  | —          | ✓        | ✓       | 2,4,5,6 F8 F9    | E            | ANO       | ✓          | ✓        | ✓          |
| 4  | —          | ✓        | ✓       | 2,4,5,6 F8 F9    | E            | ANO       | ✓          | ✓        | ✓          |
| 5  | —          | ✓        | —       | 2,4,5,6          | —            | AO        | ✓          | —        | ✓          |
| 6  | C*         | ✓        | ✓       | 2,4 F8 F9        | E            | ANO       | ✓          | ✓        | ✓          |
| 7  | —          | ✓        | ✓       | 2,4,6 F8         | E            | ANO       | —          | ✓        | ✓          |

### Canada

| ID | WHMIS CATEGORIES |    |   |     |     |     |     |    |   | CHEMICAL LISTS |      |       |     |
|----|------------------|----|---|-----|-----|-----|-----|----|---|----------------|------|-------|-----|
|    | A                | B  | C | D1A | D1B | D2A | D2B | D3 | E | DSL            | NDSL | NPRI  | CWC |
| 1  | ✓                | B1 | — | —   | —   | —   | —   | —  | — | ✓              | —    | 5     | —   |
| 2  | —                | B2 | — | —   | —   | ✓   | —   | —  | — | ✓              | —    | 1A, 5 | —   |
| 3  | —                | B2 | — | —   | —   | ✓   | ✓   | —  | — | ✓              | —    | 1A, 5 | —   |
| 4  | —                | B2 | — | —   | —   | —   | ✓   | —  | — | ✓              | —    | —     | —   |
| 5  | ✓                | B1 | — | —   | —   | —   | —   | —  | — | ✓              | —    | 5     | —   |
| 6  | —                | B2 | — | —   | —   | ✓   | ✓   | —  | — | ✓              | —    | 1A, 5 | —   |
| 7  | —                | B3 | — | —   | ✓   | —   | ✓   | —  | — | ✓              | —    | —     | —   |

**This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.**



# MATERIAL SAFETY DATA SHEET

Husky Green Fin Primer

Part No. B6277CT (Aerosol)

Revision 1 ♦ June 4, 2012

Page 8 of 8

CONFORMS TO THE GLOBALLY HARMONIZED SYSTEM (GHS), ANSI Z400.1-2004, EU DIRECTIVE 91/155/EEC & 99/45/EC, OSHA 29 CFR 1910.1200, NOHSC:2011(2003), AND CANADIAN CPR

## European Union

| CODE    | RISK PHRASES   |
|---------|--|
| R 10    | Flammable.   |
| R 11    | Highly flammable.                                    |
| R12     | Extremely flammable.                                 |
| R 20    | Harmful by inhalation.                               |
| R 20/21 | Harmful by inhalation and in contact with skin       |
| R 36    | Irritating to eyes.                                  |
| R 38    | Irritating to skin.                                  |
| R 66    | Repeated exposure may cause skin dryness or cracking |
| R 67    | Vapours may cause drowsiness and dizziness           |

| CODE | SAFETY PHRASES   |
|------|--|
| S 2  | Keep out of the reach of children  |
| S 9  | Keep container in a well ventilated place  |
| S 16 | Keep away from sources of ignition – No smoking  |
| S 25 | Avoid contact with eyes  |
| S 26 | In case of contact with eyes, rinse immediately with plenty of water and seek medical advice |
| S 29 | Do not empty into drains   |
| S 33 | Take precautionary measure against static discharge  |

## RoHS Compliance



This product is RoHS compliant according to the definitions and restrictions given by Directive 2002/95/EC and The Council of January 27, 2003 on the restriction of the use of certain hazardous substances in electrical and electronic equipment.

## Australia

### Poisons Schedule Number

None of the ingredients are present at or above a concentration necessary for allocation of a Poisons Schedule Number.

### Chemical Inventory Status

All of the ingredients are listed on the Australian Inventory of Chemical Substances (AICS) or are exempt.

## Section 16

## ● OTHER INFORMATION ●

## Section 16

### Disclaimer of Liability

The information contained herein is based upon data provided to us by our suppliers, and reflects our best judgement. However, no warranty of merchantability, fitness for any use, or any other warranty or guarantee is expressed or implied regarding the accuracy of such data, or the results to be obtained from use thereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, we do not assume any responsibility for the results of such application. This information is furnished upon the condition that the persons receiving it shall make their own determinations of the suitability of the material for any particular use. Although certain hazards are described herein, we cannot guarantee these are the only hazards that exist.

### Revision History

Revision 1, 06/04/2012, Original