

Husky Green Fin Coil Protector Aerosol

SAFETY DATA SHEET

Prepared according to Federal Register / Vol. 77, No. 58 / March 26, 2012 / Rules and Regulations

Section 1. Identification

1.1 Product identifier **HUSKY GREEN FIN COIL PROTECTOR AEROSOL**

Product Code 11063 108205 604

1.2 Recommended use Anti-Corrosive coating for HVAC/R coils

1.3 Details of the supplier of the safety data sheet

Formulated Specifically for: Bronz-Glow Technologies, Inc.
175 Bronz-Glow Way
St. Augustine, FL 32095
904-825-0175

1.4 Emergency phone number **Chemtrec 1-800-424-9300 (US) 703-527-3887 (International)**

Section 2. Hazard(s) identification

Physical hazards	Flammable aerosols	Category 1
	Gases under pressure	Liquefied gas
Health hazards	Acute toxicity, oral	Category 4
	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2B
	Carcinogenicity	Category 1B
	Reproductive toxicity	Category 2
	Specific target organ toxicity, repeated exposure	Category 1
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 2
	Hazardous to the aquatic environment, long-term hazard	Category 2
OSHA defined hazards	Not classified.	

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. Keep away from heat/sparks/open flames/hot surfaces. Contains gas under pressure; may explode if heated. Harmful if swallowed. Causes skin irritation. Causes eye irritation. May cause cancer. Suspected of damaging fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure. Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Precautionary statement
Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

Safety Data Sheet

Response	If swallowed: Call a poison center/doctor if you feel unwell. If on skin: Wash with plenty of water. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Rinse mouth. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse. Collect spillage.
Storage	Store locked up. Protect from sunlight. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	86.14% of the mixture consists of component(s) of unknown acute oral toxicity. 87.66% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 87.66% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

Section 3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
ALIPHATIC PETROLEUM DISTILLATES		64742-89-8	20 to <30
PROPANE		74-98-6	20 to <30
Naphtha, Hydrotreated Light		64742-49-0	10 to <20
N-BUTANE		106-97-8	10 to <20
AMORPHOUS SILICA GEL		112945-52-5	1 to <5
CARBON BLACK		1333-86-4	1 to <5
CYCLOHEXANE		110-82-7	1 to <5
ETHYLBENZENE		100-41-4	1 to <5
METHYL ETHYL KETONE		78-93-3	1 to <5
METHYL N-AMYL KETONE		110-43-0	1 to <5
MINERAL SPIRITS		8052-41-3	1 to <5
n-Heptane		142-82-5	1 to <5
TOLUENE		108-88-3	1 to <5
XYLENE		1330-20-7	1 to <5
MEDIUM ALIPHATIC SOLVENT NAPHTHA		64742-88-7	0.1 to <1
Other components below reportable levels			5 to <10

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

Section 4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Not likely, due to the form of the product. Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical advice/attention if you feel unwell.
Most important symptoms/effects, acute and delayed	Dizziness. Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	
General information	Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Section 5 Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol. Contents under pressure. Pressurized container may explode when exposed to heat or flame.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

Section 7. Handling and storage

Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe mist or vapor. Do not taste or swallow. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.
--------------------------------------	---

Safety Data Sheet

Conditions for safe storage, including any incompatibilities

Level 2 Aerosol.
 Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Stored containers should be periodically checked for general condition and leakage. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

Section 8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
CARBON BLACK (CAS 1333-86-4)	PEL	3.5 mg/m3
CYCLOHEXANE (CAS 110-82-7)	PEL	1050 mg/m3
ETHYLBENZENE (CAS 100-41-4)	PEL	300 ppm 435 mg/m3
METHYL ETHYL KETONE (CAS 78-93-3)	PEL	100 ppm 590 mg/m3
METHYL N-AMYL KETONE (CAS 110-43-0)	PEL	200 ppm 465 mg/m3
MINERAL SPIRITS (CAS 8052-41-3)	PEL	100 ppm 2900 mg/m3
n-Heptane (CAS 142-82-5)	PEL	500 ppm 2000 mg/m3
PROPANE (CAS 74-98-6)	PEL	500 ppm 1800 mg/m3
XYLENE (CAS 1330-20-7)	PEL	1000 ppm 435 mg/m3 100 ppm

US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
TOLUENE (CAS 108-88-3)	Ceiling TWA	300 ppm 200 ppm

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value
AMORPHOUS SILICA GEL (CAS 112945-52-5)	TWA	0.8 mg/m3 20 mppcf

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
CARBON BLACK (CAS 1333-86-4)	TWA	3 mg/m3	Inhalable fraction.
CYCLOHEXANE (CAS 110-82-7)	TWA	100 ppm	
ETHYLBENZENE (CAS 100-41-4)	TWA	20 ppm	
MEDIUM ALIPHATIC SOLVENT NAPHTHA (CAS 64742-88-7)	TWA	200 mg/m3	Non-aerosol.
METHYL ETHYL KETONE (CAS 78-93-3)	STEL	300 ppm	
METHYL N-AMYL KETONE (CAS 110-43-0)	TWA	200 ppm	
	TWA	50 ppm	

Safety Data Sheet

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
MINERAL SPIRITS (CAS 8052-41-3)	TWA	100 ppm	
N-BUTANE (CAS 106-97-8)	STEL	1000 ppm	
n-Heptane (CAS 142-82-5)	STEL	500 ppm	
	TWA	400 ppm	
TOLUENE (CAS 108-88-3)	TWA	20 ppm	
XYLENE (CAS 1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
AMORPHOUS SILICA GEL (CAS 112945-52-5)	TWA	6 mg/m3
CARBON BLACK (CAS 1333-86-4)	TWA	0.1 mg/m3
CYCLOHEXANE (CAS 110-82-7)	TWA	1050 mg/m3
		300 ppm
ETHYLBENZENE (CAS 100-41-4)	STEL	545 mg/m3
		125 ppm
	TWA	435 mg/m3
		100 ppm
MEDIUM ALIPHATIC SOLVENT NAPHTHA (CAS 64742-88-7)	TWA	100 mg/m3
METHYL ETHYL KETONE (CAS 78-93-3)	STEL	885 mg/m3
		300 ppm
	TWA	590 mg/m3
		200 ppm
METHYL N-AMYL KETONE (CAS 110-43-0)	TWA	465 mg/m3
		100 ppm
MINERAL SPIRITS (CAS 8052-41-3)	Ceiling	1800 mg/m3
	TWA	350 mg/m3
N-BUTANE (CAS 106-97-8)	TWA	1900 mg/m3
		800 ppm
n-Heptane (CAS 142-82-5)	Ceiling	1800 mg/m3
		440 ppm
	TWA	350 mg/m3
		85 ppm
PROPANE (CAS 74-98-6)	TWA	1800 mg/m3
		1000 ppm
TOLUENE (CAS 108-88-3)	STEL	560 mg/m3
		150 ppm
	TWA	375 mg/m3
		100 ppm

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
ETHYLBENZENE (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*
METHYL ETHYL KETONE (CAS 78-93-3)	2 mg/l	MEK	Urine	*

Safety Data Sheet

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
TOLUENE (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*
XYLENE (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

TOLUENE (CAS 108-88-3) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

TOLUENE (CAS 108-88-3) Skin designation applies.

US ACGIH Threshold Limit Values: Skin designation

MEDIUM ALIPHATIC SOLVENT NAPHTHA (CAS 64742-88-7) Can be absorbed through the skin.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment Eye/face

protection Wear safety glasses with side shields (or goggles).

Skin protection Hand protection

Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

Other Respiratory protection

Wear appropriate chemical resistant clothing.

If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Section 9. Physical and chemical properties

Appearance

Physical state

Liquid.

Form

Aerosol. Liquefied gas.

Color

Not available.

Odor

Not available.

Odor threshold

Not available.

pH

Not available.

Melting point/freezing point

-305.68 °F (-187.6 °C) estimated

Initial boiling point and boiling range

-43.78 °F (-42.1 °C) estimated

Flash point

-156.0 °F (-104.4 °C) estimated

Evaporation rate

Not available.

Flammability (solid, gas)

Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower (%)

1.9 % estimated

Flammability limit - upper (%)

9.5 % estimated

Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	7259.29 hPa estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	550 °F (287.78 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	5.67 lbs/gal
Explosive properties	Not explosive.
Flammability class	Flammable IA estimated
Heat of combustion (NFPA 30B)	29.21 kJ/g estimated
Oxidizing properties	Not oxidizing.
Percent volatile	34.99
Specific gravity	0.68
VOC	1.98 lbs/gal Regulatory 237.57 g/l Regulatory 1.98 lbs/gal Material 237.57 g/l Material

Section 10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport. Material is stable under normal conditions.
Chemical stability	
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	
Incompatible materials	Heat. Avoid temperatures exceeding the flash point. Contact with incompatible materials. Strong acids. Strong oxidizing agents. Nitrates. Halogens. Fluorine. Chlorine.
Hazardous decomposition products	No hazardous decomposition products are known.

Section 11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause damage to organs through prolonged or repeated exposure by inhalation.
Skin contact	Causes skin irritation.
Eye contact	Causes eye irritation.
Ingestion	Harmful if swallowed.
Symptoms related to the physical, chemical and toxicological characteristics	Dizziness. Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. Skin irritation. May cause redness and pain.
Information on toxicological effects	
Acute toxicity	Harmful if swallowed.

Components	Species	Test Results
AMORPHOUS SILICA GEL (CAS 112945-52-5)		
<u>Acute</u>		
Oral		
LD50	Mouse	> 15000 mg/kg

Safety Data Sheet

Components	Species	Test Results
	Rat	> 22500 mg/kg
CARBON BLACK (CAS 1333-86-4)		
<u>Acute</u>		
Oral		
LD50	Rat	> 8000 mg/kg
CYCLOHEXANE (CAS 110-82-7)		
<u>Acute</u>		
Inhalation		
NOEL	Monkey	1243 ppm, 6 Hours
Oral		
LD50	Mouse	1300 mg/kg
	Rat	29820 mg/kg
ETHYLBENZENE (CAS 100-41-4)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	17800 mg/kg
Oral		
LD50	Rat	3500 mg/kg
METHYL ETHYL KETONE (CAS 78-93-3)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 8000 mg/kg
Inhalation		
LC50	Mouse	11000 ppm, 45 Minutes
	Rat	11700 ppm, 4 Hours
Oral		
LD50	Mouse	670 mg/kg
	Rat	2300 - 3500 mg/kg
METHYL N-AMYL KETONE (CAS 110-43-0)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	12600 mg/kg
Oral		
LD50	Mouse	730 mg/kg
	Rat	1.67 g/kg
N-BUTANE (CAS 106-97-8)		
<u>Acute</u>		
Inhalation		
LC50	Mouse	680 mg/l, 2 Hours
	Rat	658 mg/l, 4 Hours
n-Heptane (CAS 142-82-5)		
<u>Acute</u>		
Inhalation		
LC50	Rat	103 mg/l, 4 Hours
LD50	Mouse	75 mg/l, 2 Hours
PROPANE (CAS 74-98-6)		
<u>Acute</u>		
Inhalation		
LC50	Rat	> 1442.847 mg/l, 15 Minutes

Safety Data Sheet

Components	Species	Test Results
TOLUENE (CAS 108-88-3)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	12124 mg/kg 14.1 ml/kg
Inhalation		
LC50	Mouse	5320 ppm, 8 Hours 400 ppm, 24 Hours
	Rat	26700 ppm, 1 Hours 12200 ppm, 2 Hours 8000 ppm, 4 Hours
Oral		
LD50	Rat	2.6 g/kg
XYLENE (CAS 1330-20-7)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 43 g/kg
Inhalation		
LC50	Mouse	3907 mg/l, 6 Hours
	Rat	6350 mg/l, 4 Hours
Oral		
LD50	Mouse	1590 mg/kg
	Rat	3523 - 8600 mg/kg
* Estimates for product may be based on additional component data not shown.		
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Causes eye irritation.	
Respiratory or skin sensitization		
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	May cause cancer.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
AMORPHOUS SILICA GEL (CAS 112945-52-5)	3 Not classifiable as to carcinogenicity to humans.	
CARBON BLACK (CAS 1333-86-4)	2B Possibly carcinogenic to humans.	
ETHYLBENZENE (CAS 100-41-4)	2B Possibly carcinogenic to humans.	
MINERAL SPIRITS (CAS 8052-41-3)	3 Not classifiable as to carcinogenicity to humans.	
TOLUENE (CAS 108-88-3)	3 Not classifiable as to carcinogenicity to humans.	
XYLENE (CAS 1330-20-7)	3 Not classifiable as to carcinogenicity to humans.	
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)		
Not regulated.		
US. National Toxicology Program (NTP) Report on Carcinogens		
Not listed.		
Reproductive toxicity	Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals. Suspected of damaging fertility or the unborn child.	
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Causes damage to organs through prolonged or repeated exposure.	
Aspiration hazard	Not an aspiration hazard.	

Chronic effects Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

Section 12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Components	Species	Test Results
CYCLOHEXANE (CAS 110-82-7)		
Aquatic		
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>) 23.03 - 42.07 mg/l, 96 hours
ETHYLBENZENE (CAS 100-41-4)		
Aquatic		
Crustacea	EC50	Water flea (<i>Daphnia magna</i>) 1.37 - 4.4 mg/l, 48 hours
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>) 7.5 - 11 mg/l, 96 hours
METHYL ETHYL KETONE (CAS 78-93-3)		
Aquatic		
Crustacea	EC50	Water flea (<i>Daphnia magna</i>) 4025 - 6440 mg/l, 48 hours
Fish	LC50	Sheepshead minnow (<i>Cyprinodon variegatus</i>) > 400 mg/l, 96 hours
METHYL N-AMYL KETONE (CAS 110-43-0)		
Aquatic		
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>) 126 - 137 mg/l, 96 hours
n-Heptane (CAS 142-82-5)		
Aquatic		
Fish	LC50	Mozambique tilapia (<i>Tilapia mossambica</i>) 375 mg/l, 96 hours
TOLUENE (CAS 108-88-3)		
Aquatic		
Crustacea	EC50	Water flea (<i>Daphnia magna</i>) 5.46 - 9.83 mg/l, 48 hours
Fish	LC50	Coho salmon, silver salmon (<i>Oncorhynchus kisutch</i>) 8.11 mg/l, 96 hours
XYLENE (CAS 1330-20-7)		
Aquatic		
Fish	LC50	Bluegill (<i>Lepomis macrochirus</i>) 7.711 - 9.591 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

CYCLOHEXANE	3.44
ETHYLBENZENE	3.15
METHYL ETHYL KETONE	0.29
METHYL N-AMYL KETONE	1.98
MINERAL SPIRITS	3.16 - 7.15
N-BUTANE	2.89
n-Heptane	4.66
PROPANE	2.36
TOLUENE	2.73
XYLENE	3.12 - 3.2

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

Section 13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations. Dispose in accordance with all applicable regulations.
Local disposal regulations	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Hazardous waste code	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Waste from residues / unused products	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.
Contaminated packaging	

Section 14. Transport information

DOT

UN number	
UN proper shipping name	UN1950
Transport hazard class(es)	Aerosols, Flammable
Class	
Subsidiary risk	2.1
Label(s)	-
Packing group	2.1
Special precautions for user	Not applicable.
Special provisions	Read safety instructions, SDS and emergency procedures before handling.
Packaging exceptions	N82
Packaging non bulk	306
Packaging bulk	None

IATA

UN number	
UN proper shipping name	UN1950
Transport hazard class(es)	Aerosols, Flammable
Class	
Subsidiary risk	2.1
Label(s)	-
Packing group	2.1
Environmental hazards	Not applicable.
Special precautions for user	No.
Other information	Read safety instructions, SDS and emergency procedures before handling.
Passenger and cargo aircraft	Allowed.
Cargo aircraft only	

IMDG

UN number	
UN proper shipping name	UN1950
Transport hazard class(es)	Aerosols, Flammable
Class	
Subsidiary risk	2.1
Label(s)	-
Packing group	2.1
Environmental hazards	Not applicable.
Marine pollutant	
EmS	No.
Special precautions for user	Not available.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Read safety instructions, SDS and emergency procedures before handling. Not established.
---	---

DOT



IATA; IMDG



General information

Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: Ensure that containers are firmly secured. Ensure cylinder valve is closed and not leaking. Ensure valve outlet cap nut or plug (where provided) is correctly fitted. Ensure valve protection device (where provided) is correctly fitted. Ensure adequate ventilation. Ensure compliance with applicable regulations.

Section 15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

CYCLOHEXANE (CAS 110-82-7)	Listed.
ETHYLBENZENE (CAS 100-41-4)	Listed.
METHYL ETHYL KETONE (CAS 78-93-3)	Listed.
N-BUTANE (CAS 106-97-8)	Listed.
n-Heptane (CAS 142-82-5)	Listed.
PROPANE (CAS 74-98-6)	Listed.
TOLUENE (CAS 108-88-3)	Listed.
XYLENE (CAS 1330-20-7)	Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - Yes
 Delayed Hazard - Yes
 Fire Hazard - Yes
 Pressure Hazard - No
 Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
CYCLOHEXANE	110-82-7	1 to <5
ETHYLBENZENE	100-41-4	1 to <5

Revision date: 02-10-2016 Issue date: 06-10-2015

Safety Data Sheet

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
TOLUENE	108-88-3	1 to <5
XYLENE	1330-20-7	1 to <5

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

ETHYLBENZENE (CAS 100-41-4)
TOLUENE (CAS 108-88-3)
XYLENE (CAS 1330-20-7)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

N-BUTANE (CAS 106-97-8)
PROPANE (CAS 74-98-6)

Safe Drinking Water Act (SDWA) Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

METHYL ETHYL KETONE (CAS 78-93-3) 6714
TOLUENE (CAS 108-88-3) 6594

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

METHYL ETHYL KETONE (CAS 78-93-3) 35 %WV
TOLUENE (CAS 108-88-3) 35 %WV

DEA Exempt Chemical Mixtures Code Number

METHYL ETHYL KETONE (CAS 78-93-3) 6714
TOLUENE (CAS 108-88-3) 594

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

METHYL ETHYL KETONE (CAS 78-93-3) Low priority
METHYL N-AMYL KETONE (CAS 110-43-0) Other Flavoring Substances with OSHA PEL's

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

ALIPHATIC PETROLEUM DISTILLATES (CAS 64742-89-8)
CARBON BLACK (CAS 1333-86-4)
ETHYLBENZENE (CAS 100-41-4)
MEDIUM ALIPHATIC SOLVENT NAPHTHA (CAS 64742-88-7)
METHYL ETHYL KETONE (CAS 78-93-3)
MINERAL SPIRITS (CAS 8052-41-3) Naphtha,
Hydrotreated Light (CAS 64742-49-0) N-
BUTANE (CAS 106-97-8)
TOLUENE (CAS 108-88-3)
XYLENE (CAS 1330-20-7)

US. Massachusetts RTK - Substance List

AMORPHOUS SILICA GEL (CAS 112945-52-5)
CARBON BLACK (CAS 1333-86-4)
CYCLOHEXANE (CAS 110-82-7)
ETHYLBENZENE (CAS 100-41-4)
MEDIUM ALIPHATIC SOLVENT NAPHTHA (CAS 64742-88-7)
METHYL ETHYL KETONE (CAS 78-93-3)
METHYL N-AMYL KETONE (CAS 110-43-0)
MINERAL SPIRITS (CAS 8052-41-3) N-
BUTANE (CAS 106-97-8)
n-Heptane (CAS 142-82-5)
PROPANE (CAS 74-98-6)
TOLUENE (CAS 108-88-3)
XYLENE (CAS 1330-20-7)

US. New Jersey Worker and Community Right-to-Know Act

CARBON BLACK (CAS 1333-86-4)
CYCLOHEXANE (CAS 110-82-7)
ETHYLBENZENE (CAS 100-41-4)
MEDIUM ALIPHATIC SOLVENT NAPHTHA (CAS 64742-88-7)

METHYL ETHYL KETONE (CAS 78-93-3)
 METHYL N-AMYL KETONE (CAS 110-43-0)
 N-BUTANE (CAS 106-97-8)
 n-Heptane (CAS 142-82-5)
 PROPANE (CAS 74-98-6)
 TOLUENE (CAS 108-88-3)
 XYLENE (CAS 1330-20-7)

US. Pennsylvania Worker and Community Right-to-Know Law

AMORPHOUS SILICA GEL (CAS 112945-52-5)
 CARBON BLACK (CAS 1333-86-4)
 CYCLOHEXANE (CAS 110-82-7)
 ETHYLBENZENE (CAS 100-41-4)
 MEDIUM ALIPHATIC SOLVENT NAPHTHA (CAS 64742-88-7)
 METHYL ETHYL KETONE (CAS 78-93-3)
 METHYL N-AMYL KETONE (CAS 110-43-0)
 MINERAL SPIRITS (CAS 8052-41-3)
 N-BUTANE (CAS 106-97-8)
 n-Heptane (CAS 142-82-5)
 PROPANE (CAS 74-98-6)
 TOLUENE (CAS 108-88-3)
 XYLENE (CAS 1330-20-7)

US. Rhode Island RTK

CYCLOHEXANE (CAS 110-82-7)
 ETHYLBENZENE (CAS 100-41-4)
 METHYL ETHYL KETONE (CAS 78-93-3)
 N-BUTANE (CAS 106-97-8)
 PROPANE (CAS 74-98-6)
 TOLUENE (CAS 108-88-3)
 XYLENE (CAS 1330-20-7)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

CARBON BLACK (CAS 1333-86-4) Listed: February 21, 2003
 ETHYLBENZENE (CAS 100-41-4) Listed: June 11, 2004

US - California Proposition 65 - CRT: Listed date/Developmental toxin

TOLUENE (CAS 108-88-3) Listed: January 1, 1991

US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

TOLUENE (CAS 108-88-3) Listed: August 7, 2009

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
 A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Section 16. Other information, including date of preparation or last revision

Revision date	06-30-2016
Version #	07
HMIS® ratings	Health: 2* Flammability: 4 Physical hazard: 0
NFPA ratings	Health: 2 Flammability: 4 Instability: 0
Disclaimer	<p>This information is based on our current knowledge and is believed to be accurate and reliable as of the date completed. It is intended to describe the product for the purposes of health, safety and environmental requirements only. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal, and release is not to be considered a warranty or quality specification. Therefore, it should not be construed as guaranteeing any specific property of the product. The user is responsible to ensure safe conditions for handling, storage, and disposal of the product and to assume liability for loss, injury or damage due to improper use.</p>
Revision information	<p>Hazard(s) identification: Hazard statement Fire-fighting measures: General fire hazards Accidental release measures: Methods and materials for containment and cleaning up Exposure controls/personal protection: Respiratory protection Stability and reactivity: Possibility of hazardous reactions Transport information: General information Other information, including date of preparation or last revision: Disclaimer</p>