



Whatever it takes.

UP TO
16
SEER





Whatever it takes.



FEATURES

- Auto-restart function
- Turbo Mode
- Timer
- Cold Catalyst Filter
- Sleep mode (Eco Mode)
- Refrigerant leak detection
- Louver position memory function



Model		IDU	BFHCVD09131A	BFHCVD12131A	BFHCVD18131A	BFHCVD24131A
		ODU	BCHCVD09131A	BCHCVD12131A	BCHCVD18131A	BCHCVD24131A
Power supply		V-Ph-Hz	208-230V~60Hz, 1Ph	208-230V~60Hz, 1Ph	208-230V~60Hz, 1Ph	208-230V~60Hz, 1Ph
Nominal capacity		Btu/h	9000 (4000~10000)	12000 (4500~13000)	18000 (5500~14000)	24000 (7000~25000)
Input		W	810	810	810	810
Rated Current		A	4.0	5.0	8.0	8.7
SEER			16	16	16	16
Max. input consumption		W	1700	1700	1700	1700
Max. input current		A	7.5	7.5	7.5	7.5
Indoor unit	Dimension (WxDxH)	mm	680 x 178 x 255	680 x 178 x 255	680 x 178 x 255	680 x 178 x 255
	Packing (WxDxH)	mm	745 x 255 x 330	745 x 255 x 330	745 x 255 x 330	745 x 255 x 330
	Net Gross Weight	Kg	6.5 / 8.5	6.5 / 8.5	6.5 / 8.5	6.5 / 8.5
Outdoor unit	Dimension (WxDxH)	mm	780 x 250 x 540	780 x 250 x 540	780 x 250 x 540	780 x 250 x 540
	Packing (WxDxH)	mm	910 x 335 x 585	910 x 335 x 585	910 x 335 x 585	910 x 335 x 585
	Net Gross Weight	Kg	27.5 / 30.0	27.5 / 30.0	27.5 / 30.0	27.5 / 30.0
Indoor noise level (Hi/Med/Lo)		dB(A)	39 / 35 / 32	39 / 35 / 32	39 / 35 / 32	39 / 35 / 32
Outdoor noise level		dB(A)	54	54	54	54
Refrigerant type/ Quantity	Type		R410A	R410A	R410A	R410A
	Charge volume	Kg	0.55	0.55	0.55	0.55
Design pressure		MPa	4.2/1.5	4.2 / 1.5	4.2 / 1.5	4.2 / 1.5
Refrigerant piping	Liquid side/Gas side	mm	6.35 / 9.52(1/4"/3/8")	6.35 / 9.52(1/4"/3/8")	6.35 / 9.52(1/4"/3/8")	6.35 / 9.52(1/4"/3/8")
	Max. pipe length	m	20	20	20	20
	Max difference in level	m	8	8	8	8
Controller			Remote Control			

Authorized Dealer:

C.E. LLC - Miami, FL USA

www.cebrands.com