



Cambridge Part #	A	B	C	D	E
WCS-C8	0.150 [3.8]	0.264 [6.7]	0.339 [8.6]	0.228 [5.8]	0.598 [15.2]
WCS-C6	0.161 [4.1]	0.276 [7.0]	0.386 [9.8]	0.232 [5.9]	0.693 [17.6]
WCS-C3	0.197 [5.0]	0.390 [9.9]	0.480 [12.2]	0.307 [7.8]	0.866 [22.0]
WCS-C4	0.236 [6.0]	0.441 [11.2]	0.551 [14.0]	0.311 [7.9]	0.945 [24.0]
WCS-C2	0.295 [7.5]	0.512 [13.0]	0.646 [16.4]	0.360 [9.15]	1.043 [26.5]



PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF **CODA RESOURCES**. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF **CODA RESOURCES** IS PROHIBITED.

Notes:

1. UL 94V-2 Flame Retardent Thermoplastic
2. Spring Insert: Steel
3. Working Temperature: 105°
4. Max Voltage: 300V (C8, C6) / 600V (C3, C4, C2)

NAME	DATE	CAMBRIDGE		
DRAWN	RH	11/5/09	960 Alabama Ave, Brooklyn, NY 11207 P:718-649-1666 F:718-485-4403	
UNLESS OTHERWISE SPECIFIED:		TITLE: Standard Wire Connectors		
DIMENSIONS ARE IN INCHES [] DENOTES MILLIMETER		SIZE DWG. NO. REV		
MATERIAL SEE NOTES		A	Standard Wire Connectors	A
FINISH				
DO NOT SCALE DRAWING		NOT TO SCALE		SHEET 1 OF 1