

Outdoor Unit Single Zone Heat Pump Ductless System

Outdoor Model: 38MHRQ12A--1

Submittal Data

Job Data: Location:

Buyer: Buyer P.O. #: Carrier #:

Unit Number: Model Number:

Performance Data Certified By: Date:



STANDARD FEATURES

- Cost competitive
- Auto-restart function
- Condenser high-temperature protection
- Refrigerant leakage detection
- Quiet outdoor operation
- Aluminum Blue Hydrophilic pre-coated fins

LIMITED WARRANTY*

- 10 year limited to original purchaser on compressor and parts upon timely registration, otherwise 5 years
- *For residential applications. See warranty for full details.

Specifications

System	Size	12	
	Outdoor Model	38MHRQ12A--1	
Electrical	Voltage, Phase, Cycle	V/Ph/Hz	115-1-60
	MCA	A.	13
	MOCP - Fuse Rating	A.	20
Operating Range	Cooling Outdoor DB Min - Max	°F(°C)	0~122 (-17~50)
	Heating Outdoor DB Min - Max	°F(°C)	0~86 (-17~30)
Piping	Total Piping Length	ft (m)	82 (25)
	Piping Lift*	ft (m)	32 (10)
	Pipe Connection Size - Liquid	in (mm)	1/4 (6.35)
	Pipe Connection Size - Suction	in (mm)	1/2 (12.7)
Refrigerant	Type	R410A	
	Charge	lbs (kg)	2.11 (0.96)
	Metering Device	EEV	
Outdoor Coil	Face Area	Sq. Ft.	4.1
	No. Rows	1.5	
	Fins per inch	18	
	Circuits	4	
Compressor	Compressor Type	Rotary Inverter	
	Model	ASN98D22UFZ	
	Oil Type	VG74	
	Oil Charge	Fl. Oz.	13.0
	Rated Current	RLA	9.5

* Condensing unit above or below indoor unit

Performance High Wall	Energy Star		NO
	Cooling System Tons		1
	Cooling Rated Capacity	Btu/h	12000
	Cooling Cap. Range Min - Max	Btu/h	3000~12500
	SEER	Btu/Wh	16.8
	EER	Btu/Wh	10.8
	Heating Rated Capacity (47°F)	Btu/h	12000
	Heating Maximum Capacity (5°F)	Btu/h	9000
	Heating Cap. Range Min - Max	Btu/h	3000~12800
	HSPF		9
	COP (47°F)	W/W	3.1
	COP (5°F)	W/W	1.6
Outdoor	Unit Width	in (mm)	30.31(770)
	Unit Height	in (mm)	21.85(555)
	Unit Depth	in (mm)	11.81(300)
	Net Weight	lbs (kg)	65.0(29.5)
	Airflow	CFM	506
	Sound Pressure	dB(A)	53

Compatibility Table

OUTDOOR UNIT	38MHRQ12A--1
INDOOR UNIT	40MHHQ12--1

Construction View

