

40MA*Q High Wall

Sizes: 09 / 12 / 18 / 24 / 30 / 36

Select sizes are ENERGY STAR® certified, based on outdoor unit pairing

Features:

- Available in 115V and 208/230V
- Modes: cool, heat, dry, fan, auto
- Auto louver mode
- Turbo mode
- 4 fan speeds
- Sleep mode
- Follow Me
- Quiet operation, as low as 27 dB(a)
- 46° F heating mode (heating setback)

Controls:

- Wireless remote controller included with indoor unit
- Wired remote controller (optional)

Accessories:

- Condensate pump (115V and 230V optional)
- Insulated 25' line set

Compatible with:

- 38MA*R Outdoor Unit Single Zone
- 38MA*Q Outdoor Unit Single Zone
- 38MG*Q Outdoor Unit Multi-Zone



This versatile, Performance™ Series wall-mounted indoor unit delivers deluxe comfort with four fan speeds and automatic louvers. It's an efficient addition to either a Single Zone, MA High Wall Ductless System, or as part of our MG Multi-Zone Ductless System. Either way, it provides personalized comfort where you need it.



Condensate Pump
53DS-900---117 (115V)
53DS-900---118 (208/230V)



Optional Wired Controller
KSACN0101AAA

Performance
SERIES

40MA*Q High Wall

HEAT PUMP										
Size			9	12	9	12	18	24	30	36
System	Indoor Model		40MAQB09B--1	40MAQB12B--1	40MAQB09B--3	40MAQB12B--3	40MAQB18B--3	40MAQB24B--3	40MAQB30B--3	40MAQB36B--3
Electrical	Voltage, Phase, Cycle	V/Ph/Hz	115-1-60	115-1-60	208/230-1-60	208/230-1-60	208/230-1-60	208/230-1-60	208/230-1-60	208/230-1-60
	Power Supply		Indoor unit powered from outdoor unit							
Operating Range	Cooling Indoor DB Min - Max	° F (° C)	63~86 (17~30)	63~86 (17~30)	63~86 (17~30)	63~86 (17~30)	63~86 (17~30)	63~86 (17~30)	63~86 (17~30)	63~86 (17~30)
	Heating Indoor DB Min - Max	° F (° C)	32~86 (0~30)	32~86 (0~30)	32~86 (0~30)	32~86 (0~30)	32~86 (0~30)	32~86 (0~30)	32~86 (0~30)	32~86 (0~30)
Piping	Pipe Connection Size - Liquid	in (mm)	1/4 (6.35)	1/4 (6.35)	1/4 (6.35)	1/4 (6.35)	1/4 (6.35)	3/8 (9.52)	3/8 (9.52)	3/8 (9.52)
	Pipe Connection Size - Suction	in (mm)	3/8 (9.52)	1/2 (12.7)	3/8 (9.52)	1/2 (12.7)	1/2 (12.7)	5/8 (16)	5/8 (16)	5/8 (16)
Indoor	Unit Width	in (mm)	32.87 (835)	32.87 (835)	32.87 (835)	32.87 (835)	38.98 (990)	46.69 (1186)	46.69 (1186)	46.69 (1186)
	Unit Height	in (mm)	11.02 (280)	11.02 (280)	11.02 (280)	11.02 (280)	12.40 (315)	13.39 (343)	13.39 (343)	13.39 (343)
	Unit Depth	in (mm)	7.80 (198)	7.80 (198)	7.80 (198)	7.80 (198)	8.58 (218)	10.16 (258)	10.16 (258)	10.16 (258)
	Net Weight	lbs (kg)	19.18 (8.7)	19.18 (8.7)	19.18 (8.7)	19.18 (8.7)	26.46 (12.0)	40.12 (18.2)	40.12 (18.2)	40.12 (18.2)
	Number of Fan Speeds		4	4	4	4	4	4	4	4
	Airflow (lowest to highest)	CFM	210/290/360/380	210/300/360/380	210/290/360/380	210/300/360/380	310/450/650/680	520/620/780/870	520/620/780/870	520/620/780/870
	Sound Pressure (lowest to highest)	dB(A)	27/34/42	27/34/42	27/34/42	27/34/42	33/40/46	39/45/50	39/45/50	39/45/50
	Air throw Data	ft (m)	23 (7)	23 (7)	23 (7)	23 (7)	30 (9)	36 (11)	36 (11)	36 (11)

Compatibility								
Size	9	12	9	12	18	24	30	36
Indoor Unit	40MAQB09B--1	40MAQB12B--1	40MAQB09B--3	40MAQB12B--3	40MAQB18B--3	40MAQB24B--3	40MAQB30B--3	40MAQB36B--3
Outdoor Unit ¹	38MAQB09R--1	38MAQB12R--1	38MAQB09R--3	38MAQB12R--3	38MAQB18R--3	38MAQB24R--3	38MAQB30R--3	38MAQB36R--3
	38MAQB09---1	38MAQB12---1	38MAQB09---3	38MAQB12---3	38MAQB18---3	38MAQB24---3	38MAQB30---3	
			38MGQC18---3					
			38MGQD27---3					
			38MGQF36---3					
			38MGQF48---3					

¹ For Outdoor Unit performance information, please reference the Carrier Ductless Full Line Catalog.



Visit our website at CarrierDuctless.com

7310 West Morris Street, Indianapolis, IN 46231