

SMMSi / SHRMi VRF Indoor Unit MMK-AP0153H2UL - High Wall

TOSHIBA
Carrier

Submittal Data

Job Data _____ Location _____
Buyer _____ Buyer PO # _____ Carrier # _____
Unit Number _____ Model Number _____
Performance Data Certified By _____ Date _____



SMMSi / SHRMi VRF High Wall Features

- R-410A Refrigerant
- Six sizes from 7,000 to 24,000 Btu/h
- Quiet operation, as low as 30 dBA
- Vertical airflow can be set to swing or fixed position
- Air throw up to 23 ft
- Auto or manually set three fan speeds
- Easy to remove cleanable filter
- Five-year parts limited warranty

Indoor Unit Model	MMK-AP0153H2UL	
PERFORMANCE		
Cooling Rated Capacity	Btu/h	15,400
Heating Rated Capacity	Btu/h	17,000
Fan Type (Qty)		Cross-Flow (1)
Airflow (L / M / H)	CFM	320 / 390 / 490
Sound Pressure (L / M / H)	dBA	34.5 / 38 / 43
ELECTRICAL		
Power Supply	V/Ph/Hz	208-230/1/60
Power Consumption (Input)	kW	0.043
Full Load Amps (FLA)	A	0.4
Minimum Circuit Amps (MCA)	A	0.5
Maximum Overcurrent Protection (MOCP)	A	15
Motor Type	DC Inverter Driven	
Motor Watts		30

PHYSICAL DATA

Pipe Connection Size - Liquid (High Pressure)	in.	1/4 (Flare)
Pipe Connection Size - Gas (Low Pressure)	in.	1/2 (Flare)
Pipe Connection Size - Drain (OD)	in.	7/8
Pipe Connection Size - Drain (ID)	in.	5/8
Refrigerant	R-410A	
External Finish	Munsell 2.5GY9.0/0.5	
Unit Width	in.	41-5/16
Unit Height	in.	12-9/16
Unit Depth	in.	9
Unit Net Weight	lb	33

CONTROLS

Wireless Remote Controller (Standard)

ACCESSORIES (Optional)

- ☐ Lite Vision Plus Remote Controller (7-Day Programmable) RBC-AMS51E-ES
- ☐ Simple Wired Remote Control RBC-AS41UL
- ☐ Remote Sensor TCB-TC41LUL
- ☐ Wired Remote Controller RBC-AMT32UL
- ☐ Condensate Drain Pump Kit 53DS-900---118

Manufacturer reserves the right to discontinue, or change at any time, specifications or designs without notice and without incurring obligations.

DIMENSIONAL DRAWING INDOOR UNIT HIGH WALL MMK-AP0153H2UL

