




HI WALL
13 SEER
60 Hz

Features:

R-410A
REFRIGERANT

- Cooling Only
- R-410A refrigerant
- Remote control
- LED Display
- Sleep Mode
- Easy clean panel
- Quiet operation
- Auto restart function
- Dehumidification Mode
- Anti Mildew
- Auto Diagnostic function
- Gold fin in outdoor and indoor units



TECHNICAL SPECIFICATIONS

Outdoor Unit Model No.		CG42A-009-H1U2C	CG42A-012-H1U2C	CG42A-012-H3U2C	CG42A-018-H3U2C	CG42A-024-H3U2C
Model number including piping kit		CG42A-009PH1U2C	CG42A-012PH1U2C	CG42A-012PH3U2C	CG42A-018PH3U2C	CG42A-024PH3U2C
Power supply		115~/60Hz/1Ph	115~/60Hz/1P	208-230V/60Hz/1Ph	208-230V/60Hz/1Ph	208-230V/60Hz/1Ph
Cooling capacity	BTUH	9,000	11986	12,000	18,000	24,000
SEER		13	13	13	13	13
Dimensions (W x H x D)	mm	760x552x256	760x552x256	760x552x256	902x660x307	900x800x360
Net Weight	kg	32	33	30	49	58
Packing dimensions (W x H x D)	mm	863x605x376	863x605x376	863x605x376	1037x705x433	1031x925x447
Gross weight	kg	35	36	34	54	64
Current	A	7.3	4.87	4.6	6.7	9.7
Compressor		Rotary	Rotary	Rotary	Rotary	Rotary
Noise level	dB(A)	50	52	52	54	59
Connecting Pipe (Gas)	Inches	3/8"	3/8"	3/8"	1/2"	5/8"
Connecting Pipe (Liquid)	Inches	1/4"	1/4"	1/4"	1/4"	3/8"
Indoor Unit Model No.		CH42A-009-H1U2C	CH42A-012-H1U2C	CH42A-012-H3U2C	CH42A-018-H3U2C	CH42A-024-H3U2C
Dimensions (W x H x D)	mm	800x280x185	898x280x202	898x280x202	1033x313x202	1250x325x245
Net weight	kg	10	11	11	14	18
Packing dimensions (W x H x D)	mm	885x366x278	995x365x298	995x365x298	1103x395x292	1317x422x338
Gross weight	kg	13	14	14	17	25
Noise level	(Hi/Med/Lo)	40/38/36	42/40/38	42/40/38	56/54/50	57/55/52
Maximum pipe length	m	15	15	15	15	15
Maximum vertical separation	m	5	5	5	5	5



Carrier InterAmerica Corporation
Miami, Florida USA
www.ciac-comfort.com

Authorized Dealer: