

CR22K6-PFV

HCFC, R-22, 60 Hz, 1 -Phase, 208/230 V

Air Conditioning



Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evaporator Temp. (°F)	45	45
Condensing Temp. (°F)	130	100
Return Gas Temp. (°F)	65	65
Liquid Temp. (°F)	115	85
Capacity (Btu/hr)	22100	29500
Power (W):	2040	1670
Current (Amps):	9.20	7.60
EER (Btu/Wh):	10.80	17.70
Mass Flow (lbs/hr):	323	380
<u>Sound Data @</u>		
Sound Power (dBA):	72 Avg	77 Max
Vibration mils(peak-peak):	1.9 Avg	2.9 Max
Record Date:	1993-06-18	

Electrical

LRA-High*(Amp):	50.0
LRA Low* (Amp):	
LRA-Half Winding (Amp):	
MCC (Amps):	15.3
Max Operating Current(Amp):	12.2
RLA, MCC/1.4;use for contactor selection (Amp):	10.9
RLA, MCC/1.56;use for breaker & wire size selection (Amp):	9.8
RPM:	
UL File No:	
UL File Date:	1984-12-28
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.	

Mechanical

Displacement(in ³ /Rev):	2.49
Displacement(ft ³ /hr):	302.57
Overall Length (in):	10.23
Overall Width (in):	9.65
Overall Height (in):	13.19
Mounting Length (in):	7.50
Mounting Width (in):	7.50
Mounting Height (in):	13.56 *
Suction Size (in),Type:	3/4 Stub
Discharge Size (in),Type:	1/2 Stub
Initial Oil Charge (oz):	45
Oil Recharge (oz):	43
Net Weight (lbs):	66.0
Internal Free Volume (in ³):	455.0
Horse Power:	
*Overall compressor height on Copeland Brand Product's specified mounting grommets.	

Capacitors

Type	Part No	Low MFD	High MFD	Volts	User Description
Start Capacitor	014-0061-04	145.0	175.0	220	HIGH TORQUE
Start Capacitor	014-0061-16	43.0	52.0	330	LOW TORQUE
Run Capacitor	014-0064-06	30.0	0.0	370	

Alternate Applications

Refrigerant	Voltage	Phase	Freq (Hz)	Application
R-22 HCFC	200	1	50	UL High Temp