

5511M Sealant

Non-Drying Pumpable Sealant

Job: _____

Location: _____

Submitted to: _____

Prepared by: _____

Approved by: _____

Date: _____

MANUFACTURED BY



1502 Industrial Drive,
Monogahela, PA 15063
800-245-3188
www.ductmate.com

INDUSTRY REGULATIONS



ORDERING INFORMATION

Products sold through Ductmate Distributor Network

PRODUCT GUARANTEE

Ductmate warrants that 5511M, when properly installed and maintained, will be free from defects in material and workmanship, and will comply with all written specifications made by Ductmate at time of sale. Warranty shall run for a period of one year from the date of manufacture.

DESCRIPTION

5511M is a non-skinning, non-drying polymer based pump able sealant

BASIC USE

This product was developed to provide an airtight, watertight, flexible seal for metal to metal concealed joints. As a non-skinning and non-drying sealant, 5511M has been specifically formulated for precise applications to panel joints (Pittsburgh seams) at the roll forming line.

FEATURES

Exhibits excellent adhesion to most non-porous surfaces. This non-oxidizing product is capable of withstanding joint movement without cracking. The pumping consistency is particularly efficient at leak proofing concealed metal joints.

TECHNICAL INFORMATION

% Solids:	≥ 90 %
Color:	Off white to Grey
Weight per Gallon:	12 lbs ± 2lbs
Shelf/Service Life:	Indefinite (unopened Container)
Service Temp:	0°F to 200° F
Extrudability:	3-8 s/mL ASTM D1252
Slump:	≤ 0.2" ASTM D2202
Mold & Mildew:	0- 2 % growth ASTM G21
Tack Strength:	> 2,000 Psi peak ASTM C907mod
Application Method:	Hand or power pump
Packaging:	5 U.S. Gallon pails (19L) 55 U.S. Gallon drums (208 L)