



# DUROSEAL<sup>®</sup>

## WATER BASED DUCT SEALER

### SMOOTH EDS-RS

EDS-RS is a smooth Water Based Duct Sealer designed for use in high velocity air conditioning, refrigeration, ventilating, and air distributing systems up to 15 w.g. It is suitable for use in both indoor and outdoor applications and exceeds all SMACNA Pressure and Sealing Classes.



#### FEATURES

- UL Listed 181B-M
- Zero VOC's
- Qualifies for LEED EQ Credit 4.1
- Indoor/Outdoor Use - UV inhibitors
- Fast Dry Time - Dry to the touch in 3-6 hours, 90% cured in 18-36 hours
- Mold & Mildew Resistant
- Higher solids content – 73% +/- 1% allows the product to cure quicker and pressure test the jobs quicker
- Less shrinkage - Allows installer to fill larger joints and provides less slump
- Excellent adhesion to metal
- Very good elasticity - Less likely to crack or separate from duct during transportation, installation, and equipment start up
- Very thixotropic - Product brushes or trowels smooth and effortlessly; will not run, sag or drip during or after application
- Product can be easily scooped out of the bucket onto the brush without the duct sealer sliding off the brush
- Non Flammable and Non Hazardous
- No solvents in the product
- Very little odor - No ammonia smell
- Can be exposed to moisture quicker when applied outdoors because it cures much quicker than other products on the market
- Anti-microbial - biocide package included to prevent the growth of mold
- Cartridge is auto-filled, creating less air pockets



MADE IN U.S.A.



5GB7  
**181B-M**

FOR USE WITH UL LISTED  
FLEXIBLE AIR DUCTS OR CONNECTORS.

ITEM #	CODE	DESCRIPTION
5231	EDS-RS1	Smooth Duct Sealer - 1 Gallon Pail
5233	EDS-RSC	Smooth Duct Sealer - Cartridge

Duro Dyne East Division, Bay Shore, NY  
Duro Dyne Midwest Division, Fairfield, OH  
Duro Dyne West Division, Fontana, CA  
Duro Dyne Canada, Lachine, Quebec, Canada  
[www.durodyne.com](http://www.durodyne.com)

631-249-9000 Fax: 631-249-8346  
513-870-6000 Fax: 513-870-6005  
562-926-1774 Fax: 562-926-5778  
514-422-9760 Fax: 514-636-0328  
E-mail: [durodyne@durodyne.com](mailto:durodyne@durodyne.com)



© Duro Dyne Corp.  
Printed in USA 4/16  
BC006006