SUBMITTAL RECORD_____
JOB _____
LOCATION_____
SUBMITTED TO_____
SUBMITTAL PREPARED BY_____
APPROVED BY_____
DATE_____

Submittal Form
Conduit

DESCRIPTION

Conduit is used to support duct sizes over 48” or smaller duct in high pressure applications. Duro Dyne offers conduit in 1/2” and 3/4” sizes in 10 ft. lengths.



FEATURES

- Complies with ANSI C80.3
- Hot Dip Galvanized Conduit

Size	Outside Diameter	Wall Thickness	Minium Weight	Length
1/2”	0.706”	0.042”	0.286 lb/ft	10’
3/4”	0.922”	0.049”	0.435 lb/ft	10’

In accordance with: SMACNA Third Edition 2005 internal conduit pressure tables.

ITEM#	CODE	DESCRIPTION
21099	MC1210	1/2in Thin Wall Conduit - 10ft Lengths
21100	MC3410	3/4in Thin Wall Conduit - 10ft Lengths

Duro Dyne East Division, Bay Shore, NY 631-249-9000 Fax: 631-249-8346
Duro Dyne Midwest Division, Hamilton, OH 513-870-6000 Fax: 513-870-6005
Duro Dyne West Division, Fontana, CA 562-926-1774 Fax: 562-926-5778
Duro Dyne Canada, Lachine, Quebec, Canada 514-422-9760 Fax: 514-636-0328
www.durodyne.com E-mail: durodyne@durodyne.com

©2016 Duro Dyne Corporation
Printed in USA 12/2/16
BO050032