

TECHNICAL DATA SHEET

C.S.A. GAS INTERCHANGE QUICK DISCONNECTS (QD-GMC)

Applications: Propane / Natural Gas



- C.S.A. certified for natural gas and L.P. gas - air mixtures.
- Sizes 1/4, 3/8, 1/2 & 3/4 Quick Disconnects Rated To 60 P.S.I.
- Sizes 1 & 1-1/4 Quick Disconnects Rated To 1/2 P.S.I.



Quick Disconnect BTU Capacity (Flow capacities are based on 0.64 specific gravity @ 0.3" w.c. pressure drop)					
1/4	3/8	1/2	3/4	1	1-1/4
50,000	85,000	120,000	260,000	310,000	500,000

VALVED COUPLER - BRASS			NIPPLE - BRASS		
PART No.	Body Size	Female Pipe	PART No.	Body Size	Pipe
QD-GMC4-4F	1/4	1/4	QD-GMRVN4-4M	1/4	1/4 NPT
QD-GMC6-6F	3/8	3/8	QD-GMN6-6F	3/8	3/8 FPT
BB-QD-GMC6-6F	3/8	3/8	QD-GMN8-8F	1/2	1/2 FPT
(Blister Box Packaging)			QD-GMN12-12F	3/4	3/4 FPT
QD-GMC8-8F	1/2	1/2	QD-GMN16-16F	1	1 FPT
QD-GMC12-12F	3/4	3/4	QD-GMN20-20F	1-1/4	1-1/4 FPT
QD-GMC16-16F	1	1			
QD-GMC20-20F	1-1/4	1-1/4			

PART No.	Body Size	Style
QD-GMC6-Y	3/8	Y Splitter

Designed for use with our
NGO Series Gas Outlets

SIZE	COUPLER PLUG	NIPPLE CAP
1/4	QD-RVSDC-4	--
3/8	QD-GMDP-6	QD-GMDC-6
1/2	QD-GMDP-8	QD-GMDC-8
3/4	QD-GMDP-12	QD-GMDC-12



Retail packaging available.

