



## 14/4 STRANDED THHN 600V TRAY

### Description:

AWG 14/4 stranded bare copper conductors, (THHN) PVC/nylon, Sunlight Resistance, RoHS compliant PVC jacketed cable, 600V Direct Burial listed by UL.

### Physical Information:

Conductor  
Type: 14 AWG STR 19/.0147" Bare Copper  
Diameter: 0.0735" nom.

Insulation  
Type: PVC w/Nylon  
Thickness: PVC – 0.015" nom  
Nylon – 0.005" nom  
Color: Black, White, Red, Green  
Twisted and cabled with poly fillers.

Jacket  
Type: PVC  
Color: Black  
Thickness: 0.055" nom.  
Diameter: 0.365" nom.

Print Legend: HONEYWELL 14/4C POWER & CONTROL CABLE TYPE TC UL 1277 EXXXXXX  
DIRECT BURIAL SUN RES (RoHS) W/O# XXXXXX-XXXXXX XXXXX FT

Packaging: 250-ft wooden Reel, 150 lbs capacity

Rating  
Voltage: 600 V  
Temperature: -20 to 90 C  
Listing: Tray Cable - UL 1277, Direct Burial, Sunlight Resistance

Application: Mini Split Systems

Part Number: 10700108