



GENESIS SERIES

Low Voltage Cable Part No. 3251

Description: 22 AWG 1PR STR CMP-CL2P
Specifications: UL Standards 13 & 444; NEC Articles 725 & 800

Construction:

Conductor 22 AWG 7/30 Tinned Copper
Insulation FEP
Insulation Thickness 0.023" nom.
Insulation Colors Blk, White
Insulation Diameter 0.076" nom.
Lay Length 3.0" nom.
Drain Wire 22 AWG 7/28 Tinned Copper
Shield 0.001" Thick Aluminum/Mylar

Jacket Plenum PVC
Color Teal or Orange
Jacket Thickness 0.015" nom.
Outside Diameter 0.185" nom.
Legend (Ink Print)

HONEYWELL P/N 3251 1PR22 SHIELDED LOW CAP 3038058 (ETL) CL2P OR CMP
(RoHS) C(ETL) FT6 W/O# XXXXXX-XXXX XXXXXX FT RM# A B C D E F 1 2 3 4 5 6 7 8 9

Properties

Temperature Rating -20 to 75 °C
Operating Voltage 300 Volts max.
Capacitance 14.5 pf/ft nom.
Impedance 100 Ohms nom.
DC Resistance 16.5 Ohms/M' at 20°C
Flame Rating UL910, NFPA 262, CSA FT6