

STANDBY GENERATOR

35 kW

LIQUID-COOLED GENERATOR SET

Standby Power Rating

Model HT035 - 35 kW 60Hz



INCLUDES

- Two Line LCD Tri-lingual Digital Sync Controller
- Electronic Governor
- Closed Coolant Recovery System
- Flexible Fuel Line Connector
- Wireless Remote Monitor*
- Sound Attenuated Aluminum Enclosure
- UV/Ozone Resistant Hoses
- Natural Gas or LP Gas Operation
- 5 Year Limited Warranty*
- UL 2200 Listed

Not for resale in CA/MA

* 3-Phase systems receive a 2 Year Limited Warranty and do not include the clipped roof corners or the remote monitor.

FEATURES

- **INNOVATIVE DESIGN & PROTOTYPE TESTING** are key components of our success in “IMPROVING POWER BY DESIGN.” But it doesn’t stop there. Total commitment to component testing, reliability testing, environmental testing, destruction and life testing, plus testing to applicable CSA, NEMA, EGSA, and other standards, allows you to choose Honeywell generators with the confidence that these systems will provide superior performance.
- **TEST CRITERIA**
 - ◆ PROTOTYPE TESTED
 - ◆ SYSTEM TORSIONAL TESTED
 - ◆ NEMA MG1-22 EVALUATION
 - ◆ MOTOR STARTING ABILITY
- **SOLID-STATE, FREQUENCY COMPENSATED VOLTAGE REGULATION** This state-of-the-art power maximizing regulation system is standard on all Honeywell models. It provides optimized FAST RESPONSE to changing load conditions and MAXIMUM MOTOR STARTING CAPABILITY by electronically torque-matching the surge loads to the engine. An unequalled $\pm 1\%$ voltage regulation.
- **SINGLE SOURCE SERVICE RESPONSE** from our extensive dealer network provides parts and service know-how for the entire unit, from the engine to the smallest electronic component.
- **Honeywell TRANSFER SWITCHES** The Honeywell generator line offers its own transfer systems and controls for total system compatibility.

35 kW

LIQUID-COOLED GENERATOR SET

Application & Engineering Data

GENERATOR SPECIFICATIONS

• Type	Synchronous
• Rotor Insulation	Class H
• Stator Insulation	Class H
• Telephone Interference Factor (TIF)	<50
• Alternator Output Leads Phase 3	4 wire
• Bearings	Sealed Ball
• Coupling	Flexible Disc
• Load Capacity (Standby Rating)	35 kW
• Excitation System	Direct

ENGINE SPECIFICATIONS

• Make	Generac
• Model	Inline 4
• Cylinders	4
• Displacement	2.4 Liter
• Bore	3.41
• Stroke	3.94
• Compression Ratio	9.5:1
• Intake Air System	Turbocharged/ Aftercooled
• Valve Seats	Hardened
• Lifter Type	Hydraulic

GOVERNOR SPECIFICATIONS

• Type	Electronic	
• Frequency Regulation	Isochronous	
• Steady State Regulation	± 0.25%	
• Adjustments For	Speed	Yes
	Droop	Yes

VOLTAGE REGULATION

• Type	Electronic
• Sensing	Single Phase
• Regulation	± 1%

GENERATOR FEATURES

- Revolving field heavy duty generator
- Directly connected to the engine
- Operating temperature rise 120 °C above a 40 °C ambient
- Insulation is Class H rated at 150 °C rise
- All models are fully prototyped tested

ENGINE LUBRICATION SYSTEM

• Oil Pump	Gear
• Oil Filter	Full flow spin-on cartridge
• Crankcase	4 Quarts

ENGINE COOLING SYSTEM

• Type	Closed
• Water Pump	Belt Driven
• Fan Speed	1500
• Fan Diameter	22 inches
• Fan Mode	Puller

FUEL SYSTEM

• Fuel Type	Natural gas, propane vapor
• Carburetor	Down Draft
• Secondary Fuel Regulator	Standard
• Fuel Shut Off Solenoid	Standard
• Operating Fuel Pressure	5" - 14" H ₂ O

ELECTRICAL SYSTEM

• Battery Charge Alternator	12V 30 Amp
• Static Battery Charger	2 Amp
• Recommended Battery	Group 26, 525CCA
• System Voltage	12 Volts

ENCLOSURE FEATURES

- **Aluminum weather protective enclosure** – Ensures protection against mother nature. Electrostatically applied textured epoxy paint for added durability.
- **Enclosed critical grade muffler** – Quiet, critical grade muffler is mounted inside the unit to prevent injuries.
- **Small, compact, attractive** – Makes for an easy, eye appealing installation.
- **SAE** – Sound attenuated enclosure ensures quiet operation.

Rating definitions - Standby: Applicable for supplying emergency power for the duration of the utility power outage. No overload capability is available for this rating. (All ratings in accordance with BS5514, ISO3046 and DIN6271). (All ratings in accordance with BS5514, ISO3046, ISO8528, SAE J1349 and DIN6271).

Operating Data

KW RATING (LP/NG)		35/35			
ENGINE SIZE		2.4 Liter Inline 4			
GENERATOR OUTPUT VOLTAGE/KW - 60Hz	kW LPG	AMP	kW Nat. Gas	AMP	CB Size
120/240V, 1-phase, 1.0 pf	35	146	35	146	175
120/208V, 3-phase, 0.8 pf	35	121	35	121	150
120/240V, 3-phase, 0.8 pf	35	105	35	105	125
277/480V, 3-phase, 0.8 pf	35	52	35	52	60
ENGINE FUEL CONSUMPTION (Natural Gas) (Propane)	Natural Gas		Propane		
	(ft ³ /hr.)		(gal/hr.)		cu ft/hr
Exercise cycle	48		0.5		19
25% of rated load	156		1.7		62
50% of rated load	282		3.1		112
75% of rated load	392		4.3		156
100% of rated load*	503		5.5		200
For Btu content, multiply ft ³ /hr x 2520 (LP) or ft ³ /hr x 1000 (NG)					
ENGINE COOLING					
Air flow (inlet air including alternator and combustion air)	ft ³ /min.		2,200		
System coolant capacity	US gal.		2.5		
Heat rejection to coolant	BTU/hr.		145,000		
Max. operating air temp. on radiator	°C (°F)		60 (150)		
Max. ambient temperature	°C (°F)		50 (140)		
COMBUSTION AIR REQUIREMENTS					
Flow at rated power 60 Hz	cfm		106		
SOUND EMISSIONS IN DBA					
Exercising at 7 meters			58		
Normal operation at 7 meters			64		
EXHAUST					
Exhaust flow at rated output 60 Hz	cfm		300		
Exhaust temp. at muffler outlet	°F		1075		
ENGINE PARAMETERS					
Rated synchronous RPM	60 Hz		1800		
POWER ADJUSTMENT FOR AMBIENT CONDIIONS					
Temperature Deration	3% for every 10 °C above - °C 1.65% for every 10 °F above - °F		25 77		
Altitude Deration	1% for every 100 m above - m 3% for every 1000 ft. above - ft.		915 3000		


Refer to "Emissions Data Sheets" for maximum fuel flow for EPA and SCAQMD permitting purposes.

RATING: All three phases units are rated at 0.8 power factor. All single phase units are rated at 1.0 power factor. STANDBY RATING: Standby ratings apply to installations served by a reliable utility source. The standby rating is applicable to varying loads for the duration of a power outage. There is no overload capability for this rating. Ratings are in accordance with ISO-3046-1. Design and specifications are subject to change without notice.

35 kW

LIQUID-COOLED GENERATOR SETS

Interconnections



CONTROL FEATURES

<ul style="list-style-type: none"> • 2-Line Plain Text LCD Display • Mode Switch <ul style="list-style-type: none"> -Auto -Off -Manual/Test (start) • Programmable start delay between 10-30 seconds • Engine Start Sequence <ul style="list-style-type: none"> • Engine Warm-up • Engine Cool-Down • Starter Lock-out • Smart Battery Charger • Automatic Voltage Regulation with Over and Under Voltage Protection 	<p>Simple user interface for ease of operation</p> <p>Automatic Start on Utility failure. 7 day exerciser</p> <p>Stops unit. Power is removed. Control and charger still operate.</p> <p>Start with starter control, unit stays on. If utility fails, transfer to load takes place.</p> <p>Standard</p> <p>Cyclic cranking: 16 sec. on, 7 rest (90 sec. maximum duration)</p> <p>5 seconds</p> <p>1 minute</p> <p>Starter cannot re-engage until 5 sec. after engine has stopped.</p> <p>Standard</p> <p>Standard</p>	<ul style="list-style-type: none"> • Automatic Low Oil Pressure Shutdown • Overspeed Shutdown • High Temperature Shutdown • Overcrank Protection • Safety Fused • Failure to Transfer Protectio • Low Battery Protection • 50 Event Run Log • Future Set Capable Exerciser • Incorrect Wiring Protection • Internal Fault Protection • Common External Fault Capability • Governor Failure Protection 	<p>Standard</p>
--	---	--	---

Single and three phase connections may vary , refer to the owner's manual for specific connection information.

AVAILABLE ACCESSORIES

Model #	Product	Description
5630	Cold Weather Kit	If the temperature regularly falls below 32° F, install a cold weather kit to maintain optimal battery temperature. Kit consists of battery warmer with thermostat built into the wrap.
5616	Extreme Cold Weather Kit	Recommended where the temperature regularly falls below 32° F for extended periods of time. For liquid cooled units only.
6160	Paint Kit	Paint Kit
5656	Scheduled Maintenance Kit	The Liquid-Cooled Scheduled Maintenance Kits offer all the hardware necessary to perform a complete maintenance on Honeywell liquid-cooled generators.
5951	Advanced Sync Wireless Remote	Remotely control generator functions with the advanced model's LED display. In addition to remote testing of the generator, set the exercise cycle and maintenance interval reminders
6102	DLM Load Control Module (50 Amps)	DLM Modules are used in conjunction with the Sync Smart Switch to increase its load management capabilities. It gives the Sync Smart Switch additional load management flexibility not found in any other transfer switch.

Generac Power Systems, Inc.

S45 W29290 Hwy. 59

Waukesha, WI 53187

Tel: 1-855-GEN-INFO

honeywellgenerators.com

0190670SBY-D

Dec 2011

© Generac Power Systems, Inc. All rights reserved.
Specifications subject to change without notice.

The Honeywell Trademark is used under
license from Honeywell International Inc.

Honeywell International Inc. makes no representation
or warranties with respect to this product.

