

PTFE TAPE QUALITY IMPORT PIPE JOINT COMPOUND TAPE S-TAPE-SPEC

PRODUCT DESCRIPTION

PRODUCT

PTFE[†] TAPE Quality Import Pipe Joint Compound Tape

DESCRIPTION

PTFE TAPE is an economical, all purpose, non-seizing, PTFE thread sealing compound in tape form that produces a leakproof seal on all types of metal and plastic threaded connections. 3.5 MIL PTFE (polytetrafluoroethylene) Tape supplied on finished spools.

RECOMMENDED USES

PTFE TAPE can be used on all types of threaded fittings for passage of water potable and non-potable, most chemicals, oxygen, gas, hydraulic and high pressure lines.

Chemically inert. It is suitable for use on systems carrying almost all types of chemicals and gases including:

Acids, Dilute	Hydraulic Oils
Air, Compressed	Hydrogen
Aliphatic Solvents	Inert Gases
Alkalis, Dilute	Jet Fuel
Ammonia	Kerosene
Brine	Lacquer
Butane	L P Gases
Carbon Dioxide	Mineral Oils
Castor Oils	Naphtha
Chlorinated Water	Natural Gas
Coal Tar Naphtha	Nitrogen Gas
Cutting Oils	Propane
Diesel Fuel Oil	Refrigeration
Fatty Acids	Gases
Freons (All)	Soap, Liquid
Gasohol	Steam Lines
Gasoline [^]	Sugar, Liquid
Glycol	Vegetable Oils
Heating Oils	Water
Helium, Gaseous	Xylol

COLOR/CONSISTENCY

The tape is white in color. It shall be free of visible voids, cracks, folds, contamination and has consistent physical properties. **PTFE TAPE** has an indefinite shelf life.

S-TAPE-SPEC

© 2014 J.C. Whitlam Manufacturing Company

[†]PolyTetraFluoroEthylene [^]Contact J.C. Whitlam Mfg. Co. for compatible blends.

*Dupont registered trademarks **FlowGuard GOLD and Blazemaster are registered trademarks of The Lubrizol Corporation

Celanese registered trademark *General Electric Plastics registered trademark

PTFE (polytetrafluoroethylene) is the same chemical composition as Dupont Teflon[®]

The information contained in this bulletin is correct to the best of our knowledge. The recommendations or suggestions herein are made without guarantee or representation as to result, since the conditions of use are beyond our control. We suggest that you evaluate the recommendations contained in this bulletin. No statement is to be construed as violating any copyright or patent. They are intended only as a source of information.

TEMPERATURE RANGE USE

Gases:

-450°F (-268°C) to 500°F (260°C)

Liquids:

-450°F (-268°C) to 500°F (260°C)

PRESSURE RANGE USE

Gases:

up to 10,000 PSI (1450 kPa)

Liquids:

up to 3,000 PSI (435 kPa)

The system may be pressurized immediately after assembly.

FOR USE ON THREADED

ABS, PVC, CPVC, Delrin*, Zytel*, FlowGuard GOLD** CPVC, Blazemaster** CPVC, Fiberglass, Nylon, Polypropylene, Polybutylene, Polyethylene, Celcon***, Cyclocac**** plastics, and all types of metal.

CORROSIVENESS

PTFE TAPE is non-corrosive, and prevents the corrosion and seizing of threads.

U.S. MILITARY SPECIFICATIONS

PTFE TAPE meets MIL-T-27730A.

ENVIRONMENTAL STATEMENT

PTFE TAPE is chemically inert to virtually all environments. Non Flammable.

DENSITY

0.38 g/l

TENSILE STRENGTH LONGITUDINAL

3000 PSI max - ASTM D882 (mod)

ELONGATION

Minimum of 50%

THICKNESS

0.003", +0.001 or -0.35.

PACKAGING

U.S. Measure:

Stock

Code Size

Plastic Spool

S260	½" x 260" (1.27 cm x 6.6 m)
S520	½" x 520" (1.27 cm x 13.2 m)
S1296	½" x 1296" (1.27 cm x 32.9 m)
SW260	¾" x 260" (1.9 cm x 6.6 m)
SW520	¾" x 520" (1.9 cm x 13.2 m)
SW1296	¾" x 1296" (1.9 cm x 32.9 m)
SX520	1" x 520" (2.54 cm x 13.2 m)
SX1296	1" x 1296" (2.54 cm x 32.9 m)

SHIPPING WEIGHT PER CASE

Stock

Code

Case Weight

#/Case

S520	3 lbs. (1.4 kg)	100
S260	3 lbs. (1.4 kg)	100
S1296	3 lbs. (1.4 kg)	50
SW260	3 lbs. (1.4 kg)	70
SW520	3 lbs. (1.4 kg)	70
SW1296	15 lbs. (6.8 kg)	150
SX520	3 lbs. (1.4 kg)	50
SX1296	18 lbs. (8.2 kg)	150

DIRECTIONS FOR USE

1. Remove plastic spool.
2. Apply tape clockwise onto male threads.
3. Make up joint in a normal manner.

On large diameter pipe 4" (10.2 cm) and up, first wrap the pipe threads with two or more thicknesses of **PTFE TAPE**, then apply **SELECT-UNYTE** over the tape.



P.O. Box 380
Wadsworth, Ohio 44282
Phone: 330-334-2524
Fax: 330-334-3005

Email: info@jcwhitlam.com
Website: www.joinpipe.com