



EZ-Pull Line Sets

Applications

Ductless mini - split systems. VRF commercial systems. Split system (A/C & Heat Pump).



Technical Specs

Copper Tubing: Commercial Grade Refrigeration Tubing

Copper: No. C122200 DHP (Phosphorous deoxidized, high residual phosphorous), 99.97%

Water Vapor Permeability: According to ASTM E96-00

Low-density Polyethylene Foam: Closed cells foam, CFC and HCFC gas free

Working Temperature: Meets/exceeds ASTM C 1427-07

Wall Thickness: 1/2" & 3/4"

Surface Burning Characteristics: UL 94HBT, UL 723, ASTM E84 (25/50), flame and spread index less than 25 and smoke development index less than 50 as tested according to UL 723

ALL polyethylene insulated line sets sold in the U.S. do not meet UL 94VBT

Special Features

- Currently in use in the US market
- Meets ASTM E84 for smoke and fire (25/50)
- Superior tear resistance
- "Rugged" exterior allows for easier installation of the line set
- UV Resistant
- R410 A Approved
- Insulation is marked every foot
- Paintable

Insulation R Values

1/2" Wall - R3.3

3/4" Wall - R5.2

*R - Value calculation using a K-Factor of 0.25 BTU-in/hr-ft (2)-F @ 75°F, 24°C mean temp.

JMF offers more Line Set Product options than anyone in the industry.

To view our full product offering visit
www.jmfcompany.com