

Model	Configuration	Rated Capacity (Cooling/Heating)	Max Capacity @ 17° F	Max Capacity @ 5° F	SEER	EER	HSPF	COP @ 47° F	COP @ 17° F
MXZ-C Models									
MXZ-3C24NA2	Non-Ducted	22,000 / 25,000	19,600	18,200	20.0	13.60	9.8	4.20	2.97
	Ducted	23,600 / 24,600	19,600		16.0	11.20	9.2	3.80	2.61
MXZ-3C30NA2	Non-Ducted	28,400 / 28,600	21,000	18,200	19.0	10.60	10.6	3.90	2.77
	Ducted	27,400 / 27,600	21,000		16.2	9.60	9.6	3.64	2.78
MXZ-4C36NA2	Non-Ducted	35,400 / 36,000	26,600	24,000	19.2	9.40	11.0	3.50	2.67
	Ducted	34,400 / 34,400	26,600		16.0	8.70	9.8	3.25	2.54
MXZ-5C42NA2	Non-Ducted	40,500 / 45,000	30,500	26,000	19.7	9.20	10.3	3.69	2.43
	Ducted	37,500 / 41,000	29,100		15.2	9.00	9.1	3.47	2.35
MXZ-8C48NA	Non-Ducted	48,000 / 54,000	36,600	32,400	18.9	12.0	11.4	3.75	2.60
	Ducted		36,600		14.7	9.50	10.1	3.17	2.30
MXZ-C H2i Models									
MXZ-2C20NAHZ2	Non-Ducted	18,000 / 22,000	22,000	22,000	17.0	13.50	9.8	4.00	2.77
	Ducted	20,000 / 22,000			15.0	11.00	9.5	3.69	2.53
MXZ-3C24NAHZ2	Non-Ducted	22,000 / 25,000	25,000	25,000	19.0	13.50	10.0	4.25	2.53
	Ducted	23,600 / 24,600	24,600		15.5	10.00	9.0	3.80	2.51
MXZ-3C30NAHZ2	Non-Ducted	28,400 / 28,600	28,600	28,600	18.0	12.50	11.0	4.00	2.65
	Ducted	27,400 / 27,600	27,600		16.0	10.30	9.8	3.70	2.50
MXZ-4C36NAHZ	Non-Ducted	36,000 / 45,000	45,000	45,000	19.1	14.00	11.3	3.95	2.85
	Ducted				15.8	11.30	10.1	3.10	2.30
MXZ-5C42NAHZ	Non-Ducted	42,000 / 48,000	48,000	48,000	19.0	13.40	11.0	4.10	2.85
	Ducted				15.0	10.80	10.1	3.23	2.50
MXZ-8C48NAHZ	Non-Ducted	48,000 / 54,000	54,000	54,000	18.9	12.00	11.0	3.75	2.70
	Ducted				14.7	9.5	10	3.17	2.40

