

Job Name:

Schedule Reference:

Date:

OUTDOOR VRF SYSTEM FEATURES

- Single-phase outdoor unit with variable refrigerant flow (VRF) zoning technology
- Inverter-driven (variable speed) compressor
- Total refrigerant piping length of 394' (120 m)
- Uses CITY MULTI indoor units and Controls Network

OPTIONAL PARTS

- ☐ Branch Joint (T-Branch).....CMY-Y62-G-E
- ☐ Header - Four-Branch.....CMY-Y64-G-E
- ☐ Header - Eight-Branch.....CMY-Y68-G-E
- ☐ Air Outlet Guide (One Piece)**.....PAC-SG59SG-E
- ☐ Wind Baffle (One Piece)**.....WB-PA2
- ☐ Drain Pan.....PAC-SG64DP-E
- ☐ Drain Socket.....PAC-SG61DS-E
- ☐ Drain Socket.....PAC-SH71DS-E



PUMY-P40NKMU*(-BS)

INVERTER

***UNIT OPTION**

- ☐ Standard Model.....PUMY-P48NHMU
- ☐ Standard Model.....PUMY-P48NHMUR4
- ☐ Sea Coast (BS) Model.....PUMY-P48NHMU-BS
- ☐ Sea Coast (BS) Model.....PUMY-P48NHMUR4-BS

Specifications		Model Name
Unit Type		PUMY-P48NHMU
Nominal Cooling Capacity	Btu/h	48,000
Nominal Heating Capacity	Btu/h	54,000
Operating Temperature Range	Cooling (Outdoor) *1	23° F ~ 115° F (-5° ~ +46° C) DB*
	Heating (Outdoor)	0° F ~ +60° F (-18° ~ +15° C) WB
External Dimensions (H x W x D)	In. / mm	53-3/16 x 37-7/16 x 13 (+1-3/16) / 1,350 x 950 x 330 (+30)
Net Weight	Lbs. / kg	287 / 130
External finish		Precoated Galvanized-steel Sheets
Electrical Power Requirements	Voltage, Phase, Hertz	208 / 230V, 1-phase, 60Hz
Cooling Power Input	kW	4.97
Heating Power Input	kW	4.88
Cooling Current (208/230V)	A	24.0 / 21.7
Heating Current (208/230V)	A	23.6 / 21.3
Minimum Circuit Ampacity (MCA)	A	26
Recommended Fuse/Breaker Size	A	30
Maximum Fuse Size	A	40
Piping Diameter (Flared) (In. / mm)	Liquid (High Pressure)	3/8 / 9.52
	Gas (Low Pressure)	5/8 / 15.88
Indoor Unit	Total Capacity	50 to 130% of Outdoor Unit Capacity
	Model / Quantity	P06 to P54 / 1 to 8
Sound Pressure Levels	dB(A)	50/52
Fan		
Type x Quantity		Propeller Fan x 2
Airflow Rate	CFM	3,530
Direct-drive Inverter Motor Output	kW	0.086
Compressor Operating Range		25% to 100%
Compressor Type x Quantity		Inverter-driven Scroll Hermetic x 1
Compressor Motor Output	kW	2.4
Refrigerant		R410A
Lubricant		FV50S
High-pressure Protection Device		601 psi / 4.15 MPa
Compressor / Fan Protection Device		Overheat Protection / Thermal Switch
Inverter Protection Device		Overheat / Overcurrent Protection
AHRI Ratings (Ducted / Non-Ducted)	SEER	14.5 / 15.5
	COP	3.14 / 3.56
Blue Fin Anti-corrosion Protection: Cellulose- and polyurethane-resin coating treatment applied to condenser coil that protects it from air contaminants; ≥1µm thick; Salt Spray Test Method - no unusual rust development to 240 hours.		

NOTES:

*1 If PKFY-P06/08 indoor units are connected, then range is 50° F ~ 115° F (10° C ~ 46° C).

SEACOAST PROTECTION

- External Panel Base, External Front Panel, Pillar: Alloyed galvanized-steel sheets with thermoset polyester-resin coating on internal and external surfaces
- Compressor Cover: Galvanized-aluminum sheets with thermoset polyester-resin coating on internal and external surfaces
- Electrical Parts Box: Galvanized-aluminum sheets with thermoset polyester-resin coating on external surface
- Fan Motor Support: Galvanized-steel sheets with thermoset polyester-resin coating on internal and external surfaces
- Printed Circuit Board: Epoxy resin with polyurethane-coating on external surface

Model: PUMY-P48NHMU*(-BS) – DIMENSIONS

Ref.: PUMY_NHMu_EXD_USDB_P36-48
Unit: mm(in)

