



## Warning

### Hazard statements:

Causes serious eye irritation.

### Precautionary statements:

Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Restricted to professional users.

### First Aid Measures

#### After inhalation:

Respiration of particulates is unlikely during normal usage. Supply fresh air; consult doctor in case of complaints. Provide oxygen treatment if affected person has difficulty breathing.

#### After skin contact:

Immediately remove any clothing soiled by the product. Immediately wash with water and soap and rinse thoroughly. Seek medical treatment in case of complaints.

#### After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

#### After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

### Most important symptoms and effects, both acute and delayed:

Headache, Causes eye irritation., Dizziness  
Gastric or intestinal disorders when ingested.  
Nausea in case of ingestion.

### Indication of any immediate medical attention and special treatment needed:

No relevant information available.

### Firefighting Measures

#### Extinguishing media

#### Suitable extinguishing agents:

Foam, Fire-extinguishing powder, Carbon dioxide  
Water fog / haze

#### For safety reasons unsuitable extinguishing agents:

None.

### Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

### Advice for firefighters

#### Protective equipment:

Wear self-contained respiratory protective device.  
Wear fully protective suit.



## Eco-COATING GREY

# 55-41 BRUSH GRADE

FIRE RESISTIVE VAPOR BARRIER COATING  
FOR USE ON LOW TEMPERATURE EQUIPMENT.

MAXIMUM VOC .14LBS./GAL OR 16.4 GRAMS/LITER  
UNDERWRITERS LABORATORIES, INC.®

### CLASSIFIED

#### GENERAL PURPOSE COATING

#### SURFACE BURNING CHARACTERISTICS

R10069	Applied to Inorganic Reinforced Cement Board	
	USC	CNC
Flame Spread	10	10
Smoke Developed	5	5
Number of Coats	1	1
Rate Per Coat	50 Ft. <sup>2</sup> /gal	1.2 m <sup>2</sup> /L

Flash point of finished coating (closed cup): No flash to boiling



## KEEP FROM FREEZING

## U.S. GALLON

**CLEAN-UP**  
Water or 44-10.

**ASBESTOS FREE**

### INGREDIENTS

Acrylic Polymer Dispersion-proprietary Limestone, CAS 1317-65-3, Chlorinated Paraffin, CAS 61788-76-9, Titanium Dioxide, CAS 13463-67-7, Water, CAS 7732-18-5

### DIRECTIONS FOR USE

Do not thin. Use as supplied. Flash all outdoor insulation. Be sure surfaces are dry and clean. Apply a 2 gal./100 sq. ft. tack coat. Embed a fabric.

Apply a 2 to 4 gal./100 sq. ft. finish coat.

Eco-Coating may be applied by brush, glove or spray. Contact MEI Inc. for detailed spray instructions.

### LIMITATIONS

Do not apply to surfaces where water ponding will occur.

Avoid using dark colors over plastic foam insulations outdoors.

Apply between 40°F and 100°F.

**WARRANTY TERMS:** The physical and chemical properties of this product are representative of the typical average values derived in accordance with test methods deemed acceptable, and can vary when subjected to normal manufacturing methods. These values are supplied only as a technical service and are subject to change without notice. To be sure information is current call Mon-Eco Industries, Inc. **Terms of Warranty:** Warrantor, Mon-Eco Industries, Inc. warrants satisfactory results of this product only when recommendations herein established are followed. The recommendations for use are established upon tests and information deemed reliable. We recommend that adequate testing be made by the user to determine if the product is suitable for the intended purpose and use. Warrantor assumes no responsibility beyond replacement or refund of the purchase price of this product, since warrantor has no control over the methods and application of its product, methods and conditions of transportation, handling and storage of the product. **WARRANTOR EXPLICITLY DISCLAIMS ALL LIABILITY FOR INCIDENTAL OR CONSEQUENTIAL DAMAGE.** No agent or representative of Mon-Eco Industries, Inc. has the authority to change or extend these conditions.



**WARNING - Cancer**

[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## MON-ECO INDUSTRIES, INC.

5 JOANNA COURT, EAST BRUNSWICK, N.J. 08816

Made in U.S.A.