according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 29.05.2015 Revision: 29.05.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Eco-Mastic
- · Article number: 55-51
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Coating compound/ Surface coating/ paint
- · 1.3 Details of the supplier of the Safety Data Sheet
- · Manufacturer/Supplier:

Mon-Eco Industries, Inc.

5 Joanna Ct.

East Brunswick, NJ 08816 Phone: 732-257-7942

· 1.4 Emergency telephone number:

ChemTel Inc.

(800)255-3924, +1 (813)248-0585



SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H412.

Classifications listed also are applicable to the OSHA GHS Hazard Communication Standard (29CFR1910.1200).



health hazard

Carc. 1A H350 May cause cancer.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC

T; Toxic

R45: May cause cancer.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

The classification is in accordance with the latest editions of international substances lists, and is supplemented by information from technical literature and by information provided by the company.

(Contd. on page 2)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 29.05.2015 Revision: 29.05.2015

Trade name: Eco-Mastic

(Contd. of page 1)

· Additional information:

There are no other hazards not otherwise classified that have been identified.

0 percent of the mixture consists of component(s) of unknown toxicity

2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is additionally classified and labelled according to the Globally Harmonized System within the United States (GHS).

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



GHS08

· Signal word Danger

· Hazard-determining components of labelling:

titanium dioxide

Attapulgite (Palygorskite)

Quartz (SiO2)

· Hazard statements

The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H412.

H350 May cause cancer.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

The following Precautionary Statements are applicable only to the OSHA GHS regulations and not the specific CLP regulation: P280.

The following Precautionary Statements are applicable only to the EU CLP regulations and not the OSHA GHS regulations: P273, P281.

P280 Wear protective gloves/protective clothing/eye protection.

P281 Use personal protective equipment as required.

P273 Avoid release to the environment.
P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Additional information:

Restricted to professional users.

- · Hazard description:
- · WHMIS-symbols:

As of 11 February 2015, the current WHMIS system is being replaced by the GHS system. This is the classification under the older system.

D2A - Very toxic material causing other toxic effects



(Contd. on page 3)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 29.05.2015 Revision: 29.05.2015

Trade name: Eco-Mastic

· NFPA ratings (scale 0 - 4)

(Contd. of page 2)



Health = 1 Fire = 0Reactivity = 0

· HMIS-ratings (scale 0 - 4)



11 Health = *1 Fire = 0

* - Indicates a long term health hazard from repeated or prolonged exposures.

· HMIS Long Term Health Hazard Substances

13463-67-7 titanium dioxide 14808-60-7 Quartz (SiO2)

- 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · **Description**: Mixture of substances listed below with nonhazardous additions.

CAS: 13463-67-7 EINECS: 236-675-5	titanium dioxide	$\leq 2,5$
CAS: 12174-11-7 EC number: 601-805-5	Attapulgite (Palygorskite) Xn R40	≤ 2,5
CAS: 9036-19-5	© Carc. 2, H351 Polyethylene glycol octylphenyl ether Xn R22; Xi R41 R52/53 Eye Dam. 1, H318 Aquatic Chronic 2, H411 1 Acute Tox. 4, H302	≤ 2,5
CAS: 57-55-6 EINECS: 200-338-0	Propylene Glycol substance with a Community workplace exposure limit	≤ 2,5
CAS: 9016-45-9 NLP: 500-024-6	4-nonylphenyl-polyethylene glycol Xi R36/38; № N R51/53 Aquatic Chronic 2, H411 Skin Irrit. 2, H315; Eye Irrit. 2, H319	< 1

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 29.05.2015 Revision: 29.05.2015

Trade name: Eco-Mastic

		. of page
CAS: 14808-60-7 EINECS: 238-878-4	Quartz (SiO2) ☑ T R49; ★ Xn R48 ❖ Carc. 1A, H350	< 1%
CAS: 64742-46-7 EINECS: 265-148-2 Index number: 649-221-00-X	Distillates (petroleum), hydtrotreated middle Carc. 1B, H350	< 1%
CAS: 64742-52-5 EINECS: 265-155-0 Index number: 649-465-00-7	Distillates (petroleum), hydrotreated heavy naphthenic & Carc. 1B, H350	< 1%
CAS: 64742-54-7 EINECS: 265-157-1 Index number: 649-467-00-8	Distillates (petroleum), hydrotreated heavy paraffinic & Carc. 1B, H350	< 1%
CAS: 64742-55-8 EINECS: 265-158-7 Index number: 649-468-00-3	Distillates (petroleum), hydrotreated light paraffinic & Carc. 1B, H350	< 1%
CAS: 64742-65-0 EINECS: 265-169-7 Index number: 649-474-00-6	Distillates (petroleum), solvent-dewaxed heavy paraffinic & Carc. 1B, H350	< 1%

·SVHC

9016-45-9 4-nonylphenyl-polyethylene glycol

Additional information:

For the listed ingredients, the identity and exact percentages are being withheld as a trade secret. For the wording of the listed risk phrases refer to section 16.

· Notable Trace Components (≤ 0,1% w/w)		
CAS: 1897-45-6	chlorothalonil (ISO)	
EINECS: 217-588-1		
Index number: 608-014-00-4	Carc. Cat. 3	
	♦ Acute Tox. 2, H330	
	🗴 Carc. 2, H351	
	♠ Eye Dam. 1, H318	
	Aquatic Acute 1, H400; Aquatic Chronic 1, H410	

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

Take affected persons out into the fresh air.

· After inhalation:

Supply fresh air; consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation is experienced, consult a doctor.

(Contd. on page 5)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 29.05.2015 Revision: 29.05.2015

Trade name: Eco-Mastic

(Contd. of page 4)

· After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

Headache

Dizziness

Slight irritant effect on skin and mucous membranes.

Slight irritant effect on eyes.

Gastric or intestinal disorders when ingested.

Nausea in case of ingestion.

· Hazards

May cause cancer.

May cause respiratory irritation.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents:

Foam

Fire-extinguishing powder

Gaseous extinguishing agents

Carbon dioxide

- · For safety reasons unsuitable extinguishing agents: None.
- 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- 5.3 Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

· Additional information No further relevant information available.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Particular danger of slipping on leaked/spilled product.

Wear protective equipment. Keep unprotected persons away.

For large spills, evacuate area and contact authorities to perform cleanup.

6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

(Contd. on page 6)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA **GHS**

Printing date 29.05.2015 Revision: 29.05.2015

Trade name: Eco-Mastic

(Contd. of page 5)

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Send for recovery or disposal in suitable receptacles.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Prevent formation of aerosols.

Use only in well ventilated areas.

Avoid splashes or spray in enclosed areas.

- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:

Avoid storage near extreme heat, ignition sources or open flame.

Information about storage in one common storage facility:

Store away from foodstuffs.

Do not store together with oxidising and acidic materials.

- · Further information about storage conditions: Keep container tightly sealed.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

· Ingredients v	· Ingredients with limit values that require monitoring at the workplace:		
13463-67-7 ti	13463-67-7 titanium dioxide		
PEL (USA)	Long-term value: 15* mg/m³ *total dust		
REL (USA)	See Pocket Guide App. A		
TLV (USA)	Long-term value: 10 mg/m³ withdrawn from NIC		
EL (Canada)	Long-term value: 10* 3** mg/m³ *total dust;**respirable fraction; IARC 2B		
EV (Canada)	Long-term value: 10 mg/m³ total dust		

(Contd. on page 7)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 29.05.2015 Revision: 29.05.2015

Trade name: Eco-Mastic

		(Contd. of page 6)	
57-55-6 Prop	57-55-6 Propylene Glycol		
WEEL (USA)	Long-term value: 10 mg/m³		
EV (Canada)	Long-term value: 155* 10** mg/m³, 50* ppm *vapour and aerosol;**aerosol only		
14808-60-7 Q	uartz (SiO2)		
PEL (USA)	see Quartz listing		
REL (USA)	Long-term value: 0,05* mg/m³ *respirable dust; See Pocket Guide App. A		
TLV (USA)	Long-term value: 0,025* mg/m³ *as respirable fraction		
EL (Canada)	Long-term value: 0,025 mg/m³ ACGIH A2; IARC 1		
EV (Canada)	Long-term value: 0,10* mg/m³ *respirable fraction		

- **DNELs** No further relevant information available.
- · PNECs No further relevant information available.
- Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Do not inhale gases / fumes / aerosols.

Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

For spills, respiratory protection may be advisable.

NIOSH or EN approved organic vapor respirator equipped with a dust/mist prefilter should be used.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Eye protection:



Safety glasses

- · Body protection: Protective work clothing
- Limitation and supervision of exposure into the environment

No further relevant information available.

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 29.05.2015 Revision: 29.05.2015

Trade name: Eco-Mastic

(Contd. of page 7)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Liquid Colour: Grey • Odour: Mild

Odour threshold: Not determined.pH-value: Not determined.

· Change in condition

Melting point/Melting range:
Boiling point/Boiling range:

Flash point:

Not applicable.

Flammability (solid, gaseous):

Auto/Self-ignition temperature:

Not determined.

Not determined.

Not determined.

· **Self-igniting:** Product is not self-igniting.

• Danger of explosion: Product does not present an explosion hazard.

· Explosion limits:

Lower:
Upper:
Not determined.
Not determined.

Vapour pressure at 20 °C (68 °F):
23 hPa (17 mm Hg)

20 iii 2 (ii iiii iig)

Density at 20 °C (68 °F): 1,34 g/cm³ (11,182 lbs/gal)

· Relative density Not determined.

• Vapour density at 20 °C (68 °F) > 1 g/cm³ (> 8,345 lbs/gal) (Air =1)

• Evaporation rate at 20 °C (68 °F) ~1 (Water= 1)

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined. **Kinematic:** Not determined.

• **9.2 Other information** No further relevant information available.

(Contd. on page 9)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 29.05.2015 Revision: 29.05.2015

Trade name: Eco-Mastic

(Contd. of page 8)

SECTION 10: Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

10.3 Possibility of hazardous reactions

Toxic fumes may be released if heated above the decomposition point.

Reacts with strong acids and oxidising agents.

· 10.4 Conditions to avoid

Keep away from heat and direct sunlight.

Store away from oxidising agents.

- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

Hydrogen chloride (HCI)

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity:
- LD/LC50 values relevant for classification: None.
- · Primary irritant effect:
- on the skin: Slight irritant effect on skin and mucous membranes.
- on the eye: Slight irritant effect on eyes.
- Sensitisation: No sensitising effects known.
- · Subacute to chronic toxicity: No further relevant information available.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

May cause cancer.

- · Acute effects (acute toxicity, irritation and corrosivity): Vapours have narcotic effect.
- Repeated dose toxicity: May cause damage to organs through prolonged or repeated exposure.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction):

Carc. 1A

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: The material is harmful to the environment.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Ecotoxical effects:
- · Remark: Harmful to fish

(Contd. on page 10)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 29.05.2015 Revision: 29.05.2015

Trade name: Eco-Mastic

(Contd. of page 9)

· Additional ecological information:

· General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground.

Harmful to aquatic organisms

Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB:** Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number

· DOT, ADR, ADN, IMDG, IATA Not Regulated

· 14.2 UN proper shipping name

DOT, ADR, ADN, IMDG, IATA Not Regulated

· 14.3 Transport hazard class(es)

· DOT, ADR, ADN, IMDG, IATA

· Class Not Regulated

· 14.4 Packing group

· DOT, ADR, IMDG, IATA Not Regulated

· 14.5 Environmental hazards:

· Marine pollutant: No

• 14.6 Special precautions for user Not applicable.

· 14.7 Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· UN "Model Regulation":

(Contd. on page 11)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 29.05.2015 Revision: 29.05.2015

Trade name: Eco-Mastic

(Contd. of page 10)

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- **United States (USA)**
- ·SARA
- · Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

- · Proposition 65 (California):
- Chemicals known to cause cancer:

Reference to Titanium Dioxide is based on unbound respirable particles and is not generally applicable to product as supplied.

Reference to Attapulgite is based on unbound respirable particles and is not generally applicable to product as supplied.

Reference to Crystalline Silica and/or Quartz is based on unbound respirable particles and is not generally applicable to product as supplied.

Present in trace quantities: chlorothalonil, carbon black.

13463-67-7	titanium dioxide
12174-11-7	Attapulgite (Palygorskite)
14808-60-7	Quartz (SiO2)
1897-45-6	chlorothalonil (ISO)
1333-86-4	Carbon black

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

Present in trace quantities.

67-56-1 methanol

- Carcinogenic Categories
- EPA (Environmental Protection Agency)

None of the ingredients are listed.

· IARC (International Agency for Research on Cancer)		
13463-67-7	titanium dioxide	2B
12174-11-7	Attapulgite (Palygorskite)	2B
9002-88-4	Linear Low Density Polyethylene	3
14808-60-7	Quartz (SiO2)	1
	(Contd. on no	10

(Contd. on page 12)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 29.05.2015 Revision: 29.05.2015

Trade name: Eco-Mastic

	(Contd. of page 11)
· TLV (Threshold Limit Value established by ACGIH)	
13463-67-7 titanium dioxide	A4
14808-60-7 Quartz (SiO2)	A2
· NIOSH-Ca (National Institute for Occupational Safety and Health)	
13463-67-7 titanium dioxide	
14808-60-7 Quartz (SiO2)	
Canada	
· Canadian Domestic Substances List (DSL)	
All ingredients are listed.	
· Canadian Ingredient Disclosure list (limit 0.1%)	
None of the ingredients are listed.	
· Canadian Ingredient Disclosure list (limit 1%)	
9036-19-5 Polyethylene glycol octylphenyl ether	
57-55-6 Propylene Glycol	

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

Other regulations, limitations and prohibitive regulations

This product has been classified in accordance with hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

- Substances of very high concern (SVHC) according to REACH, Article 57
 9016-45-9 | 4-nonylphenyl-polyethylene glycol
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eve irritation.
- H350 May cause cancer.
- H351 Suspected of causing cancer.
- H411 Toxic to aquatic life with long lasting effects.
- R22 Harmful if swallowed.
- R36/38 Irritating to eyes and skin.
- R40 Limited evidence of a carcinogenic effect.
- R41 Risk of serious damage to eyes.
- R48 Danger of serious damage to health by prolonged exposure.

(Contd. on page 13)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 29.05.2015 Revision: 29.05.2015

Trade name: Eco-Mastic

(Contd. of page 12)

R49 May cause cancer by inhalation.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

WHMIS: Workplace Hazardous Materials Information System (Canada)

VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1 Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Carc. 1A: Carcinogenicity, Hazard Category 1A Carc. 1B: Carcinogenicity, Hazard Category 1B Carc. 2: Carcinogenicity, Hazard Category 2

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

Sources

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com