

KEEP HUMIDIFIERS CLEAN & SCALE-FREE

Description

Humidi-Treat is designed for humidifiers using up to 25 gallons per day, and will inhibit scale for one season. Install Humidi-Treat on the water line that supplies water directly to the humidifier. Equipped with John Guest fittings.

Application

- Clean pad or install new pad before installing Humidi-Treat.
- For best results humidifier should have a daily dump of water from the sump to diminish scale forming minerals.
- Install a new Humidi-Treat before each heating season.
- Operating temperature, min./ max, 40° - 80° F

Installation Steps

1. Shut off water.
2. Disconnect existing filter or cut water line where filter is to be installed.
3. Install water line directly into the John Guest fitting at each end of the Humidi-Treat cartridge. No additional fittings or tools necessary.
4. Insure proper direction of water flow and connect inlet and outlet.
5. Carefully turn on the water and check for leaks.
6. Check the filter after approximately 8 hours for slight leaks not visible during initial installation.

Packaging

1 each

4190-02


Water Treatment Products

Humidi-Treat



1/4 inch John Guest fittings

Typical Installation Diagram



Read and understand the product's label and Material Safety Data Sheet ("MSDS") for precautionary and first aid information.

The MSDS is available on the Nu-Calgon website at www.nucalgon.com.

