

**PA13NA
PA13PA**

**13 SEER Split–System Air Conditioner
With R–410A Refrigerant
Single & Three Phase
1–1/2 To 5 Tons**

Product Data



FEATURES AND BENEFITS

AVAILABLE SIZES:

Nominal sizes are available from 018 through 060 to meet the needs of residential and light commercial applications.

CERTIFICATION:

All models are listed with UL, (U.S. and Canada), AHRI, and CEC.

ELECTRICAL RANGE:

Units offered in single phase 208/230v are 024-060, and three phase 208/230v in 036, 048 and 060.

FAN MOTOR:

The totally enclosed fan motor provides greater reliability under adverse conditions and dependable performance for many years. The permanent split capacitor type motor was designed for optimum efficiency. The motor was then qualified under extreme conditions to help ensure a long, reliable life.

CABINET:

A weather protective cabinet of prepainted steel is protected underneath by a galvanized coating and treated with a layer of zinc phosphate for a finish that will last for many years. All screws on cabinet exterior are coated for a long-lasting, rust-resistant, quality appearance.

UNIT DESIGN:

The copper tube, enhanced sine wave, aluminum fin coil is designed for optimum heat transfer. Vertical air discharge carries sound and hot condenser air up and away from adjacent patio areas and foliage. The base pan is designed for easy removal of water, dirt, and leaves.

COMPRESSOR:

Each compressor is protected with internal temperature- and current-sensitive overloads. An internal pressure relief valve provides high pressure protection to the refrigerant system. For improved serviceability, all models are equipped with a compressor terminal plug.

SERVICE VALVES:

Both service valves are brass, front seating type with sweat connections. Valves are externally located so refrigerant tube connections can be made quickly and easily. Each valve has a service port for ease of checking operating refrigerant pressures.

SERVICEABILITY:

One access panel provides access to electrical controls. Removal of top gives access to fan motor, compressor, and condenser coil.

REFRIGERANT PIPING LENGTH LIMITATIONS

Liquid Line Sizing and Maximum Total Equivalent Lengths† for Cooling Only Systems with R-410A Refrigerant:

The maximum allowable length of a residential split system depends on the liquid line diameter and vertical separation between indoor and outdoor units.

See Table below for liquid line sizing and maximum lengths :

Maximum Total Equivalent Length Outdoor Unit BELOW Indoor Unit

Size	Liquid Line Connection	Liquid Line Diam. w/ TXV	AC with R-410A Refrigerant Maximum Total Equivalent Length†: Outdoor unit BELOW Indoor Vertical Separation ft (m)								
			0-5 (0-1.5)	6-10 (1.8-3.0)	11-20 (3.4-6.1)	21-30 (6.4-9.1)	31-40 (9.4-12.2)	41-50 (12.5-15.2)	51-60 (15.5-18.3)	61-70 (18.6-21.3)	71-80 (21.6-24.4)
			018	3/8	1/4	150	150	125	100	100	75
5/16	250*	250*	250*		250*	250*	250*	250*	225*	150	
3/8	250*	250*	250*		250*	250*	250*	250*	250*	250*	
024	3/8	1/4	75	75	75	50	50	--	--	--	--
		5/16	250*	250*	250*	250*	250*	225*	175	125	100
		3/8	250*	250*	250*	250*	250*	250*	250*	250*	250*
030	3/8	1/4	30	--	--	--	--	--	--	--	--
		5/16	175	225*	200	175	125	100	75	--	--
		3/8	250*	250*	250*	250*	250*	250*	250*	250*	250*
036	3/8	5/16	175	150	150	100	100	100	75	--	--
		3/8	250*	250*	250*	250*	250*	250*	250*	250*	250*
042	3/8	5/16	125	100	100	75	75	50	--	--	--
		3/8	250*	250*	250*	250*	250*	250*	250*	250*	150
048	3/8	3/8	250*	250*	250*	250*	250*	250*	230	160	--
060	3/8	3/8	250*	250*	250*	225*	190	150	110	--	--

* Maximum actual length not to exceed 200 ft (61 m)

† Total equivalent length accounts for losses due to elbows or fitting. See the Long Line Guideline for details.

-- = outside acceptable range

Maximum Total Equivalent Length Outdoor Unit ABOVE Indoor Unit

Size	Liquid Line Connection	Liquid Line Diam. w/ TXV	AC with R-410A Refrigerant Maximum Total Equivalent Length†: Outdoor unit ABOVE Indoor Vertical Separation ft (m)							
			25 (7.6)	26-50 (7.9-15.2)	51-75 (15.5-22.9)	76-100 (23.2-30.5)	101-125 (30.8-38.1)	126-150 (38.4-45.7)	151-175 (46.0-53.3)	176-200 (53.6-61.0)
			018	3/8	1/4	175	250*	250*	250*	250*
5/16	250*	250*			250*	250*	250*	250*	250*	250*
3/8	250*	250*			250*	250*	250*	250*	250*	250*
024	3/8	1/4	100	125	175	200	225*	250*	250*	250*
		5/16	250*	250*	250*	250*	250*	250*	250*	250*
		3/8	250*	250*	250*	250*	250*	250*	250*	250*
030	3/8	1/4	30	--	--	--	--	--	--	--
		5/16	250*	250*	250*	250*	250*	250*	250*	250*
		3/8	250*	250*	250*	250*	250*	250*	250*	250*
036	3/8	5/16	225*	250*	250*	250*	250*	250*	250*	250*
		3/8	250*	250*	250*	250*	250*	250*	250*	250*
042	3/8	5/16	175	200	250*	250*	250*	250*	250*	250*
		3/8	250*	250*	250*	250*	250*	250*	250*	250*
048	3/8	3/8	250*	250*	250*	250*	250*	250*	250*	250*
060	3/8	3/8	250*	250*	250*	250*	250*	250*	250*	250*

* Maximum actual length not to exceed 200 ft (61 m)

† Total equivalent length accounts for losses due to elbows or fitting. See the Long Line Guideline for details.

-- = outside acceptable range

REFRIGERANT CHARGE ADJUSTMENTS

Liquid Line Size	R-410A Charge oz/ft (g/m)
3/8	0.60 (17.74) (Factory charge for lineset = 9 oz / 266.16 g)
5/16	0.40 (11.83)
1/4	0.27 (7.98)

Units are factory charged for 15 ft (4.6 m) of 3/8" liquid line. The factory charge for 3/8" lineset 9 oz. When using other length or diameter liquid lines, charge adjustments are required per the chart above.

Charging Formula:

$[(\text{Lineset oz/ft} \times \text{total length}) - (\text{factory charge for lineset})] = \text{charge adjustment}$

Example 1: System has 15 ft of line set using existing 1/4" liquid line. What charge adjustment is required?

Formula: $(.27 \text{ oz/ft} \times 15\text{ft}) - (9 \text{ oz}) = (-4.95) \text{ oz.}$

Net result is to remove 4.95 oz of refrigerant from the system

Example 2: System has 45 ft of existing 5/16" liquid line. What is the charge adjustment?

Formula: $(.40 \text{ oz/ft.} \times 45\text{ft}) - (9 \text{ oz.}) = 9 \text{ oz.}$

Net result is to add 9 oz of refrigerant to the system

NOTE: Conditions must be favorable for charging by subcooling method. Indoor temperature must be 70°F to 80°F (21.1°C to 26.7°C), and outdoor temperature must be 70°F to 100°F (21.1°C to 37.8°C). If outside these conditions, adjust charge for long line sets by weigh-in method.

LONG LINE APPLICATIONS

An application is considered Long Line, when the refrigerant level in the system requires the use of accessories to maintain acceptable refrigerant management for systems reliability. See Accessory Usage Guideline table for required accessories. Defining a system as long line depends on the liquid line diameter, actual length of the tubing, and vertical separation between the indoor and outdoor units.

For Air Conditioner systems, the chart below shows when an application is considered Long Line.

AC with R-410A Refrigerant Long Line Description ft (m) Beyond these lengths, a TXV is required

Total Length	Outdoor Unit Above or Below Indoor Unit
TXV required beyond 50 ft. (15.2 m)	TXV required beyond 20 ft. (6.1 m)

AC with R-410A Refrigerant Long Line Description ft (m) (Beyond these lengths, long line accessories are required)

Liquid Line Size	Units On Same Level	Outdoor Below Indoor	Outdoor Above Indoor
1/4 + TXV	No accessories needed within allowed lengths	No accessories needed within allowed lengths	175 (53.3)
5/16 + TXV	120 (36.6)	50 (15.2) vertical or 120 (36.6) total	120 (36.6)
3/8 + TXV	80 (24.4)	35 (10.7) vertical or 80 (24.4) total	80 (24.4)

Note: See Residential Piping and Long Line Guideline for details

VAPOR LINE SIZING AND COOLING CAPACITY LOSS

Acceptable vapor line diameters provide adequate oil return to the compressor while avoiding excessive capacity loss. The suction line diameters shown in the chart below are acceptable for AC systems with R-410A refrigerant:

Vapor Line Sizing and Cooling Capacity Losses — R-410A Refrigerant 1-Stage Air Conditioner Applications

Unit Nominal Size (Btuh)	Maximum Liquid Line Diameters (In. OD)	Vapor Line Diameters (In. OD)	Cooling Capacity Loss (%)								
			Total Equivalent Line Length ft. (m)								
			1-Stage AC with R-410A								
			26-50 (7.9-15.2)	51-80 (15.5-24.4)	81-100 (24.7-30.5)	101-125 (30.8-38.1)	126-150 (38.4-45.7)	151-175 (46.0-53.3)	176-200 (53.6-61.0)	201-225 (61.3-68.6)	226-250 (68.9-76.2)
018	3/8	1/2	1	2	3	5	6	7	8	9	11
		5/8	0	1	1	1	2	2	2	3	3
		3/4	0	0	0	0	1	1	1	1	1
024	3/8	5/8	0	1	2	2	3	3	4	5	5
		3/4	0	0	1	1	1	1	1	2	2
		7/8	0	0	0	0	0	1	1	1	1
030	3/8	5/8	1	2	3	3	4	5	6	7	8
		3/4	0	0	1	1	1	2	2	2	3
		7/8	0	0	0	0	1	1	1	1	1
036	3/8	5/8	1	2	4	5	6	8	9	10	12
		3/4	0	1	1	2	2	3	3	4	4
		7/8	0	0	0	1	1	1	1	2	2
042	3/8	3/4	0	1	2	2	3	4	4	5	6
		7/8	0	0	1	1	1	2	2	2	3
		1 1/8	0	0	0	0	0	0	0	0	0
048	3/8	3/4	0	1	2	3	4	5	5	6	7
		7/8	0	0	1	1	2	2	2	3	3
		1 1/8	0	0	0	0	0	0	0	0	1
060	3/8	3/4	1	2	4	5	6	7	9	10	11
		7/8	0	1	2	2	3	4	4	5	5
		1 1/8	0	0	0	1	1	1	1	1	1

Applications in this area may be long line and may have height restrictions. See the Residential Piping and Long Line Guideline.

SPECIFICATIONS

UNIT SIZE	018	024	030	036	042	048	060
SERIES	G	F	B	E	B	E	B
ELECTRICAL							
Unit Volts—Hertz—Phase	208/230—60—1	208/230—60—1	208/230—60—1	208/230—60—1	208/230—60—1	208/230—60—1	208/230—60—1
Operating Voltage Range*	9.0	11.2	12.8	14.1	16.6	18.8	22.1
Compressor—Rated Load Amps	48.0	60.8	64.0	70.0	85.0	96.0	125.0
Locked Rotor Amps	0.5	0.8	0.8	1.4	1.1	1.4	1.4
Condenser Fan Motor— Full Load Amps	11.8	14.8	16.8	19.0	21.9	24.9	29.0
Min Unit Ampacity for Wire Sizing	14	14	14	14	12	12	10
Min Wire Size (60°/75° Copper) AWG**	66 / 62	44 / 42	46 / 44	41 / 39	52 / 50	50 / 48	68 / 66
Max Wire Length (60°/75°) ft. (m)†	(20.1 / 18.9)	(13.4 / 12.8)	(14.0 / 13.4)	(12.5 / 11.9)	(15.9 / 15.2)	(15.2 / 14.6)	(21.0 / 20.1)
Max Branch Circuit Fuse Size†	20	25	25	30	35	40	50
COMPRESSOR AND REFRIGERANT							
Type	Scroll						
Temperature and Current Protection	Internal Line Break						
R—410A Refrigerant— Amount Lb. (kg) @ 15 ft. (4.6 m)	3.15 (1.43)	3.15 (1.43)	3.63 (1.65)	4.67 (2.12)	6.12 (2.78)	7.00 (3.18)	8.80 (3.99)
Refrigerant Tubes (In. OD)	3/4 and 3/8						
†† Rated Vapor and Maximum Liquid	7/8 and 3/8						
CONDENSER COIL AND FAN							
Coil Face Area (Sq Ft)	8.4	8.4	9.8	12.60	17.3	19.29	15.14
Fan Motor—HP, Type, and RPM	1/12	PSC and 1100	PSC and 1100	PSC and 1100	PSC and 1100	PSC and 1100	PSC and 1100
Volts—Hertz—Phase	208/230—60—1	208/230—60—1	208/230—60—1	208/230—60—1	208/230—60—1	208/230—60—1	208/230—60—1
Condenser Airflow (CFM)	1700	2000	2000	2500	3000	3400	3400
OPTIONAL EQUIPMENT							
Cycle Protector	KSACY0101AAA						
Start Assist—PTC Type	KAACS0201PTC	KAACS0201PTC	KAACS0201PTC	KAACS0201PTC	KAACS0201PTC	KAACS0201PTC	KAACS0201PTC
Start Assist—Capacitor/Relay Type	KSASH1501AAA	KSASH1501AAA	KSASH1501AAA	KSASH1501AAA	KSASH1501AAA	KSASH1501AAA	KSASH1501AAA
MotorMaster® Control	KSALA0601AAA						
Ball Bearing Fan Motor (RCD)	HC32GE234	HC34GE239	HC34GE239	HC40GR232	HC38GE219	HC40GE226	HC40GE226
Low—Pressure Switch	KAALP0401PUR						
High—Pressure Switch	KAAHI0501PUR						
Compressor Sound Hood	KSASH1801COP						
Time—Delay Relay	KAATD0101TDR						
Low—Ambient Pressure Switch Kit	KSALA0301410						
Winter Start Control	KAAWS0101AAA						
Evaporator Freeze Thermostat	KSAFT0101AAA						
Compressor Crankcase Heater	KAACH1401AAA						
Liquid Line Solenoid Valve††	KAALS0201LLS						
TXV (Hard Shutoff)††	KSATX0201PUR	KSATX0201PUR	KSATX0301PUR	KSATX0301PUR	KSATX0401PUR	KSATX0501PUR	KSATX0501PUR
Liquid Line Filter Drier	KH43LG073						

N/A — Not applicable in this application.

* Permissible limits of the voltage range at which unit will operate satisfactorily. Operation outside these limits may result in unit failure.

† Time—delay fuse or circuit breaker.

‡ Length shown is as measured 1 way along wire path between unit and service panel for voltage drop not to exceed 2%.

** If wire is applied at ambient greater than 30° C, consult Table 310—16 of the NEC (NFPA 70). The ampacity of nonmetallic—sheathed cable (NM), trade name ROMEX, shall be that of 60° C conductors, per the NEC (NFPA 70) Article 336—26.

†† Do not use hard shutoff TXV with liquid solenoid valve.

‡‡ Units are rated with 25 ft (7.6 m) of inerset length. See Vapor Line Sizing and Cooling Capacity Loss table when using other sizes and lengths of lineset.

A-WEIGHTED SOUND POWER (dBA)

UNIT SIZE – SERIES (1-phase / 3-phase)	Standard Rating (dBA)	TYPICAL OCTAVE BAND SPECTRUM (dBA without tone adjustment)						
		125	250	500	1000	2000	4000	8000
018–G	71	64.0	62.0	63.0	68.0	64.0	62.0	57.0
024–F	76	50.5	61.0	67.0	68.0	65.0	60.0	55.5
030–B	72	52.0	61.5	65.5	66.5	64.5	59.5	54.5
036–E/B	75	57.0	61.5	68.5	70.0	67.0	62.5	54.0
042–B	75	56.0	64.5	69.5	71.0	66.0	64.0	59.0
048–E/D	76	54.0	63.0	69.5	71.5	70.0	66.0	58.5
060–E/B	79	57.5	67.0	72.0	75.0	72.5	68.0	61.0

NOTE: Tested in accordance with AHRI Standard 270–2008 (not listed in AHRI).

A-WEIGHTED SOUND POWER (dBA) WITH SOUND SHIELD

UNIT SIZE – SERIES (1-phase / 3-phase)	Standard Rating (dBA)	TYPICAL OCTAVE BAND SPECTRUM (dBA without tone adjustment)						
		125	250	500	1000	2000	4000	8000
018–G	70	66.0	64.0	64.0	67.0	63.0	60.0	54.0
024–F	73	53.0	62.0	67.5	68.0	65.0	60.0	53.5
030–B	71	54.0	61.5	65.5	66.0	63.5	58.5	52.0
036–E/B	74	57.0	61.5	67.5	70.0	66.5	62.5	56.0
042–B	74	55.5	64.0	69.0	69.5	65.5	63.5	57.5
048–E/D	76	55.0	63.0	69.5	71.0	68.5	65.0	58.0
060–E/B	79	57.5	68.0	72.5	74.5	72.5	68.0	60.5

NOTE: Tested in accordance with AHRI Standard 270–2008 (not listed in AHRI).

METERING DEVICE

UNIT SIZE – SERIES	INDOOR	REQUIRED SUBCOOLING °F (°C)
018–G	TXV*	14 (7.8)
024–F		10 (5.6)
030–B		10 (5.6)
036–E		12 (6.7)
036–B (3-phase)		10 (5.6)
042–B		12 (6.7)
048–E		15 (8.3)
048–D (3-phase)		10 (5.6)
060–E		15 (8.3)
060–B (3-phase)		10 (5.6)

* TXV must be ordered separately when indoor coil is not equipped with a TXV. TXV must be hard-shutoff type.

TESTED AHRI COMBINATION RATINGS

For AHRI ratings certificates, please refer to the AHRI directory www.ahridirectory.org

Additional ratings and system combinations can be accessed via the Payne database at:

http://cactaxcredits.info/payne-ratings/hp_ratings_srch.php

ACCESSORY USAGE GUIDELINE

ACCESSORY	REQUIRED FOR LOW-AMBIENT COOLING APPLICATIONS (Below 55°F/12.8°C)	REQUIRED FOR LONG LINE APPLICATIONS*	REQUIRED FOR SEA COAST APPLICATIONS (Within 2 miles/3.22 km)
Ball Bearing Fan Motor	Yes†	No	No
Compressor Start Assist Capacitor and Relay	Yes	Yes	No
Crankcase Heater	Yes	Yes	No
Evaporator Freeze Thermostat	Yes	No	No
Hard Shut-Off TXV	Yes	Yes	Yes
Liquid Line Solenoid Valve	No	No	No
Motor Master® Control or Low-ambient Pressure Switch	Yes	No	No
Support Feet	Recommended	No	Recommended
Winter Start Control	Yes #	No	No

* For tubing set lengths between 80 and 200 ft. (24.38 and 60.96 m) horizontal or 35 ft. (10.7 m) vertical differential (total equivalent length), refer to the Residential Split-System Longline Application Guideline.

† Required for Low-Ambient Controller (full modulation feature) MotorMaster® Control.

Required if Low Pressure Switch is factory or field installed.

Accessory Description and Usage (Listed Alphabetically)

1. Ball-Bearing Fan Motor

A fan motor with ball bearings which permits speed reduction while maintaining bearing lubrication.

Usage Guideline:

Required on all units when MotorMaster® is used.

2. Compressor Start Assist - Capacitor and Relay

Start capacitor and relay gives a "hard" boost to compressor motor at each start up.

Usage Guideline:

Required for reciprocating compressors in the following applications:

- Long line
- Low ambient cooling
- Hard shut off expansion valve on indoor coil
- Liquid line solenoid on indoor coil

Required for single-phase scroll compressors in the following applications:

- Long line
- Low ambient cooling

Suggested for all compressors in areas with a history of low voltage problems.

3. Compressor Start Assist — PTC Type

Solid state electrical device which gives a "soft" boost to the compressor at each start-up.

Usage Guideline:

Suggested in installations with marginal power supply.

4. Crankcase Heater

An electric resistance heater which mounts to the base of the compressor to keep the lubricant warm during off cycles. Improves compressor lubrication on restart and minimizes the chance of liquid slugging.

Usage Guideline:

- Required in low ambient cooling applications.
- Required in long line applications.
- Suggested in all commercial applications.

5. Cycle Protector

The cycle protector is designed to prevent compressor short cycling. This control provides an approximate 5-minute delay after power to the compressor has been interrupted for any reason, including power outage, protector control trip, thermostat jiggling, or normal cycling.

6. Evaporator Freeze Thermostat

An SPST temperature-actuated switch that stops unit operation when evaporator reaches freeze-up conditions.

Usage Guideline:

Required when low ambient kit has been added.

7. Low-Ambient Pressure Switch Kit

A long life pressure switch which is mounted to outdoor unit service valve. It is designed to cycle the outdoor fan motor in order to maintain head pressure within normal operating limits (approximately 100 psig to 225 psig). The control will maintain working head pressure at low-ambient temperatures down to 0°F (-18°C) when properly installed.

Usage Guideline:

A Low-Ambient Pressure Switch or MotorMaster® Low-Ambient Controller must be used when cooling operation is used at outdoor temperatures below 55°F (12.8°C).

8. MotorMaster® Low-Ambient Controller

A fan-speed control device activated by a temperature sensor, designed to control condenser fan motor speed in response to the saturated, condensing temperature during operation in cooling mode only. For outdoor temperatures down to -20°F (-28.9°C), it maintains condensing temperature at 100°F ±10°F (37.8°C ± 5.5°C).

Usage Guideline:

A MotorMaster® Low Ambient Controller or Low-Ambient Pressure Switch must be used when cooling operation is used at outdoor temperatures below 55°F (12.8°C).

Suggested for all commercial applications.

9. Outdoor Air Temperature Sensor

Designed for use with Carrier Thermostats listed in this publication. This device enables the thermostat to display the outdoor temperature. This device also

is required to enable special thermostat features such as auxiliary heat lock out.

Usage Guideline:

Suggested for all Carrier thermostats listed in this publication.

Accessory Description and Usage (Listed Alphabetically) (Continued)

10. Sound Hood

Wraparound sound reducing cover for the compressor. Reduces the sound level by about 2 dBA.

Usage Guideline:

Suggested when unit is installed closer than 15 ft (4.57 m) to quiet areas, bedrooms, etc.

Suggested when unit is installed between two houses less than 10 ft (3.05 m) apart.

11. Support Feet

Four stick-on plastic feet that raise the unit 4 in. (101.6 mm) above the mounting pad. This allows sand, dirt, and other debris to be flushed from the unit base, minimizing corrosion.

Usage Guideline:

Suggested in the following applications:

Coastal installations.

Windy areas or where debris is normally circulating.

Rooftop installations.

For improved sound ratings.

12. Thermostatic Expansion Valve (TXV)

A modulating flow-control valve which meters refrigerant liquid flow rate into the evaporator in response to the superheat of the refrigerant gas leaving the evaporator.

Kit includes valve, adapter tubes, and external equalizer tube. Hard shut off types are available.

NOTE: When using a hard shut off TXV with single phase reciprocating compressors, a Compressor Start Assist Capacitor and Relay is required.

Usage Guideline:

Required to achieve AHRI ratings in certain equipment combinations. Refer to combination ratings.

Hard shut off TXV or LLS required in air conditioner long line applications.

Required for use on all zoning systems.

13. Time-Delay Relay

An SPST delay relay which briefly continues operation of indoor blower motor to provide additional cooling after the compressor cycles off.

NOTE: Most indoor unit controls include this feature. For those that do not, use the guideline below.

Usage Guideline:

For improved efficiency ratings for certain combinations of indoor and outdoor units. Refer to AHRI Unitary Directory.

14. Winter Start Control


This control is designed to alleviate nuisance opening of the low-pressure switch by bypassing it for the first 3 minutes of operation.

DIMENSIONS - ENGLISH

UNIT	SERIES	ELECTRICAL CHARACTERISTICS	A	B	C	D	E	F	G	K	L	M	N	P	OPERATING WEIGHT (LBS)	SHIPPING WEIGHT (LBS)	SHIPPING DIMENSIONS (L x W x H)
PAT3NA018	G	X 0 0 0	23 1/8"	24 13/16"	3 3/4"	3/4"	4 7/16"	18 1/16"	7 13/16"	2 13/16"	1/2"	12"	11 3/4"	11 7/8"	104	120	24 1/8" X 24 1/8" X 27 3/16"
PAT3NA024	F	X 0 0 0	23 1/8"	24 13/16"	3 3/4"	3/4"	4 7/16"	18 1/16"	7 13/16"	2 13/16"	1/2"	12"	11 3/4"	11 7/8"	107	123	24 1/8" X 24 1/8" X 27 3/16"
PAT3NA030	B	X 0 0 0	23 1/8"	28 7/16"	3 3/4"	3/4"	4 7/16"	18 1/16"	7 13/16"	2 13/16"	1/2"	12"	11 3/4"	12 1/2"	110	126	24 1/8" X 24 1/8" X 30 5/8"
PAT3NA036	E	X 0 0 0	23 1/8"	35 3/16"	3 7/8"	7/8"	4 7/16"	18 1/16"	7 13/16"	2 13/16"	1/2"	12"	11 3/4"	13 3/4"	128	142	24 1/8" X 24 1/8" X 37 7/16"
PAT3PA036	B	O 0 0 X	23 1/8"	35 3/16"	3 7/8"	7/8"	4 7/16"	18 1/16"	7 13/16"	2 13/16"	1/2"	12"	11 3/4"	13 3/4"	128	142	24 1/8" X 24 1/8" X 37 7/16"
PAT3NA042	B	X 0 0 0	31 3/16"	31 13/16"	3 7/8"	7/8"	6 9/16"	24 11/16"	9 1/8"	2 15/16"	5/8"	16"	15 1/2"	13 3/4"	164	178	32 3/16" X 32 3/16" X 34"
PAT3NA048	E	X 0 0 0	31 3/16"	35 3/16"	3 7/8"	7/8"	6 9/16"	24 11/16"	9 1/8"	2 15/16"	5/8"	16"	15 1/2"	15 1/2"	174	187	32 3/16" X 32 3/16" X 37 7/16"
PAT3PA048	D	O 0 0 X	31 3/16"	35 3/16"	3 7/8"	7/8"	6 9/16"	24 11/16"	9 1/8"	2 15/16"	5/8"	16"	15 1/2"	15 1/2"	174	187	32 3/16" X 32 3/16" X 37 7/16"
PAT3NA060	E	X 0 0 0	31 3/16"	28 7/16"	3 7/8"	7/8"	6 9/16"	24 11/16"	9 1/8"	2 15/16"	5/8"	16"	15 1/2"	12 3/4"	195	210	32 3/16" X 32 3/16" X 30 5/8"
PAT3PA060	B	O 0 0 X	31 3/16"	28 7/16"	3 7/8"	7/8"	6 9/16"	24 11/16"	9 1/8"	2 15/16"	5/8"	16"	15 1/2"	12 3/4"	195	210	32 3/16" X 32 3/16" X 30 5/8"

208-230-160	230-160	208/230-360	460-360
-------------	---------	-------------	---------

X = YES
O = NO



UNIT SIZE	"C" MIN. GROUND MOUNTING PAD APPLICATION DIMENSIONS	"Y" MIN. ROOF-TOP MOUNTING PAD APPLICATION DIMENSIONS
18, 24, 30, 36	23 1/8"	17 3/4"
-	25 3/4"	20 7/16"
42, 48, 60	31 3/16"	23"
-	35"	26 3/4"

MEASUREMENT - ENGLISH
U.S. EXPORT CLASSIFICATION: EAR89


PART NUMBER	SD4639-4	SHEET	1	REV	0
PART SHEET	2				

DIMENSIONS - SI

UNIT	SERIES	ELECTRICAL CHARACTERISTICS	A	B	C	D	E	F	G	K	L	M	N	P	OPERATING WEIGHT (Kgs)	SHIPPING WEIGHT (Kgs)	SHIPPING DIMENSIONS (L x W x H)
PA13MA018	G	X 0 0 0	587.4	630.2	95.2	19.0	112.7	458.8	198.4	71.4	12.7	304.8	298.4	301.6	47.2	54.4	612.8 X 612.8 X 690.6
PA13MA024	F	X 0 0 0	587.4	630.2	95.2	19.0	112.7	458.8	198.4	71.4	12.7	304.8	298.4	301.6	48.5	55.8	612.8 X 612.8 X 690.6
PA13MA030	B	X 0 0 0	587.4	722.3	95.2	19.0	112.7	458.8	198.4	71.4	12.7	304.8	298.4	317.5	49.9	57.2	612.8 X 612.8 X 777.9
PA13MA036	E	X 0 0 0	587.4	893.8	98.4	22.2	112.7	458.8	198.4	71.4	12.7	304.8	298.4	349.2	58.2	64.5	612.8 X 612.8 X 950.9
PA13PA036	B	0 0 0 X	587.4	893.8	98.4	22.2	112.7	458.8	198.4	71.4	12.7	304.8	298.4	349.2	58.2	64.5	612.8 X 612.8 X 950.9
PA13MA042	B	X 0 0 0	792.2	808.0	98.4	22.2	166.7	671.1	231.8	74.6	15.9	406.4	393.7	349.2	74.4	80.9	817.6 X 817.6 X 863.6
PA13MA048	E	X 0 0 0	792.2	893.8	98.4	22.2	166.7	671.1	231.8	74.6	15.9	406.4	393.7	393.7	79.1	85.0	817.6 X 817.6 X 950.9
PA13PA048	D	0 0 0 X	792.2	893.8	98.4	22.2	166.7	671.1	231.8	74.6	15.9	406.4	393.7	393.7	79.1	85.0	817.6 X 817.6 X 950.9
PA13MA060	E	X 0 0 0	792.2	722.3	98.4	22.2	166.7	671.1	231.8	74.6	15.9	406.4	393.7	323.8	88.6	95.5	817.6 X 817.6 X 777.9
PA13PA060	B	0 0 0 X	792.2	722.3	98.4	22.2	166.7	671.1	231.8	74.6	15.9	406.4	393.7	323.8	88.6	95.5	817.6 X 817.6 X 777.9

208-230-160	230-160	208/230-3-60	460-3-60
-------------	---------	--------------	----------

X = YES
0 = NO




UNIT SIZE	"X" MIN. GROUND MOUNTING PAD APPLICATION DIMENSIONS	"Y" MIN. ROOF-TOP MOUNTING PAD APPLICATION DIMENSIONS
18,24,30,36	587.4	451.3
-	654.0	518.5
42,48,60	792.2	583.2
-	889.0	679.7

MEASUREMENT- METRIC "SI"
U.S. EXPORT CLASSIFICATION:EAR99

PART NUMBER	SD04639-4	SHT	REV
REF. SHEET	NONE	2	0

CLEARANCES



Note: Numbers in () = mm

IMPORTANT: When installing multiple units in an alcove, roof well, or partially enclosed area, ensure there is adequate ventilation to prevent re-circulation of discharge air.

DETAILED COOLING CAPACITIES#

EVAPORATOR AIR		CONDENSER ENTERING AIR TEMPERATURES ° F (° C)																	
CFM	EWB ° F (° C)	75 (23.9)			85 (29.4)			95 (35)			105 (40.6)			115 (46.1)			125 (51.7)		
		Capacity MBtuh		Total System KW**	Capacity MBtuh		Total System KW**	Capacity MBtuh		Total System KW**	Capacity MBtuh		Total System KW**	Capacity MBtuh		Total System KW**	Capacity MBtuh		Total System KW**
		Total	Sens†	Total	Sens†	Total	Sens†	Total	Sens†	Total	Sens†	Total	Sens†	Total	Sens†	Total	Sens†	Total	Sens†
PA13NA018 - G Outdoor Section With CNPV*2414AL* + TDR Indoor Section																			
	72 (22.2)	21.21	11.38	1.27	20.31	11.05	1.42	19.41	10.71	1.59	18.37	10.33	1.78	17.33	9.96	2.02	16.00	9.48	2.26
	67 (19.4)	19.33	14.06	1.28	18.52	13.73	1.43	17.62	13.36	1.60	16.64	12.96	1.79	15.65	12.56	2.02	14.43	12.08	2.26
525	63 (17.2)	18.04	16.20	1.29	17.23	15.83	1.44	16.39	15.44	1.60	15.49	15.02	1.79	14.60	14.56	2.02	13.66	13.66	2.26
	62 (16.7)	17.76	16.72	1.29	16.97	16.34	1.44	16.16	15.93	1.60	15.36	15.36	1.79	14.58	14.58	2.02	13.66	13.66	2.26
	57 (13.9)	17.47	16.77	1.44	16.08	16.08	1.44	16.08	16.08	1.60	15.34	15.34	1.79	14.56	14.56	2.02	13.64	13.64	2.27
	72 (22.2)	21.47	11.95	1.30	20.62	11.65	1.45	19.68	11.30	1.62	18.64	10.93	1.81	17.55	10.55	2.05	16.24	10.08	2.29
	67 (19.4)	19.71	15.05	1.31	18.81	14.68	1.46	17.90	14.32	1.63	16.89	13.92	1.82	15.88	13.52	2.05	14.57	13.00	2.28
600	63 (17.2)	18.40	17.43	1.32	17.61	17.05	1.46	16.77	16.64	1.63	15.96	15.96	1.82	15.14	15.14	2.05	14.18	14.18	2.29
	62 (16.7)	18.19	18.01	1.32	17.54	17.28	1.46	16.74	16.74	1.63	15.96	15.96	1.82	15.14	15.14	2.05	14.17	14.17	2.30
	57 (13.9)	18.12	18.12	1.32	17.44	17.44	1.47	16.72	16.72	1.63	15.93	15.93	1.82	15.12	15.12	2.05	14.13	14.13	2.30
	72 (22.2)	21.70	12.53	1.33	20.81	12.21	1.48	19.86	11.87	1.65	18.78	11.49	1.84	17.62	11.09	2.06	16.35	10.84	2.32
	67 (19.4)	19.88	15.95	1.34	19.03	15.61	1.49	18.11	15.24	1.66	17.08	14.83	1.85	16.07	14.43	2.08	14.78	13.90	2.32
675	63 (17.2)	18.79	18.56	1.35	18.02	18.02	1.49	17.27	17.27	1.66	16.44	16.44	1.85	15.60	15.60	2.08	14.58	14.58	2.32
	62 (16.7)	18.71	18.71	1.34	18.02	18.02	1.49	17.26	17.26	1.66	16.44	16.44	1.85	15.59	15.59	2.08	14.58	14.58	2.33
	57 (13.9)	18.70	18.70	1.34	18.00	18.00	1.49	17.24	17.24	1.66	16.41	16.41	1.85	15.57	15.57	2.08	14.55	14.55	2.32

EVAPORATOR AIR		CONDENSER ENTERING AIR TEMPERATURES ° F (° C)																	
CFM	EWB ° F (° C)	75 (23.9)			85 (29.4)			95 (35)			105 (40.6)			115 (46.1)					
		Capacity MBtuh		Total System KW**	Capacity MBtuh		Total System KW**	Capacity MBtuh		Total System KW**	Capacity MBtuh		Total System KW**	Capacity MBtuh		Total System KW**			
		Total	Sens†	Total	Sens†	Total	Sens†	Total	Sens†	Total	Sens†	Total	Sens†	Total	Sens†	Total	Sens†	Total	Sens†
PA13NA024 - F Outdoor Section With CAP**2414A** Indoor Section																			
	72 (22.2)	27.06	13.28	1.64	25.82	12.84	1.84	24.64	12.43	2.06	23.44	12.02	2.30	22.11	11.56	2.57	20.22	11.56	2.57
	67 (19.4)	24.87	16.41	1.64	23.82	16.00	1.84	22.70	15.57	2.05	21.55	15.13	2.30	20.29	14.66	2.57	18.87	14.66	2.57
700	62 (16.7)	22.98	19.55	1.63	22.00	19.12	1.83	20.97	18.66	2.05	19.91	18.18	2.30	18.87	18.87	2.57	17.15	18.87	2.57
	57 (13.9)	22.41	22.41	1.63	21.61	21.61	1.83	20.75	20.75	2.05	19.85	19.85	2.30	18.87	18.87	2.57	17.15	18.87	2.57
	72 (22.2)	27.49	13.93	1.68	26.14	13.46	1.88	24.93	13.05	2.10	23.69	12.64	2.34	22.33	12.18	2.60	20.02	12.18	2.60
	67 (19.4)	25.24	17.44	1.68	24.15	17.03	1.87	23.00	16.60	2.09	21.83	16.16	2.33	20.54	15.69	2.60	18.87	15.69	2.60
800	62 (16.7)	23.44	20.97	1.67	22.46	20.51	1.87	21.49	21.49	2.09	20.55	20.55	2.33	19.52	19.52	2.60	17.15	19.52	2.60
	57 (13.9)	23.25	23.25	1.67	22.40	22.40	1.87	21.49	21.49	2.09	20.55	20.55	2.33	19.52	19.52	2.60	17.15	19.52	2.60
	72 (22.2)	27.76	14.53	1.72	26.38	14.07	1.91	25.12	13.65	2.13	23.86	13.23	2.38	22.46	12.77	2.64	20.02	12.77	2.64
	67 (19.4)	25.50	18.44	1.71	24.39	18.03	1.91	23.21	17.59	2.13	22.02	17.15	2.37	20.70	16.66	2.64	18.87	16.66	2.64
900	62 (16.7)	23.92	23.92	1.71	23.03	23.03	1.91	22.08	22.08	2.13	21.10	21.10	2.37	20.02	20.02	2.64	18.87	20.02	2.64
	57 (13.9)	23.92	23.92	1.71	23.04	23.04	1.91	22.08	22.08	2.13	21.10	21.10	2.37	20.02	20.02	2.64	18.87	20.02	2.64

See notes on page 15

DETAILED COOLING CAPACITIES# (CONT.)

EVAPORATOR AIR		CONDENSER ENTERING AIR TEMPERATURES ° F (° C)																			
		75 (23.9)				85 (29.4)				95 (35)				105 (40.6)				115 (46.1)			
		CFM	EWB ° F (° C)	Capacity MBtuHt		Total Sys-tem KW**	Capacity MBtuHt		Total Sys-tem KW**	Capacity MBtuHt		Total Sys-tem KW**	Capacity MBtuHt		Total Sys-tem KW**	Capacity MBtuHt		Total Sys-tem KW**			
Total	Sens†			Total	Sens†		Total	Sens†		Total	Sens†		Total	Sens†		Total	Sens†				
		PA13NA030-B Outdoor Section With CAP**3014A** Indoor Section																			
	72 (22.2)	31.88	16.54	1.97	30.55	16.06	2.21	29.17	15.57	2.48	27.73	15.07	2.77	26.14	14.51	3.10					
	67 (19.4)	29.45	20.69	1.97	28.21	20.19	2.21	26.90	19.68	2.47	25.54	19.15	2.77	24.04	18.57	3.09					
	62 (16.7)	27.29	24.80	1.96	26.15	24.27	2.20	24.96	23.68	2.47	23.83	23.83	2.76	22.65	22.65	3.09					
	57 (13.9)	26.90	26.90	1.96	25.94	25.94	2.20	24.91	24.91	2.47	23.83	23.83	2.76	22.65	22.65	3.09					
	72 (22.2)	32.25	17.34	2.02	30.87	18.86	2.26	29.45	18.86	2.53	27.98	18.86	2.82	26.34	18.86	3.14					
	67 (19.4)	29.82	22.01	2.01	28.55	21.52	2.25	27.20	21.00	2.52	25.81	20.47	2.81	24.28	19.88	3.14					
	62 (16.7)	27.85	27.62	2.01	26.81	26.81	2.25	25.72	25.72	2.51	24.59	24.59	2.81	23.35	23.35	3.14					
	57 (13.9)	27.82	27.82	2.01	26.81	26.81	2.25	25.73	25.73	2.51	24.60	24.60	2.81	23.35	23.35	3.14					
	72 (22.2)	32.50	18.10	2.07	31.08	17.61	2.31	29.63	17.12	2.57	28.13	16.61	2.87	26.46	16.05	3.19					
	67 (19.4)	30.08	23.28	2.06	28.78	22.78	2.30	27.41	22.26	2.57	26.00	21.72	2.86	24.45	21.12	3.19					
	62 (16.7)	28.55	28.55	2.06	27.50	27.50	2.30	26.36	26.36	2.56	25.19	25.19	2.86	23.89	23.89	3.18					
	57 (13.9)	28.55	28.55	2.06	27.50	27.50	2.30	26.37	26.37	2.56	25.19	25.19	2.86	23.89	23.89	3.18					

EVAPORATOR AIR		CONDENSER ENTERING AIR TEMPERATURES ° F (° C)																			
		75 (23.9)				85 (29.4)				95 (35)				105 (40.6)				115 (46.1)			
		CFM	EWB ° F (° C)	Capacity MBtuHt		Total Sys-tem KW**	Capacity MBtuHt		Total Sys-tem KW**	Capacity MBtuHt		Total Sys-tem KW**	Capacity MBtuHt		Total Sys-tem KW**	Capacity MBtuHt		Total Sys-tem KW**			
Total	Sens†			Total	Sens†		Total	Sens†		Total	Sens†		Total	Sens†		Total	Sens†				
		PA13NA036-EB Outdoor Section With CAP**4821A** Indoor Section																			
	72 (22.2)	29.86	29.86	3.90	38.13	19.65	2.71	36.46	19.06	3.04	34.71	18.45	3.40	32.77	17.79	3.80					
	67 (19.4)	36.66	25.23	2.41	35.22	24.67	2.71	33.64	24.05	3.03	31.99	23.42	3.40	30.17	22.72	3.79					
	62 (16.7)	33.97	30.22	2.40	32.65	29.62	2.70	31.21	28.94	3.03	29.76	28.76	3.39	28.35	28.35	3.79					
	57 (13.9)	33.42	33.42	2.40	32.30	32.30	2.70	31.07	31.07	3.03	29.78	29.78	3.39	28.35	28.35	3.79					
	72 (22.2)	40.35	21.22	2.47	38.49	20.57	2.77	36.81	19.99	3.10	35.01	19.38	3.46	33.02	18.70	3.85					
	67 (19.4)	37.10	26.78	2.47	35.62	26.22	2.76	34.00	25.60	3.09	32.31	24.96	3.45	30.45	24.26	3.85					
	62 (16.7)	34.75	32.12	2.46	33.33	33.33	2.76	32.07	32.07	3.09	30.71	30.71	3.45	29.20	29.20	3.85					
	57 (13.9)	34.54	34.54	2.46	33.37	33.37	2.76	32.07	32.07	3.09	30.71	30.71	3.45	29.20	29.20	3.85					
	72 (22.2)	40.70	22.12	2.53	38.75	21.45	2.83	37.03	20.86	3.16	35.19	20.25	3.52	33.17	19.57	3.91					
	67 (19.4)	37.49	28.29	2.52	35.90	27.69	2.82	34.25	27.07	3.15	32.53	26.42	3.51	30.65	25.71	3.90					
	62 (16.7)	35.43	35.43	2.52	34.21	34.21	2.82	32.85	32.85	3.14	31.43	31.43	3.51	29.86	29.86	3.90					
	57 (13.9)	35.43	35.43	2.52	34.21	34.21	2.82	32.85	32.85	3.14	31.43	31.43	3.51	29.86	29.86	3.90					

See notes on page 15

DETAILED COOLING CAPACITIES# (CONT.)

EVAPORATOR AIR		CONDENSER ENTERING AIR TEMPERATURES ° F (° C)														
		75 (23.9)			85 (29.4)			95 (35)			105 (40.6)			115 (46.1)		
CFM	EWB ° F (° C)	Capacity MBtuHt		Total Sys-tem KW**	Capacity MBtuHt		Total Sys-tem KW**	Capacity MBtuHt		Total Sys-tem KW**	Capacity MBtuHt		Total Sys-tem KW**	Capacity MBtuHt		Total Sys-tem KW**
		Total	Sens†		Total	Sens†		Total	Sens†		Total	Sens†		Total	Sens†	
PA13NA042 – B Outdoor Section With CAP**4221A** Indoor Section																
	72 (22.2)	46.73	23.07	2.89	44.70	22.34	3.20	42.56	21.57	3.54	40.30	20.78	3.92	37.86	19.94	4.34
	67 (19.4)	42.85	28.38	2.87	40.97	27.64	3.18	38.98	26.86	3.52	36.89	26.05	3.91	34.65	25.19	4.33
	62 (16.7)	39.95	33.67	2.86	37.65	32.90	3.17	35.87	32.09	3.51	34.03	31.22	3.90	32.16	32.16	4.32
	57 (13.9)	38.30	38.30	2.85	36.91	36.91	3.17	35.44	35.44	3.51	33.88	33.88	3.90	32.18	32.18	4.32
	72 (22.2)	47.42	24.09	2.96	45.31	23.35	3.27	43.09	22.57	3.61	40.75	21.77	3.99	38.23	20.92	4.40
	67 (19.4)	43.52	30.05	2.94	41.57	29.29	3.25	39.50	28.50	3.59	37.35	27.69	3.97	35.04	26.83	4.39
	62 (16.7)	40.18	35.98	2.93	38.46	35.17	3.24	36.65	36.65	3.58	35.04	35.04	3.96	33.24	33.24	4.39
	57 (13.9)	39.77	39.77	2.92	38.29	38.29	3.23	36.71	36.71	3.58	35.04	35.04	3.96	33.24	33.24	4.39
	72 (22.2)	47.94	25.07	3.02	45.76	24.32	3.33	43.48	23.54	3.67	41.08	22.73	4.05	38.49	21.87	4.47
	67 (19.4)	44.03	31.67	3.01	42.02	30.91	3.31	39.90	30.12	3.66	37.70	29.30	4.04	35.34	28.42	4.46
	62 (16.7)	40.98	40.58	2.99	39.39	39.39	3.30	37.73	37.73	3.65	35.97	35.97	4.03	34.07	34.07	4.45
	57 (13.9)	40.96	40.96	2.99	39.40	39.40	3.30	37.74	37.74	3.65	35.98	35.98	4.03	34.07	34.07	4.45
CONDENSER ENTERING AIR TEMPERATURES ° F (° C)																
EVAPORATOR AIR		CONDENSER ENTERING AIR TEMPERATURES ° F (° C)														
		75 (23.9)			85 (29.4)			95 (35)			105 (40.6)			115 (46.1)		
CFM	EWB ° F (° C)	Capacity MBtuHt		Total Sys-tem KW**	Capacity MBtuHt		Total Sys-tem KW**	Capacity MBtuHt		Total Sys-tem KW**	Capacity MBtuHt		Total Sys-tem KW**	Capacity MBtuHt		Total Sys-tem KW**
		Total	Sens†		Total	Sens†		Total	Sens†		Total	Sens†		Total	Sens†	
PA13NA048 – E-D Outdoor Section With CAP**4821A** Indoor Section																
	72 (22.2)	54.60	27.69	3.34	52.26	26.84	3.70	49.78	25.94	4.11	47.16	25.01	4.56	44.34	24.02	5.06
	67 (19.4)	49.83	34.09	3.33	47.64	33.21	3.70	45.33	32.30	4.10	42.89	31.34	4.56	40.29	30.34	5.05
	62 (16.7)	45.55	40.45	3.32	43.56	39.53	3.69	41.50	38.56	4.10	39.36	39.17	4.55	37.40	37.40	5.05
	57 (13.9)	44.50	44.50	3.32	42.88	42.88	3.69	41.17	41.17	4.10	39.35	39.35	4.55	37.40	37.40	5.05
	72 (22.2)	55.49	29.01	3.42	53.07	28.15	3.78	50.49	27.24	4.19	47.77	26.30	4.64	44.86	25.30	5.13
	67 (19.4)	50.68	36.22	3.41	48.40	35.33	3.77	46.00	34.40	4.18	43.48	33.44	4.63	40.81	32.43	5.13
	62 (16.7)	46.57	43.32	3.40	44.58	44.17	3.77	42.69	42.69	4.18	40.76	40.76	4.63	38.69	38.69	5.13
	57 (13.9)	46.24	46.24	3.40	44.52	44.52	3.77	42.69	42.69	4.18	40.76	40.76	4.63	38.69	38.69	5.13
	72 (22.2)	56.14	30.25	3.49	53.64	29.38	3.86	50.99	28.46	4.27	48.20	27.51	4.72	45.21	26.50	5.21
	67 (19.4)	51.29	38.24	3.48	48.95	37.35	3.85	46.49	36.41	4.26	43.92	35.44	4.71	41.18	34.40	5.21
	62 (16.7)	47.65	47.65	3.48	45.85	45.85	3.85	43.93	43.93	4.26	41.90	41.90	4.71	39.72	39.72	5.21
	57 (13.9)	47.66	47.66	3.48	45.85	45.85	3.85	43.94	43.94	4.26	41.90	41.90	4.71	39.72	39.72	5.21

See notes on page 15

DETAILED COOLING CAPACITIES# (CONT.)

EVAPORATOR AIR		CONDENSER ENTERING AIR TEMPERATURES ° F (° C)														
		75 (23.9)			85 (29.4)			95 (35)			105 (40.6)			115 (46.1)		
		CFM	EWB ° F (° C)	Capacity MBtuHt		Total Sys-tem KW**	Capacity MBtuHt		Total Sys-tem KW**	Capacity MBtuHt		Total Sys-tem KW**	Capacity MBtuHt		Total Sys-tem KW**	
Total	Sens†			Total	Sens†		Total	Sens†		Total	Sens†					
		PA13NA060—E-B Outdoor Section With CAP**6024A** Indoor Section														
	72 (22.2)	67.21	34.03	4.17	64.33	32.99	4.62	61.25	31.88	5.13	57.99	30.72	5.69	54.51	29.50	6.30
1750	67 (19.4)	61.78	42.10	4.12	59.11	41.03	4.58	56.26	39.90	5.08	53.27	38.73	5.64	50.10	37.51	6.26
	62 (16.7)	56.85	50.10	4.08	54.44	49.01	4.54	51.89	47.82	5.04	49.28	46.54	5.60	46.74	46.74	6.23
	57 (13.9)	55.51	55.51	4.07	53.53	53.53	4.53	51.41	51.41	5.04	49.17	49.17	5.60	46.74	46.74	6.23
2000	72 (22.2)	68.22	35.65	4.27	65.20	34.58	4.73	62.01	33.46	5.23	58.62	32.28	5.79	55.02	31.05	6.40
	67 (19.4)	62.74	44.73	4.22	59.96	43.64	4.68	57.00	42.50	5.18	53.90	41.32	5.74	50.62	40.07	6.36
	62 (16.7)	58.02	53.65	4.18	55.58	52.46	4.64	53.19	53.19	5.15	50.79	50.79	5.71	48.19	48.19	6.33
2250	72 (22.2)	68.93	37.17	4.37	65.81	36.09	4.83	62.53	34.96	5.33	59.04	33.77	5.89	55.34	32.51	6.50
	67 (19.4)	63.43	47.24	4.32	60.56	46.14	4.78	57.53	44.99	5.28	54.34	43.78	5.84	50.99	42.50	6.46
	62 (16.7)	59.25	59.25	4.29	57.01	57.01	4.75	54.62	54.62	5.25	52.11	52.11	5.82	49.36	49.36	6.44
	57 (13.9)	59.25	59.25	4.29	57.01	57.01	4.75	54.62	54.62	5.25	52.12	52.12	5.82	49.36	49.36	6.44

NOTES:

- † Total and sensible capacities are net capacities. Blower motor heat has been subtracted.
- ‡ Sensible capacities shown are based on 80°F (27°C) entering air at the indoor coil. For sensible capacities at other than 80°F (27°C), deduct 835 BtuH (245 kW) per 1000 CFM (480 L/S) of indoor coil air for each degree below 80°F (27°C), or add 835 BtuH (245 kW) per 1000 CFM (480 L/S) of indoor coil air per degree above 80°F (27°C).
- # Detailed cooling capacities are based on indoor and outdoor unit at the same elevation per AHRI standard 210/240—2008. If additional tubing length and/or indoor unit is located above outdoor unit, a slight variation in capacity may occur.

** System kw is total of indoor and outdoor unit kilowatts.

EWB — Entering Wet Bulb

NOTE: When the required data fall between the published data, interpolation may be performed. Extrapolation is not an acceptable practice.

SYSTEM DESIGN

1. Intended for outdoor installation with free air inlet and outlet. Outdoor fan external static pressure available is less than 0.01-in. wc.
2. Minimum outdoor operating air temperature without low-ambient operation accessory is 55°F (12.8°C).
3. Maximum outdoor operating air temperature is 125°F (51.7°C).
4. For reliable operation, unit should be level in all horizontal planes.
5. Maximum elevation of indoor coil above or below base of outdoor unit is: indoor coil above = 80 ft (24.38 m), indoor coil below = 200 ft (60.96 m).
6. For interconnecting refrigerant tube lengths greater than 80 ft (24.38 m) horizontal or 35 ft (10.7 m) vertical differential, consult Residential Piping and Long-Line Guideline available from equipment distributor.
7. Crankcase heater required when the application qualifies as long-line.
8. If any refrigerant tubing is buried, provide a minimum 6 in (152.4 mm) vertical rise to the valve connections at the unit. Refrigerant tubing lengths up to 36 in (914.4 mm) may be buried without further consideration.
9. Use only copper wire for electric connection at unit. Aluminum and clad aluminum are not acceptable for the type of connector provided.