Date Prepared

Replaces

May 22, 2006

Apr. 01, 2003

MATERIAL SAFETY DATA SHEET

SECTION 1 CHEMICAL PRODUCT AND COMPANY INFORMATION

Product Name: Totaline Condenser Cleaner Non-Acid (Aerosol)

Product Number(s): P902-0118
Product Use: Condenser coil cleaner

Company Name:

North American Research Corporation

P.O. Box 1318 Lewisville, TX 75067

Telephone Numbers: (972) 492-1800, (800) 527-7520, Fax (972) 394-6755

Emergencies: Infotrac (800) 535-5053 (24 hours, everyday)

SECTION 2 COMPOSITION / INFORMATION ON INGREDIENTS

OSHA Hazardous Components (29 CFR 1910.1200):

	CAS				%
	Registry No.	OSHA PEL	ACGIH TLV	Other Limits	(Optional)
Potassium Hydroxide	1310-58-3	2 mg/m ³ Ceiling	2 mg/m ³ Ceiling	None known	< 26
Propane/N-Butane Propellant	68476-86-8	1,000 ppm	1,000 ppm	None known	

SECTION 3 HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

POISON! DANGER! CORROSIVE. CAUSES SEVERE BURNS TO SKIN, EYES, AND OTHER BODY TISSUE. HARMFUL OR FATAL IF SWALLOWED. DO NOT SPRAY NEAR SPARK OR OPEN FLAME. CONTENTS UNDER PRESSURE. DO NOT PUNCTURE OR INCINERATE CONTAINER.

POTENTIAL HEALTH EFFECTS

EYE CONTACT: Corrosive. May cause permanent damage including blindness.

SKIN CONTACT: Corrosive. May cause permanent damage.

INHALATION: May cause irritation and corrosive effects to the nose, throat, and respiratory tract. Severe injury is usually

avoided by self-limiting coughing and sneezing symptoms.

INGESTION: Corrosive. May cause burns to mouth, throat, and stomach.

CHRONIC EXPOSURE: No known chronic effects.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: None known other than existing skin disorders.

CARCINOGENICITY: NTP? No IARC Monographs? No OSHA Regulated? No

SECTION 4 FIRST-AID MEASURES

EYE CONTACT: Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Get medical attention

immediately.

SKIN CONTACT: Flush immediately with plenty of water for at least 15 minutes. Get medical attention immediately.

INHALATION: If breathing is difficult: Remove to fresh air. Get medical attention immediately.

INGESTION: Do not induce vomiting! Immediately drink large quantities of water. Never give anything by mouth to an

unconscious person. Get medical attention immediately.

SECTION 5 FIRE-FIGHTING MEASURES

FLASHPOINT: Not flammable METHOD: Aerosol flame projection

FLAMMABLE LIMITS: LEL: Not applicable UEL: Not applicable AUTOIGNITION TEMP: Not applicable

GENERAL HAZARD: Not considered to be a fire hazard unless propellant gas only is sprayed from can. No flammable gasses escape when liquid product is sprayed normally. Do not spray near spark or open flame. Will react with some metals, eg. Aluminum, tin, zinc to form flammable hydrogen gas.

FIRE EXTINGUISHING MEDIA: Use means suitable for extinguishing surrounding fire. Water spray may be used to keep fire-exposed containers cool.

SPECIAL INFORMATION: At elevated temperatures (above 120°F), aerosol containers may burst. Corrosive material. See sections 8 and 10.

SECTION 6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS: Put on appropriate personal protective equipment.

ENVIRONMENTAL PRECAUTIONS AND CLEAN-UP:

Small spills: Mop up or soak up with rags and flush with water.

In the event of major spillage: Use appropriate containment consistent with good industrial or environmental practice. Recover as much as possible. Pump, sweep or scrape up the remaining material and place in suitable clean containers for disposal by proper methods. Use a water rinse for final clean-up.

SECTION 7 STORAGE AND HANDLING

HANDLING: This product uses a flammable aerosol propellant. Do not spray near sparks or open flames such as pilot lights. While the product itself is not considered a flammable aerosol, certain conditions, such as the initial spray of a new can or the final sprays of a used can, could expel propellant gas only which will ignite if exposed to sparks or open flame.

Avoid contact with eyes, skin, and clothing. Do not taste or swallow. Avoid breathing vapors or spray mists. Wash thoroughly after handling. Remove and wash contaminated clothing and footwear before reuse. Product residue may remain on/in empty containers. All precautions for handling the product must be used in handling the empty container and residue. FOR INDUSTRIAL USE ONLY.

STORAGE: Store aerosol containers below 120°F. Store in a cool, dry, ventilated area out of direct sunlight. Protect against physical damage in storage and on service vehicle.

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS: Good general ventilation should be sufficient to control airborne levels. Respiratory protection is not required if good ventilation is maintained.

PERSONAL PROTECTION:

EYES: Chemical splash goggles.

HANDS: Chemical resistant gloves; rubber, neoprene, or other impervious material.

RESPIRATORY: If mists/vapors are not adequately controlled by ventilation, use appropriate respiratory protection to avoid over

exposure. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must

be followed whenever workplace conditions warrant a respirator's use.

FEET: Chemical resistant boots; rubber, neoprene, or other impervious material. BODY: If major exposure is possible, wear suitable, impervious protective clothing.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: Yellowish, golden liquid. Bland odor.

SPECIFIC GRAVITY: 1.1

VAPOR PRESSURE: Not determined VAPOR DENSITY: Not determined

SOLUBILITY IN WATER: Complete pH: 14

BOILING POINT: 212°F FREEZING / MELTING POINT: Not determined

EVAPORATION RATE (Butyl Acetate = 1): Not determined

SECTION 10 STABILITY AND REACTIVITY

STABILITY: Stable under ordinary conditions of use and storage. HAZARDOUS POLYMERIZATION: Will not occur.

INCOMPATIBILITY (Materials to Avoid): Reactive with oxidizing agents, acids, chlorinated hydrocarbons, acetone. Will react with some metals, e.g., aluminum, tin, zinc, to form flammable hydrogen gas.

HAZARDOUS DECOMPOSITION PRODUCTS: When exposed to fire, produces normal products of combustion.

SECTION 11 TOXICOLOGICAL INFORMATION

For Potassium Hydroxide (1310-58-3): Oral LD50 (rat): 365 mg/kg. Primary skin irritation: (rabbit, 24hr) severe. Primary eye irritation: (rabbit, 24hr) severe.

SECTION 12 ECOLOGICAL INFORMATION

For Potassium Hydroxide (1310-58-3): LC50 (96hr) Fathead minnow, 45% KOH solution = 179 mg/L.

SECTION 13 DISPOSAL CONSIDERATIONS

Use up contents, replace cap and discard in trash. Disposal of unused, undiluted product is regulated under environmental and transportation laws as a corrosive waste. Dispose of container and unused contents in accordance with federal, state, and local requirements.

SECTION 14 TRANSPORT INFORMATION

U.S. Department of Transportation: Consumer Commodity ORM-D (domestic, ground shipments only)

Aerosols, corrosive, Packing Group II, 2.2, UN1950, Ltd. Qty.

SECTION 15 REGULATORY INFORMATION

TSCA: All ingredients of this product are listed or are excluded from listing on the U.S. TSCA chemical substances inventory.

CERCLA: Potassium Hydroxide (1310-58-3); RQ 1000 lbs.

SARA TITLE III: Section 311/312 Hazard Category: Acute: Yes Chronic: No Fire: No Pressure: No Reactive Hazard: Yes

Section 313 Reportable Ingredients: None

SECTION 16 OTHER INFORMATION

NFPA RATING: Health - 3, Flammability - 4 (aerosol propellant), Reactivity - 1

HMIS® RATING: Health - 3, Flammability - 4 (aerosol propellant), Reactivity - 2

HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint and Coatings Association (NPCA).

NOTICE: This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all federal, state, provincial, and local laws and regulations.