| PRODUCT NUMBER:  | PRODUCT DATA SHEET   | MODEL VARIATIONS  |
|--|--|---|
| 3500/3600 SERIES<br><b>DESCRIPTION:</b><br>METAL TOP INSULATED REGISTER BOX  | <b>DATE:</b><br>10/31/12   | 3500F - R4.2 WITH FLANGE<br>3600F - R6.0 WITH FLANGE<br>3600F8 - R8.0 WITH FLANGE<br>3500NF - R4.2 WITHOUT FLANGE<br>3600NF - R6.0 WITHOUT FLANGE<br>3600NF8 - R8.0 WITHOUT FLANGE  |
|  |  | PRODUCTION DATA   |
|  |  | OUTER BOX: 30 GAUGE GALVANIZED STEEL.<br>COLLAR: ROLL FORMED 30GA GALVANIZED<br>STEEL PER ASTM A653 CS TYPE B.  |
|  | SHOWN  | PRODUCT CHARACTERISTICS   |
| SHOWN<br>WITH FLANGE   |  | INTERNAL INSULATION: R4.2, R6.0 OR R8.0<br>BLACK INTERIOR.<br>½" DRYWALL FLANGE.<br>12 HOLE CLUSTER FOR REGISTER ATTACHMENT.<br>AVAILABLE WITH OR WITHOUT MOUNTING FLANG<br>AVAILABLE WITH OR WITHOUT GASKET.<br><b>PRODUCT SIZE INFORMATION</b><br>4 <sup>3</sup> / <sub>8</sub> " DEEP FRAMED BOX<br>3" LONG COLLAR WITH CONVEX BEAD<br>OUTER BOX DIMENSION IS 2 <sup>5</sup> / <sub>8</sub> " GREATER<br>THAN REGISTER DIMENSION |
| <b>NOTES:</b><br>INTERNAL INSULATION USED MEETS THE REQUIREMENTS<br>STANDARD TEST METHOD FOR FUNGI RESISTANCE.             | OF ASTM C 1338 (FORMERLY ASTM C 665)                                     | Snap-Rite<br>Manufacturing, Inc.<br>A Gray Co.  |
| CAN ALSO BE MADE WITH A 45° ANGLE COLLAR INSTEAD<br>3500FA = R4 W/45° COLLAR & FLANGE<br>3600FA = R6 W/45° COLLAR & FLANGE | 3500NFA = R4 W/45° COLLAR NO FLANG<br>3600NFA = R6 W/45° COLLAR NO FLANG | 232 NORTH IDA STREET 6285 PETERSON ROAD   GE COATS, NC 27521 LAKE PARK, GA 31636   GE PH: 910-897-4080 PH: 229-559-3772   |
| 3600FA8=R8 W/45° COLLAR & FLANGE   | 3600NFA8=R8 W/45° COLLAR NO FLANG  | FX: 910-897-0355 FX: 229-559-9965   |