

HI WALL

B Series / 60 Hz



-  **Cooling Only**
-  **Quiet operation**
-  **R-410A refrigerant**
-  **Auto restart function**
-  **Remote control**
-  **Dehumidification Mode**
-  **LED Display**
-  **Anti Mildew**
-  **Energy Saving Mode**
-  **Auto Diagnostic function**
-  **Timer**
-  **Turbo Mode**

Technical Specifications:

TECHNICAL SPECIFICATIONS								
Outdoor Unit Model with Piping Kit		TBG41B-009PH1H1C	TBG41B-009PH3H1C	TBG41B-012PH1H1C	TBG41B-012PH3H1C	TBG41B-018PH3H1C	TBG41B-024PH3H1C	TBG41B-036PH3H1C
Power supply		115V/60Hz/1Ph	208-230V/60Hz/1Ph	115V/60Hz/1Ph	208-230V/60Hz/1Ph	208-230V/60Hz/1Ph	208-230V/60Hz/1Ph	208-230V/60Hz/1Ph
Nominal Cooling capacity	BTUH	9,000	9,000	12,000	12,000	18,000	24,000	33,000
EER	BTUH/W	9.9	9.7	10.3	9.9	10.1	10.3	9.89
Dimensions (W x H x D)	mm	720 x 428 x 310	720 x 428 x 310	776 x 540 x 320	776 x 540 x 320	848 x 540 x 320	913 x 680 x 378	980 x 790 x 440
Net weight	kg	20	23	27	27	50	48	20.0
Packing dimensions (W x H x D)	mm	765 x 475 x 350	765 x 475 x 350	820 x 355 x 580	820 x 355 x 580	878 x 580 x 360	994 x 428 x 725	1083 x 488 x 855
Gross weight	kg	28	26	29.5	29.5	36	52	75
Current	A	11.09	5.8	11.39	8.1	10.9	11.6	13.7
Compressor		Rotary	Rotary	Rotary	Rotary	Rotary	Rotary	Rotary
Refrigerant	Type / Charge kg	R410A / 0.55	R410A / 0.55	R410A / 0.53	R410A / 0.63	R410A / 0.78	R410A / 1.25	R410A / 2.40
Noise Level	sound pressure dB(A)	48	48	52	50	53	54	58
Connecting Pipe (Gas)	mm / Inches	9.52mm / 3/8"	9.52mm / 3/8"	12mm / 1/2"	12mm / 1/2"	12mm / 1/2"	16mm / 5/8"	19mm / 3/4"
Connecting Pipe (Liquid)	mm / Inches	6mm / 1/4"	6mm / 1/4"	6mm / 1/4"	6mm / 1/4"	6mm / 1/4"	6mm / 1/4"	6mm / 1/4"
Maximum Pipe length	m	15	15	20	20	25	25	30
Maximum vertical separation	m	10	10	10	10	10	10	20
Indoor Unit Model No.		TBH41B-009-H1H1C	TBH41B-009-H3H1C	TBH41B-012-H1H1C	TBH41B-012-H3H1C	TBH41B-018-H3H1C	TBH41B-024-H3H1C	TBH41B-036-H3H1C
Dimensions (W x H x D)	mm	713 x 270 x 195	713 x 270 x 195	790 x 200 x 275	790 x 200 x 275	970 x 300 x 224	1078 x 325 x 246	1350 x 326 x 267
Net weight	kg	8.50	8.50	9	9	13.50	16.50	20
Packing dimensions (W x H x D)	mm	773 x 347 x 265	773 x 347 x 265	850 x 262 x 339	850 x 262 x 339	1038 x 305 x 380	1145 x 335 x 413	1438 x 421 x 381
Gross weight	kg	10.50	10.50	11	11	16.5	20	27
Noise Level	(Max / Min)	40/27	40/27	44 / 29	42 / 28	47 / 36	50 / 38	56/47

REFRIGERANT R-410A

Authorized Dealer:



Carrier InterAmerica Corp
Miami, Florida USA
www.tempblue.com