



Features:

- Auto Restart Function
- 12 Grades Indoor Fan Speeds
- 5 Grades Outdoor Fan Speeds
- Turbo Mode
- 2 Way Draining
- Self Diagnosis And Auto Protection
- Auto Desfroting
- Emergency Using Function
- Refrigerant Leakage Detect
- Low Ambient Cooling
- Anti Cold Air Function
- Louver Position Memory Function
- Manual Switch Button
- Silent Mode
- Auto Swing
- Two Directional Airflow
- Timer
- High Density Filter



Technical Specifications:

Outdoor Unit Model Number		TBG43QX012PH3N1C	TBG43QX018PH3N1C	TBG43QX024PH3N1C
Indoor Unit Model number		TBH43QX012-H3N1C	TBH43QX018-H3N1C	TBH43QX024-H3N1C
Power supply	V,HZ,Ph	208/230V,1Ph,60Hz	208/230V,1Ph,60Hz	208/230V,1Ph,60Hz
Cooling				
Capacity	Btu/h	12000(3753~12283)	18000(7267~19789)	23000(7881~26900)
Input	W	960	1440	1840
Rated current	A	4.4	6.55	8.37
EER	W/W	13.5	12.8	12.6
SEER	W/W	23	23	20
Indoor Unit				
Air flow (Hi/Mi/Lo)	CFM	282/208/145	563/389/330	570/451/380
Indoor noise level (Hi/Mi/Lo)	dB(A)	37.5/30/22.5	45/36.5/30.5	46/40/34
Dimension(W*D*H)	inch	31.57x7.44x11.69	42.51x8.90x13.19	42.51x8.90x13.19
Packing (W*D*H)	inch	34.45x11.22x14.77	45.47x16.34x12.40	45.47x16.34x12.40
Net/Gross weight	lbs.	17.0/22.0	18.7/24.3	17.4/21.6
Outdoor Unit				
Outdoor noise level	dB(A)	54	55	56.5
Dimension(W*D*H)	inch	32 x13x22	34x15x28	38x17x32
Packing (W*D*H)	inch	36.22x15.35x24.21	37.99x15.55x30.11	42.91x19.69x34.45
Net/Gross weight	lbs.	71.0/77.0	75.4/82.5	133.5/145.5
Connection Pipe				
Liquid side/ Gas side	mm(inch)	6.35mm(1/4in)/12.7mm(1/2in)	6.35mm(1/4in)/12.7mm(1/2in)	9.52mm(3/8in)/15.9mm(5/8in)
Max. Distance Height	m/ ft	25/ 55.11	30/ 66.15	30/ 66.15
Max. Distance Length	m/ ft	10/ 22.04	20/ 44.10	20/ 44.10
Qty per 20' /40' /40'HQ	Unit	84/178/214	60/126/142	44/92/108

REFRIGERANT **R-410A**

AHRI CERTIFIED



Authorized Dealer:



Carrier InterAmerica Corp
Miami, Florida USA
www.tempblue.com