

SMMSe/SHRMe VRF Indoor Unit MMD-AP0240VHG2UL / Vertical Air Handler

TOSHIBA
Carrier

Submittal Data

Job Data _____ Location _____
 Buyer _____ Buyer PO # _____ Carrier # _____
 Unit Number _____ Model Number _____
 Performance Data Certified By _____ Date _____



STANDARD FEATURES

- Dual Drainage Spouts
- Three Fan Speeds - High, Medium and Low
- Unit Can Be Installed Standing Vertical or Laid Horizontally
- Electronically Commutated Fan Motor (ECM)
- Built In Pulse Modulating Valve For Installation Ease
- Removable Front Panel Provides Easy Access
- Filter MERV 3

INDOOR UNIT MODEL	MMD-AP0240VHG2UL	
PERFORMANCE		
Cooling Rated Capacity	Btu/h	24,000
Heating Rated Capacity	Btu/h	27,000
Airflow (H / M / L)	CFM	760 / 660 / 600
Sound Data (H / M / L) †	dBA	41.4 / 38.4 / 37.5
ESP (Factory Default)	wg	0.3
ELECTRICAL		
Power Supply	V/Ph/Hz	208-230/1/60
MCA*	A	2.8
MOCP*	A	15

Full Load Amps (FLA)	A	2.2
PHYSICAL DATA		
Pipe Connection Size - Liquid	inches	3/8 (brazed)
Pipe Connection Size - Suction	inches	5/8 (brazed)
Pipe Connection Size - Drain	inches	3/4 (FTP)
Refrigerant		R410A
DIMENSIONS (inches)	H (in)	46-7/8
	W (in)	17-3/4
	D (in)	22-1/4
NET WEIGHT	lbs	164

ACCESSORIES (Optional)

- Wired Remote Controller (7-Day Programmable) - RBC-AMS54E-UL
- Simple Wired Remote Control - RBC-AS41UL
- Stand Alone Receiver with Wireless Remote TCB-AX32UL
- Remote Sensor TCB-TC41LUL
- Wired Remote Controller - RBC-AMT32UL
- Filter Box / 2" MERV8 (TCB-FB2F241VDGUL)
- Plenum TCB-PL2S241VDGUL
- Electrical Heater (240V / 208V):

1.0kW/0.8kW	TCB-HT101VDGUL
3.0kW/2.3kW	TCB-HT301VDGUL
5.0kW/3.8kW	TCB-HT501VDGUL
6.0kW/4.5kW	TCB-HT601VDGUL

NOTES:

- * Does not include electric heater
- † Average / weighted sound values

Manufacturer reserves the right to discontinue, or change at any time, specifications or designs without notice and without incurring obligations.

Dimensional Drawing Indoor Unit Vertical Air Handler MMD-AP0240VHG2UL

