

SMMSi / SHRMi VRF Indoor Unit MMU-AP0122H2UL - 4-Way Cassette

TOSHIBA
Carrier

Submittal Data

Job Data _____ Location _____
Buyer _____ Buyer PO # _____ Carrier # _____
Unit Number _____ Model Number _____
Performance Data Certified By _____ Date _____



SMMSi / SHRMi VRF 4-Way Cassette Features

- R-410A Refrigerant
- Ten sizes from 7,500 to 42,000 Btu/h
- Optional fresh air intake
- Quiet operation, as low as 31 dBA
- Standard condensate pump with 26 inch lift capability
- Independent louver control (fixed or swing)
- Optional wired or wireless controls
- Auto or manually set three fan speeds
- Easy to remove cleanable filter
- Five-year parts limited warranty

Indoor Unit Model	MMU-AP0122H2UL	
PERFORMANCE		
Cooling Rated Capacity	Btu/h	12,000
Heating Rated Capacity	Btu/h	13,500
Fan Type (Qty)		Turbo (1)
Airflow (L / M / H)	CFM	460 / 490 / 550
Sound Pressure (L / M / H)	dBA	31 / 33 / 34
ELECTRICAL		
Power Supply	V/Ph/Hz	208-230/1/60
Power Consumption (Input)	kW	0.023
Full Load Amps (FLA)	A	0.6
Minimum Circuit Amps	A	0.8
Maximum Overcurrent Protection	A	15
Motor Type	DC Inverter Driven	
Motor Watts		60

PHYSICAL DATA		
Pipe Connection Size - Liquid (High Pressure)	in.	1/4 (Flare)
Pipe Connection Size - Gas (Low Pressure)	in.	3/8 (Flare)
Pipe Connection Size - Drain (OD)	in.	1-1/4
Pipe Connection Size - Drain (ID)	in.	1
Refrigerant	R-410A	
External Finish	Munsell 2.5GY9.0/0.5	
Unit Width	in.	33-1/8
Unit Height	in.	10-1/8
Unit Depth	in.	33-1/8
Unit Net Weight	lb	46
Panel Width	in.	37-3/8
Panel Height	in.	1-3/16
Panel Depth	in.	37-3/8
Panel Net Weight	lb	10

ACCESSORIES (Optional)

- | | |
|--|---|
| ☐ Lite Vision Plus Remote Controller (7-Day Programmable) RBC-AMS51E-ES | ☐ Wired Remote Controller RBC-AMT32UL |
| ☐ Simple Wired Remote Control RBC-AS41UL | ☐ Grille Panel RBC-U31PG(W)-UL |
| ☐ Stand-Alone Receiver with Wireless Remote RBC-AX32U(W)-UL | ☐ Spacer for Height Adjustment TCB-SP1602UUL |
| ☐ Stand-Alone Receiver with Wireless Remote TCB-TC41UL | ☐ Air Discharge Direction Kit TCB-BC1602UUL |
| ☐ Remote Sensor TCB-TC41LUL | ☐ Fresh Air Chamber TCB-GFC1602UUL |
| | ☐ Fresh Air Inlet Box TCB-GB1602UUL |
| | ☐ Auxiliary Fresh Air Flange TCB-FF101URUL |

Manufacturer reserves the right to discontinue, or change at any time, specifications or designs without notice and without incurring obligations.

DIMENSIONAL DRAWING INDOOR UNIT 4-WAY CASSETTE MMU-AP012H2UL

