

## EXTREME™ SELF LIGHTING REPLACEMENT TIPS

Increase the range of your torch kit with additional self lighting tips. All TurboTorch® tips feature an orifice screw that can be easily removed for simple cleaning or replacement, extending the life of the tip.



**PL-3A**  
(0386-0874)



**PL-5A**  
(0386-0818)



**PL-8A**  
(0386-0819)



**PL-12A**  
(0386-0820)



**3A-TE**  
(0386-1059)



**5A-TE**  
(0386-1064)



**8A-TE**  
(0386-1065)



**12A-TE**  
(0386-1066)

Tip No.	Tip Size		Gas Flow		Soft Solder		Silver Solder		Replacement Orifice		Replacement Tip	BTU
	IN.	MM	@14 PSI SCFH	(0.9 BAR) M3/HR	IN.	MM	IN.	MM				
PL-3A	3/16	5.0	3.6	0.108	1/4-1	10-25	1/8-1/2	3-12	OR-A3	0386-1001	3A-TE	1,280
PL-5A	1/4	6.4	5	0.15	3/4-1 1/2	20-40	1/4-3/4	10-20	OR-A8	0386-1003	5A-TE	2,080
PL-8A	5/16	7.9	7	0.21	1-2	25-50	1/2-1	15-30	-	0305-0511	8A-TE	2,520
PL-12A	3/8	9.5	9	0.27	2-4	50-90	1-2	25-50	OR-T-6	0386-1024	12A-TE	3,360