

REFRIGERANT

RECOVERY

SMALL RECOVERY

LARGE RECOVERY



SPECIFICATIONS

STANDARD

| MODEL | 30 LBS | 50 LBS | 123 LBS | 239 LBS | 1,000 LBS |
|-------------------------------|-------------------|-------------------|-------------------|-------------------|-------------------|
| HEIGHT (IN) | 17.7 | 18.8 | 54.8 | 48.7 | 57.3 |
| WATER CAPACITY (LBS) | 26.2 | 47.7 | 123 | 239 | 1,000 |
| NOMINAL TARE WEIGHT (LBS) | 17 | 27.8 | 58 | 78.5 | 334 |
| CYLINDER DIAMETER (IN) | 9.1 | 12.3 | 10 | 14.7 | 30 |
| CYLINDER VOLUME (CU. IN) | 726 | 1,324 | 3,405 | 6,515 | 27,680 |
| COLLAR DIAMETER (IN) | 6.5 | 6.5 | 3.9 | 11.4 | 16 |
| COLLAR HEIGHT (IN) | 5.1 | 5.1 | - | 6.4 | 6.9 |
| FOOTRING DIAMETER (IN) | 7.8 | 7.8 | 10 | 14.5 | 22 |
| STANDARD SPECIFICATION | DOT-4BA400 | DOT-4BA400 | DOT-4BW400 | DOT-4BW260 | DOT-4BW260 |
| SERVICE PRESSURE (PSIG) | 400 | 400 | 400 | 260 | 260 |
| TEST PRESSURE (PSIG) | 800 | 800 | 800 | 520 | 520 |
| OPTIONAL SPECIFICATION | - | - | - | DOT-4BW400 | DOT-4BW400 |
| SERVICE PRESSURE (PSIG) | - | - | - | 400 | 400 |
| TEST PRESSURE (PSIG) | - | - | - | 800 | 800 |

All tare weights and dimensions are approximate.

To convert to refrigerant capacity:

Maximum allowable gross cylinder fill weight is 0.8 x water capacity x specific gravity of the refrigerant recovered @ 77°/25°C + cylinder tare weight.

Cylinder photos are not shown to scale.

REFRIGERANT

RECOVERY

SMALL RECOVERY

LARGE RECOVERY



SPECIFICATIONS

METRIC

| MODEL | 30 LBS | 50 LBS | 123 LBS | 239 LBS | 1,000 LBS |
|-------------------------------|-------------------|-------------------|-------------------|-------------------|-------------------|
| HEIGHT (MM) | 449.5 | 477.5 | 1,392 | 1,237 | 1,455 |
| WATER CAPACITY (KG) | 11.9 | 21.6 | 55.8 | 108.4 | 450 |
| NOMINAL TARE WEIGHT (KG) | 7.7 | 12.6 | 26.3 | 35.6 | 151.5 |
| CYLINDER DIAMETER (MM) | 231.1 | 312.4 | 254 | 373.4 | 762 |
| CYLINDER VOLUME (L) | 11.9 | 21.6 | 55.8 | 108.4 | 450 |
| COLLAR DIAMETER (MM) | 165.1 | 165.1 | 98.4 | 289.6 | 406.4 |
| COLLAR HEIGHT (MM) | 130 | 130 | - | 163 | 175 |
| FOOTRING DIAMETER (MM) | 198.1 | 198.1 | 254 | 368.3 | 558.8 |
| STANDARD SPECIFICATION | DOT-4BA400 | DOT-4BA400 | DOT-4BW400 | DOT-4BW260 | DOT-4BW260 |
| SERVICE PRESSURE (BAR) | 28 | 27 | 27 | 18 | 18 |
| TEST PRESSURE (BAR) | 55 | 54 | 54 | 36 | 36 |
| OPTIONAL SPECIFICATION | - | - | - | DOT-4BW400 | DOT-4BW400 |
| SERVICE PRESSURE (BAR) | - | - | - | 27 | 27 |
| TEST PRESSURE (BAR) | - | - | - | 54 | 54 |

All tare weights and dimensions are approximate.

To convert to refrigerant capacity:

Maximum allowable gross cylinder fill weight is 0.8 x water capacity x specific gravity of the refrigerant recovered @ 77°/25°C + cylinder tare weight.

Cylinder photos are not shown to scale.